



MARKSUSA

2026/2027

Price List

**Mortise Locksets, Cylindrical,
Tubular, Electronic,
Exit Devices, &
Access Control Locksets**



Effective July 1, 2026

GENERAL INFORMATION

TABLE OF CONTENTS

Terms & Conditions	5
Required Information	6
Backset	6
Door Thickness	6
Handing	6
Mounts & Displays	6

MORTISE LOCKSET PRICE LIST

Mortise Lock Trim Information	7
Lever/Knobset Trim	7
How To Order Mortise Locksets	8
Option Codes	9-10
Plate Designs	11-20
Classic - CL	11-12
Capitol - CP	13
Crown - CR	14-15
Drake - DR	16-17
LA - LA	18-19
New Yorker - NY	20-21
Rose Designs	22-23
Rose with Ring - RR	22-23
Plain Rose - RW	22-23
Small Rose with Ring - RQ	22-23
Small Rose - RS	22-23
Square Rose (Wrought) - RX	22-23
Square Rose (Forged) - RK	22-23
Square Rose with Corner Screws - RL	22-23
Ornamental Iron	24-25
Series 21 Unilock™	24
Series 22	24
Series 9215 Unilock™	24
Series 9225	24
THINLINE® Series 2750	24
Knob & Lever Kits	25
Accessories	25
Cylinders	25
Mortise Parts & Trim	26-37
Mortise Lock Bodies Series 5 & 55	26
Mortise Lock Bodies Series 6 & 8	27
Mortise Lock Bodies Series 7 & 9	28
Mortise Deadlocks Series 31, 2, 3, 5 & 55	29
Mortise Lockset Functions	30-31
Mortise Lock Parts: Knob/Lever Rose Kits	32
Mortise Lock Parts: Collars & Turnpieces, Strikes, Spindles	33
Mortise Lock Parts: Indicators	34
Trim Lock Parts: Plate/Rose Design	35-36
Trim Lock Parts: Knob/Lever Design	37

CYLINDRICAL & TUBULAR LOCKSET PRICE LIST

How To Order Cylindrical Locksets	38
Series	38
Cylindrical Functions	38
Finishes	38
Options	38
Cylindrical Locksets	39-41
10 Line Grade 2 Cylindrical Knobsets	39
95 Line Grade 1 Cylindrical Survivor Series Leversets	40
75 Line Grade 2 Cylindrical Survivor Series Leversets	41
Cylindrical Lock Accessories	42-43
Latches, Strikes, Spacer Rings, Etc.	42
Cylinders, Cylindrical Lock Tailpieces, Cylindrical IC Core Tailpieces	43
How to order example for Cylindrical Lock Cylinders & Tailpieces	43
Cylindrical Knob/Lever Functions	44
How To Order Tubular Lockset	45
Series	45
Roses44	
Knob/Lever	45
Tubular Function	45
Finishes	45
Options	45
Tubular Knob & Lever Functions	45
Rose Designs	46
Rose with Ring - RR	46
Plain Rose - RW	46
Small Rose with Ring - RQ	46
Small Rose - RS	46
Square Rose (Wrought)- RX	46
Square Rose (Forged) - RK	46
Square Rose with Corner Screws- RL	46
60 Series Stainless Tubular Locksets	47
160 Series Copa Lever	47
260 Series Commerce Lever	47
360 Series Maxwell Lever	47
Tubular Lockset Accessories	48
Strikes, Latches, Support Housing	48
Turnpieces	48
Latches & Cylindrical Cartridge	48
How To Order For Defender Locksets	49
Series	49
Deadbolt/Deadlatch Functions	49
Finishes	49
Options	49
Defender Series Tubular Deadbolts & Cylindrical Cartridge Deadlatch	50
130 Series Defender Tubular Deadbolts	50
145 Series Grade 1 Defender Cylindrical Cartridge Deadlatches	50
Defender Series Accessories	51
Strikes, Latches & Spacers	51
Latches & Cylindrical Cartridge	51
Tailpieces & Cylinders	51

ELECTRIFIED LOCKSETS AND BASIC ACCESS CONTROL

Request To Exit (REX) Leversets & Electrified Locksets	52
Request To Exit (REX) Cylindrical Grade 1 Leversets (EA195, EA295, EA395 & EA495)	52
How To Order Example For REX Leversets	52

WOVEN WIRE LOCKSETS

Gate Locks	53
Swinging Gate Locks	53
Sliding Gate Locks	53
Parts.....	53

CUSTOM AND SPECIALTY LOCKSETS

Housing Authority	54
Series HA113 Housing Authority Mortise Lockset	54
School Lockdown	55-57
Series LA318GJ & LA318GS Maximum Security Mortise Lockset.....	55
Series BE101 & LA118	56
Specialty lokdown	57
Behavioral Life Safety	58-65
Series 195BH D-Lig Slide Cylindrical Lockset	58
Series 5BH D-Lig Slide Mortise Lockset	59
Series 195SS Institutional Life Safety Cylindrical Lever Lockset	60
Series 5SS19 Institutional Life Safety Mortise Lever Locksets	61
Series 31SS55 Institutional Life Safety Mortise Deadlock	62
Hospital Locksets	63
Series 180PD Cylindrical Push/Pull Paddlesets	63
Series 5PD & 55PD Mortise Push/Pull Paddlesets	63

HI-SECURITY™

Mortise Lock Cylinders	64
Keys & Keying	65
Hi-Security™ Cylinders.....	66
Security-Mate™ Cylinders, Special Application Cylinders.....	67
How To Order HI-SECURITY™ Cylinders and Keys	68
Keys, Cams & Tailpieces	69
Parts List.....	70

EXIT PANIC EXIT DEVICES

Series M9900 Exit Device - Rim Mount	71
Series M9900 VR Exit Device - Surface Vertical Rod	71
Series M9900 Exterior Trim	72
Series M8800 Exit Device.....	73
Series M99LD School Lockdown Exit Device with Trim	73
Series M195 Exterior Trim	74
Series M99 Night Latch Trim	74
Electric Latch Retraction with Simultaneous Dogging	75
Exit Alarm	75
Electric Dogging	76
Delayed Egress	76

NEW! SMART DEADBOLT & INTERCONNECTED DEADBOLT

Smart Deadbolt & Interconnected Deadbolt	77-79
Standalone Series NDB & Interconnect Series NIC.....	78
How to Order.....	79
MVP EZ, MVPAccess & CA4Kv1.2	79

MVP EZ & MVP Access	79
---------------------------	----

ArchiTech™ SERIES NETWORKX LOCKS

ArchiTech™ Series Networkx Locks	80
Electronic options	81
ArchiTech™ Cylindrical Locks	82
Price Builder	82
Trim options	82
How to Order	82
ArchiTech™ Mortise Locks	83-84
Price builder	83
Trim options	83
Functions	83
How to Order	84
ArchiTech™ Availability Chart	84
ArchiTech™ Parts and Accessories	85
iLock® App	85

Marks USA Antimicrobial Finish: Peace of mind for your hardware application when protected against GERMS and MOLD using Stericoat AM. Marks USA antimicrobial finish is recommended for hospitals, assisted living facilities, schools and childcare facilities. **Use Code - AM**

Lifetime Mechanical Limited Warranty: MARKS USA warrants that its products are free from defects in materials and workmanship.

This warranty is limited to the lifetime of the door on which our lock is installed to the original purchaser so long as they occupy the premises. In the event our product does not conform to this warranty, MARKS USA will repair or replace the product free of charge. This warranty does not cover defects or damage arising from improper installation, lack of or improper maintenance, improper storage, shipping and handling, ordinary wear and tear, misuse, abuse, accident, unauthorized service, or use with unauthorized non-MARKS products or parts. We reserve the right to make changes in materials, components or manufacturing methods. Liability under all warranties expressed or implied is limited to replacement of the defective goods. This warranty does not cover nor provide for the reimbursement or payment of incidental or consequential damages. Additionally, the company will not warrant ANSI A156.2 Grade 2 lever product installed in educational facilities and student housing. The following exclusions are Mortise Lock Trims, Exit Trims, Metro Series, Ornamental Iron, Cylinders, Key Blanks, and Parts.

2 Year Electronic Limited Warranty: MARKS USA warrants to the original purchaser that its products are free from defects in materials and workmanship so long as they occupy the premises.

In the event our product does not conform to this warranty, MARKS USA will repair or replace the product free of charge at its sole discretion. This warranty does not cover defects or damage arising from improper installation, lack of or improper maintenance, improper storage, shipping and handling, improper application or specification, ordinary wear and tear, misuse, abuse, accident, improper voltage, unauthorized service, or use with unauthorized non-MARKS products or parts. We reserve the right to make changes in materials, components or manufacturing methods. Liability under all warranties expressed or implied is limited to replacement of the defective goods. This warranty does not cover nor provide for the reimbursement or payment of incidental or consequential damages or any shipping charges related to exercising of this warranty.

TERMS & CONDITIONS:

TERMS: Net 30

FREIGHT: Prices are F.O.B. Amityville, New York. Freight allowed on shipments over \$7500 net invoice value within Continental U.S.

RETURNED GOODS: Goods may not be returned without a Returned Goods Authorization (RGA) and are subject to a restocking charge. RGA label must be on all cartons.

MINIMUM CHARGE: Orders for less than \$250 net invoice are subject to a \$25 handling charge.


MINIMUM SALES VOLUME: The company reserves the right to discontinue direct sales to any customer who does not meet the minimum annual sales requirements during any 12 month period. Minimum annual sales volume is determined on the basis of accepted orders during each applicable year. All orders are acknowledged. It is the customers responsibility to check accuracy of the acknowledgment when received.

ArchiTech, Networkx, iLock, CA4K, MVP EZ, MVP Access, LifeSaver and Hi-Security are trademarks of Napco Locking Solutions, a division of NAPCO Security Technologies. All other trademarks listed are properties of their respective companies.

Effective September 1, 2025. All prices published are suggested list prices in US Dollars. Some specifications are preliminary & subject to change without prior notice (Subsequent Tariffs/Surcharges May Apply.). Not responsible for typographical errors.

Marks USA is a Division of Napco Security Technologies, Inc. (NASDAQ:NSSC) © NAPCO 9.1.25

BACKSET - Required Information




DOOR THICKNESS - Required Information

STANDARD DOOR THICKNESS RANGE:

Mortise locksets: 1-3/4"
Cylindrical locksets: 1-5/8" through 1-7/8"
Ornamental locksets: 1" through 1-1/4"
Tubular locksets: 1-3/8" through 1-3/4"
Other door thickness: Consult factory


SPECIFY:

Door thickness (A)
Lock location (B)



HANDING - Required Information

All locksets supplied 1/2 (LH) and 1/2 (RH) unless otherwise specified



MOUNTS & DISPLAYS AVAILABLE, CONSULT FACTORY

1RW78N/26D



1RR57N/15



5DR72FD/26



5RW96LF/26D-A21




1PDN/32D




MORTISE LOCK TRIM INFORMATION

LEVERSET/KNOBSET TRIM




Outside Inside

ENTRANCE
Cylinder/
Turnpiece




Outside Inside

ENTRANCE
Double Cylinder




Outside Inside

OFFICE/CLASSROOM




Outside Inside

PRIVACY



Outside Inside

EXTERIOR/PATIO



Outside Inside

DUMMY TRIM
Both sides

HOW TO ORDER MORTISE LOCKSETS

1. Select type of lockset.
2. See corresponding pages in the catalogs for information regarding this type of lock.
3. Create the part number for your lock by selecting the information from fields 1 through 6.
Please note dummy trim is Series "0".
4. Options must be listed in Alpha - Numeric order.
5. Note that if Part Number is over 15 characters, it becomes a special number with the option field *1.
(Your options will then be listed separately.)
Please note the standard (default) features of each lock - they do not need to be selected in the options section.
6. Please indicate keying detail or special instructions on each item ordered.
7. Door Templates are available by email request to marksorders@marksusa.com

How To Order Example for Mortise Locksets	7	NY	10	A	/	3	-	G3
	1. Lock Series	2. Plate/Rose Design	3. Knob/Lever Design	4. Marks Function	Slash	5. Finish	Dash	6. Options

How To Order Example for Rose Design	5	RW	92	N	/	10B	-	D1
	1. Lock Series	2. Plate/Rose Design	3. Knob/Lever Design	4. Marks Function	Slash	5. Finish	Dash	6. Options

How To Order Example for Ornamental Iron	9215	AC	/	26D	-	D4
	1. Series	2. Marks Function	Slash	3. Finish	Dash	4. Options

How To Order Example for Mortise Lock Bodies	55	JM	/	26D	-	T
	1. Series	2. Marks Function	Slash	3. Finish	Dash	4. Options

How To ORDER

OPTION CODES

TRIM MODIFICATIONS	CODE	PRICE	TYPE
Tactile knob/lever, coated ext. only	A1	38	M,C,T
Emergency coinkey	A2	18	M
Tamper-proof screws	A3	10	M
Tactile knob/lever, knurled	A4	38	M,C,T
Handicapped turnpiece	A5	12	M
Hotel indicator	A6	28	M
Pinned knob	A7	23	M
Mushroom knob	A9	4	M
No logo	A10	NC	
Engraved	A11	45	M
Concealed cylinder	A12	17	M
Dummy trim sub-assembly	A13	NC	M
Coinkey w/ rose	A15	45	M
Occupancy Indicator non keyed	A17	58	M
Tactile knob/lever, coated int. & ext.	A18	78	M
Square trim	A23	19	M
Square collar	A23C	11	M
Square turnpiece	A23T	11	M
Small emergency hole	A24	NC	M
Recessed Pull (one side)	A28	45	M,C
Exposed Rose Screws	A29	NC	M,T
Engraved and Filled	A30	83	M
No inside turnpiece	A32	NC	M
Red/Green TD Occ ind no coin key	A40	114	M
A9618-Atascadero	A41	74	M
Red/Green TD Occ ind w/ coin key	A42	114	M
SKA200 Handed (All Trims)	A50	205	M
SKA200-CK Handed w/Coin key (Rose Trims Only)	A51	205	M
SKA200-TP (All Trims) Handed w/ Turn Pc	A52	205	M
SKA210 Handed (All Trims)	A53	205	M
SKA210-CK Handed w/Coin key (Rose Trims Only)	A54	205	M
SKA210-TP Handed w/ Turn Pc (Rose Trims Only)	A55	234	M
Phillip Head Screws Only	A56	NC	M,C

CYLINDER	CODE	PRICE	TYPE
SFIC Housing (6 or 7 Pin)	G1	NC	M
Special optional keyway	G2	24	M,C
Less cylinder	G3	Deduct 10	M,C
MARKS "A" keyway	G4	10	M
MARKS "C" keyway	G5	11	O
SFIC Housing w/9271 Collar (6 Pin)	G6	NC	M
IC core housing, Schlage large format (FOR MORTISE ONLY)	G7	51	M
No Cylinder, no key bypass	G8	NC	A
IC Housing, Sargent Large format	G9	38	M
Oversized recessed Cyl bore sgl or dbl less Cyl	G10	18	M
T-Turn in lieu of keyed cylinder	G12	NC	E

MOUNTS	CODE	PRICE	TYPE
M6500 Mounted mort. prep 2-3/4" bs	M1		
M6500 Mounted 2-1/2"	M2		
ME100M Mounted I Que prep	M3		
Mounted 3 hole prep	M4		
M1319 Mounted cyl/deadbolt prep	M6		
M295 Mounted Plastic	M7		
M1900 Mounted 2-1/8" prep	M8		
Mounted Panic Devices	M10		
5001PL Plastic Mortise Cover	M11		

STRIKE	CODE	PRICE	TYPE
4-7/8" ASA strike	S1	9	C,T
Straight lip strike	S2	3	M
2-3/4" "T" strike	S3	NC	C,T
3-5/8" x 1-1/4" Security strike	S4	8	T
2-1/4" Curved lip strike	S5	NC	T
4-7/8" Strikes: 1 Left / 1 Right	S6	9	INT
Strike with 1-1/2" lip	S7	11	M
Radius corner strike	S8	NC	M
4035-1 strike	S9	NC	M
1-7/8" Lip Strike	S10	NC	C,T
Square corner Full Lip Strike	SQ	NC	T

LOCK BODY	CODE	PRICE	TYPE
Lever override guard - outside	B1	28	M
Lever override guard - both sides	B2	40	M
Hardened pins - deadbolt	B3	12	M
Lever springs	B4	13	M
Pin and lever springs	B5	24	M
Hollow spacer	B6	12	M
8 mm hubs on square	B7	12	M
Turnpiece hub on square	B8	8	M
With deadbolt	B9	12	M
Boxed Lock Body	B10	NC	M
Lever spring outside only	B11	NC	M
Lever spring Inside only	B12	NC	M
Special Deadbolt Unnotched	B13	NC	ORN

LOCK FRONT	CODE	PRICE	TYPE
1-1/16" x 8"	Q	17	M
1-1/16" x 5-5/8"	R	18	M
1-1/16" x 7-5/8"	T	17	M
1-1/4" x 10"	U	69	M
1-1/16" x 7-3/4"	V	17	M
1" x 7-1/8"	W	NC	M
1-1/4" x 8"	X	16	M
1-1/4" x 8-5/8"	Y	69	M
1" x 8"	Z	16	M

DOOR THICKNESS	CODE	PRICE	TYPE
2"	D1*	NC	C
2-1/4"	D2*	48	C
1-3/4"	D4	NC	M
1-3/8"	D5	NC	M
Over 2-3/8 - 4" Cylindrical	D9*	409	A,C
2" - 4" Door Thickness	D14	253	M

CYLINDRICAL 18-20 WEEKS

**Prices are for centered on door. For offset, call for price.*

How To Order

OPTIONS & FINISHES

TRIM CHANGES	CODE	PRICE	TYPE
Lead lined	F1	366	M,C
Large inside plate	F2	23	M
Less inside trim	F4	NC	M
Less outside trim	F5	NC	M
For 1-1/2" bore	F6	13	T
Yale/Accentra Conventional cylinder	F7	15	M
Sargent Conventional cylinder	F8	15	C
Corbin Conventional cylinder	F9	15	C
Adjustable spring collars	F10	4	M
Corbin Russwin 6 pin IC core	F12	22	C
Corbin Russwin 7 pin IC core	F13	22	C
Yale/Accentra 6 pin IC core	F14	15	C
Yale/Accentra 7 pin IC core	F15	15	C
Less outside knob/lever	F16	NC	M
Less trim with custom escutcheon	F18	NC	M
Schlage 6 pin IC core	F19	15	C
Sargent IC core	F20	15	C
Medeco IC core large format	F21	15	C
Blank inside plate/lever	F25	NC	M
Blank outside plate/lever	F26	NC	M
Yale/Accentra 6 pin IC core w/captivated tail	F27	15	C
Yale/Accentra 710 IC core w/ captivated tail	F28	15	C
Screwless interior escutcheon	F29	38	M

LATCH	CODE	PRICE	TYPE
Solid latch	E1	13	M
Open hold open latch	E2	24	M
Auxiliary latch	E3	23	M
2-3/4" backset, 1-1/8" x 2-1/4" face	E4	8	C,T
2-3/8" back set, 1" x 2-1/4" face	E6	NC	C,T
2-3/4" BS, 9/16" throw, Gr. 1 UL	E7	30	C
2-3/4" BS, 9/16" throw, Gr. 1			
UL listed with cylindrical cartridge *E7 option N function only, 2-3/4BS	E7*	68	T
2-3/8", 2-3/4", 3-3/4" & 5" Backsets			
5" bs, 9/16" throw, Gr. 1 UL	E9	30	C,T
3-3/4" BS, 9/16" throw Gr. UL	E10	30	C
2-3/8" backset, 1-1/8" x 2-1/4" face	E11	9	C,T
2-3/4" backset, 1" x 2-1/4" face	E12	9	C,T
Adjustable latch 1-1/8" x 2-1/4" face	E13	8	T
Adjustable latch 1" x 2-1/4" face UL	E14	12	T
Radius corners on tubular	E15	NC	T
UL latch, adjustable	E16	10	T
Kick off latch (P) 1834P	E17	NC	C

ELECTRIFIED	CODE	PRICE	TYPE
24V	H1	NC	C, M
12V	H2	NC	C, M
Electrically locked (EL)	H9	NC	M
Electrically unlocked (EU)	H10	NC	M

ELECTRONICS	CODE	VALUE	TYPE
Request to exit switch	W10	101	M
Key sensor	W11	101	A,C
Titan lever	W12	13	IQ
REX switch, key bolt sensor	W13	303	M
Bolt sensor	W14	101	M
Latch sensor	W15	101	M
REX + Latch Sensor	W16	203	M

FINISHES	ANSI #
US 3 Polished Brass, Clear Coated	605
US 4 Satin Brass, Clear Coated	606
US 5 Antique Brass, Clear Coated	609
US 10 Satin Bronze, Clear Coated	612
US 10B Dark Bronze, Clear Coated	613
US 14 Bright Nickel Plating, Clear Coated	614
US 15 Satin Nickel	619
US 19 Flat Black, Powder Coated	622
US 20A Dark Oxidized Statuary Bronze, Clear Coated	624
US 26 Polished Chrome, Plated	625
US 26D Satin Chrome, Plated	626
US 32 Polished Stainless Steel	629
US 32D Satin Stainless Steel	630




AM	Antimicrobial Finish	AM, +200
-----------	-----------------------------	-----------------

CLASSIC PLATE DESIGN CL

	ANSI-A156.13 • Grade 1 3 Hour Fire Rating			Series 5 • 2-3/4" Backset Series 55 • 2-1/2" Backset	
	Standard Features			KNOBS	LEVERS
	• Thru-bolted screwless knob/lever plate assemblies • Independent spring loaded captivated spindles • Reversible mortise lock 2-1/2" or 2-3/4" backset • Lock front: 1-1/4" x 8" • Dimensions: Ext: 8" H x 2-1/2" W, Int: 8" H x 2-1/2" W • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys • Height: 7/32" Options available on page 9-10			10, 20	002, 031, 44, 47C, 55, 57, 72, 77, 78, 82, 86, 92, 96,
				FINISH GROUPS	
MARKS #	FUNCTION	ANSI #	32D	32D	
KEYED SINGLE CYLINDER, NO DEADBOLT					
D	OFFICE VEST.		495.26	611.42	
DW	VESTIBULE				
E, K	OFFICE	F04			
EW	STOREROOM	F07			
J	CLASSROOM	F05			
JM, JR	HOSPITAL	F06			
GL	INSTIT. PRIVACY	F26	751.13	866.50	
EL	ELECTRICALLY LOCKED				
EU	ELECTRICALLY UNLOCKED				
KEYED SINGLE CYLINDER, WITH DEADBOLT					
A	ENTRANCE	F08, F10	506.24	622.41	
B	ENTRANCE	F21			
F	DORMITORY	F12			
FS	DORMITORY				
FW	DORMITORY	F13	556.48	671.85	
FD	APARTMENT	F20			
H	HOTEL	F15			
LH	SPECIAL PRIVACY				
KEYED DOUBLE CYLINDER, NO DEADBOLT					
G	APARTMENT	F09	533.72	649.09	
GC	INTRUDER LATCHBOLT	F32			
GG	CLASSROOM SECURITY				
GR	CLASSROOM SECURITY w/HOLDBACK				
WW	INSTITUTIONAL	F30	533.72	649.09	
AC	ENTRANCE	F35			
C	STOREROOM	F14			
FC	INTRUDER DEADBOLT	F34			
FA	DORMITORY	F11			
FX	DORMITORY	F33			
KEYLESS					
N	PASSAGE	F01	415.99	532.15	
L	BATHROOM	F02	507.81	623.19	
LF, LJ	PRIVACY	F19, F22			
EX	EXIT	F31	458.37	573.74	
DUMMY TRIM					
DI	DUMMY TRIM INSIDE		209.56	266.85	
DO	DUMMY TRIM OUTSIDE				
DT	FULLY DUMMY		416.76	532.93	
KNOBS & LEVERS ARE PACKED 6 PER CASE					
NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory					

CLASSIC PLATE DESIGN CL

	ANSI-A156.13 • Grade 2		Series 7 • 2-3/4" Backset Series 9 • 2-1/2" Backset	
	Standard Features		KNOBS	LEVERS
	• Thru-bolted screwless knob/lever plate assemblies • Independent spring loaded captivated spindles • 2-1/2" or 2-3/4" backset • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys • Lock front Series 7: 1-1/4" x 8", Series 9: 1-1/16" x 7-5/8" • Dimensions: Ext: 8" H x 2-1/2" W, Int: 8" H x 2-1/2" W Options available on page 9-10		10, 20	031, 037A, 44, 47C, 55, 57, 72, 77, 78, 82, 86, 92, 96, 002
			FINISH GROUPS	
MARKS #	FUNCTION	ANSI #	32D	32D
KEYED SINGLE CYLINDER, NO DEADBOLT				
D	OFFICE VEST.		469.36	585.52
DW	VESTIBULE			
KEYED SINGLE CYLINDER, WITH DEADBOLT				
A	ENTRANCE	F08, F10	481.13	596.51
B	ENTRANCE	F21		
F	DORMITORY	F12		
FS	DORMITORY			
FW	DORMITORY	F13		
KEYED DOUBLE CYLINDER, WITH DEADBOLT				
AC	ENTRANCE	F35	508.60	623.98
C	STOREROOM	F14		
FX	DORMITORY	F33		
KEYLESS				
N	PASSAGE	F01	390.09	506.24
L	BATHROOM	F02	481.91	597.29
LF	PRIVACY	F19		
DUMMY TRIM				
DI	DUMMY TRIM INSIDE		209.56	266.85
DO	DUMMY TRIM OUTSIDE			
DT	FULLY DUMMY		416.77	532.93
KNOBS & LEVERS ARE PACKED 6 PER CASE				
NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory				

KNOB	Round Knob 10	Ball Knob 20	Commerce Lever 037A	Metropolitan Lever 002
				
LEVER	Lucida Lever 47C	Copa Lever 031	Brompton Lever 55	Monaco Lever 57
				
	Towne Lever 72	Maxwell Lever 77	Omni Lever 78	Plaza Lever 82
				
	Dayton Lever 83 Specify handing	Crescent Lever 86	American Lever 92	Titan Lever 96
				

CAPITOL PLATE DESIGN CP

		ANSI-A156.13 • Grade 1 3 Hour Fire Rating				Series 5 • 2-3/4" Backset Series 55 • 2-1/2" Backset	
	Standard Features			KNOBS		LEVERS	
	• Thru-bolted screwless knob/lever plate assemblies • Independent spring loaded captivated spindles • Reversible mortise lock 2-1/2" or 2-3/4" backset • Lock front: 1-1/4" x 8" • Dimensions: Ext: 8-1/2" H x 2-3/4" W, Int: 8-1/2" H x 2-3/4" W • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys • Concealed 5 pin cylinder (option A12) • Thickness: 1/8" Options available on page 9-10			10, 20		002, 031, 037A, 47C, 55, 57, 72, 77, 78, 82, 86, 92, 96,	002, 031, 037A, 47C, 82, 83, 86, 92, 96
				FINISH GROUPS			
MARKS #	FUNCTION	ANSI #	3, 32D	10B, 15, 19	3, 32D	4, 10, 10B, 15, 19	
KEYED SINGLE CYLINDER, NO DEADBOLT							
D	OFFICE VEST.		515.66	545.49	631.04	671.36	
DW	VESTIBULE						
E, K	OFFICE	F04					
EW	STOREROOM	F07					
J	CLASSROOM	F05					
JM, JR	HOSPITAL	F06					
GL	INSTIT. PRIVACY	F26	771.53	801.36	886.91	804.69	
EL	ELECTRICALLY LOCKED						
EU	ELECTRICALLY UNLOCKED						
KEYED SINGLE CYLINDER, WITH DEADBOLT							
A	ENTRANCE	F08, F10	526.65	557.26	642.82	672.64	
B	ENTRANCE	F21					
F	DORMITORY	F12					
FS	DORMITORY						
FW	DORMITORY	F13					
FD	APARTMENT	F20	576.10	605.92	692.26	722.87	
H	HOTEL	F15					
LH	SPECIAL PRIVACY						
KEYED DOUBLE CYLINDER, NO DEADBOLT							
G	APARTMENT	F09	554.91	584.73	670.28	700.11	
GC	INTRUDER LATCHBOLT	F32					
GG	CLASSROOM SECURITY						
GR	CLASSROOM SECURITY w/HOLDBACK						
WW	INSTITUTIONAL	F30					
KEYED DOUBLE CYLINDER, WITH DEADBOLT							
AC	ENTRANCE	F35	554.91	584.73	670.28	700.11	
C	STOREROOM	F14					
FC	INTRUDER DEADBOLT	F34					
FA	DORMITORY	F11					
FX	DORMITORY	F33					
KEYLESS							
N	PASSAGE	F01	437.18	467.00	553.34	583.16	
L	BATHROOM	F02	528.22	558.05	643.60	673.42	
LF, LJ	PRIVACY	F19, F22					
EX	EXIT	F31	479.56	509.38	594.93	624.76	
DUMMY TRIM							
DI	DUMMY TRIM INSIDE		218.20	233.89	276.27	291.98	
DO	DUMMY TRIM OUTSIDE						
DT	FULLY DUMMY		437.18	467.79	554.12	556.14	
KNObS & LEvERS ARE PACKED 6 PER CASE							
NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory							

KNOBS & LEVERS ARE PACKED 6 PER CASE



NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory

CROWN PLATE DESIGN CR

	ANSI-A156.13 • Grade 1 3 Hour Fire Rating		Series 5 • 2-3/4" Backset Series 55 • 2-1/2" Backset				
	Standard Features		KNOBS		LEVERS		
	• Thru-bolted screwless knob/lever plate assemblies • Independent spring loaded captivated spindles • Reversible mortise lock 2-1/2" or 2-3/4" backset • Lever support springs • Lock front: 1-1/4" x 8" • Dimensions: Ext: 8-1/2" H x 2" W, Int: 8-1/2" H x 2" W • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys • Height: 13/32" • Square Edges Options available on page 9-10		10, 20		002, 031, 037A, 47C, 55, 57, 72, 77, 78, 82, 83, 86, 92, 96 *26D N/A 92, 96, 82,86		002, 031, 037A, 47C, 82, 86, 92, 96
					FINISH GROUPS		
MARKS #	FUNCTION	ANSI #	3, 26D, 32D	10, 10B, 32	3, 15, 26D	4, 10, 10B, 14, 19, 26	32, 32D
KEYED SINGLE CYLINDER, NO DEADBOLT							
D	OFFICE VEST.		532.93	562.75	613.77	673.42	643.60
DW	VESTIBULE						
E, K	OFFICE	F04					
EW	STOREROOM	F07					
J	CLASSROOM	F05					
JM, JR	HOSPITAL	F06					
GL	INSTIT. PRIVACY	F26	788.02	818.63	857.08	916.74	886.91
EL	ELECTRICALLY LOCKED						
EU	ELECTRICALLY UNLOCKED						
KEYED SINGLE CYLINDER, WITH DEADBOLT							
A	ENTRANCE	F08, F10	543.92	573.74	624.76	684.41	654.59
B	ENTRANCE	F21					
F	DORMITORY	F12					
FS	DORMITORY						
FW	DORMITORY	F13	561.19	591.01	642.03	701.68	671.85
FD	APARTMENT	F20					
H	HOTEL	F15					
LH	SPECIAL PRIVACY						
KEYED DOUBLE CYLINDER, NO DEADBOLT							
G	APARTMENT	F09	568.25	598.08	648.31	708.75	678.92
GC	INTRUDER LATCHBOLT	F32					
GG	CLASSROOM SECURITY						
GR	CLASSROOM SECURITY w/HOLDBACK						
WW	INSTITUTIONAL	F30					
KEYED DOUBLE CYLINDER, WITH DEADBOLT							
AC	ENTRANCE	F35	568.25	598.08	648.31	708.75	678.92
C	STOREROOM	F14					
FC	INTRUDER DEADBOLT	F34					
FA	DORMITORY	F11					
FX	DORMITORY	F33					
KEYLESS							
N	PASSAGE	F01	457.59	487.41	538.42	598.08	568.25
L	BATHROOM	F02	543.92	573.74	624.76	684.41	654.59
LF, LJ	PRIVACY	F19, F22					
497.61	528.22	578.46	638.89	609.07	550.91	608.47	580.06
DUMMY TRIM							
DI	DUMMY TRIM INSIDE		228.40	245.66	271.57	316.31	286.48
DO	DUMMY TRIM OUTSIDE						
DT	FULLY DUMMY		461.51	491.33	542.35	602.00	572.17
KNOBS & LEVERS ARE PACKED 6 PER CASE							
NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory							

CROWN PLATE DESIGN CR

	ANSI-A156.13 • Grade 2		Series 7 • 2-3/4" Backset Series 9 • 2-1/2" Backset				
	Standard Features		KNOBS		LEVERS		
	• Thru-bolted screwless knob/lever plate • Independent spring loaded captivated spindles • 2-1/2" or 2-3/4" backset • Lever support springs • Lock front Series 7: 1-1/4" x 8", Series 9: 1-1/16" x 7-5/8" • Dimensions: Ext: 8-1/2" H x 2" W, Int: 8-1/2" H x 2" W • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys - Options available on page 9-10		10, 20		002, 031, 037A, 47C 55, 57, 72, 77, 78, 82, 83, 86, 92, 96		002, 031, 037A, 47C, 82, 86, 92, 96
					*26D N/A 92, 96, 82,86		
		FINISH GROUPS					
MARKS #	FUNCTION	ANSI #	3, 26D, 32D	10, 10B, 32	3, 15, 26D	4, 10, 10B, 14, 19	32, 32D
KEYED SINGLE CYLINDER, NO DEADBOLT							
D	OFFICE VEST.		507.81	537.64	587.88	647.52	617.70
DW	VESTIBULE						
KEYED SINGLE CYLINDER, WITH DEADBOLT							
A	ENTRANCE	F08, F10	518.02	547.84	598.86	658.51	628.68
B	ENTRANCE	F21					
F	DORMITORY	F12					
FS	DORMITORY						
FW	DORMITORY						
KEYED DOUBLE CYLINDER, WITH DEADBOLT							
AC	ENTRANCE	F35	535.37	572.17	623.19	682.84	653.02
C	STOREROOM	F14					
FX	DORMITORY	F33					
KEYLESS							
N	PASSAGE	F01	431.68	461.51	512.53	572.17	542.35
L	BATHROOM	F02	518.02	547.84	598.86	658.51	628.68
LF	PRIVACY	F19					
DUMMY TRIM							
DI	DUMMY TRIM INSIDE		228.40	245.66	271.57	316.31	286.48
DO	DUMMY TRIM OUTSIDE						
DT	FULLY DUMMY		461.51	491.33	542.35	602.00	572.17
KNOBS & LEVERS ARE PACKED 6 PER CASE							
NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory							



KNOBS	Round Knob 10	Ball Knob 20	Commerce Lever 037A	Metropolitan Lever 002
				
LEVERS	Lucida Lever 47C	Copa Lever 031	Brompton Lever 55	Monaco Lever 57
				
	Towne Lever 72	Maxwell Lever 77	Omni Lever 78	Plaza Lever 82
				
	Dayton Lever 83 Specify handing	Crescent Lever 86	American Lever 92	Titan Lever 96
				

DRAKE PLATE DESIGN DR

	ANSI-A156.13 • Grade 1 3 Hour Fire Rating			Series 5 • 2-3/4" Backset Series 55 • 2-1/2" Backset								
	Standard Features		KNOBS		LEVERS							
	• Thru-bolted screwless knob/lever plate • Independent spring loaded captivated spindles • Reversible mortise lock 2-1/2" or 2-3/4" backset • Lever support springs • Lock front: 1-1/4" x 8" • Dimensions: Ext: 11" H x 2-1/2" W, Int: 11" H x 2-1/2" W • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys • Height: 13/32" • Square Edges Options available on page 9-10		10, 20		002, 031,037A, 47C, 55, 57, 72, 77, 78, 82, 83, 86, 92, 96 *26D N/A 92, 96, 82,86		002, 031,037A 47C, 82, 86, 92, 96					
					FINISH GROUPS							
MARKS #	FUNCTION	ANSI #	3, 26D, 32D	10, 10B, 32	3, 15, 26D	4, 10, 10B, 14, 19, 26	32, 32D					
KEYED SINGLE CYLINDER, NO DEADBOLT												
D	OFFICE VEST.		588.66	618.48	669.50	729.15	699.33					
DW	VESTIBULE											
E, K	OFFICE	F04										
EW	STOREROOM	F07										
J	CLASSROOM	F05										
JM, JR	HOSPITAL	F06										
GL	INSTIT. PRIVACY	F26	843.74	873.57	912.81	972.47	942.64					
EL	ELECTRICALLY LOCKED											
EU	ELECTRICALLY UNLOCKED											
KEYED SINGLE CYLINDER, WITH DEADBOLT												
A	ENTRANCE	F08, F10	599.44	629.47	680.49	740.14	710.32					
B	ENTRANCE	F21										
F	DORMITORY	F12										
FS	DORMITORY											
FW	DORMITORY	F13	616.91	646.74	696.97	757.41	727.58					
FD	APARTMENT	F20										
H	HOTEL	F15										
LH	SPECIAL PRIVACY											
KEYED DOUBLE CYLINDER, NO DEADBOLT												
G	APARTMENT	F09	623.98	653.81	704.03	764.47	733.86					
GC	INTRUDER LATCHBOLT	F32										
GG	CLASSROOM SECURITY											
GR	CLASSROOM SECURITY w/HOLDBACK											
WW	INSTITUTIONAL	F30	623.98	653.81	704.03	764.47	733.86					
KEYED DOUBLE CYLINDER, WITH DEADBOLT												
AC	ENTRANCE	F35										
C	STOREROOM	F14										
FC	INTRUDER DEADBOLT	F34										
FA	DORMITORY	F11										
FX	DORMITORY	F33										
KEYLESS												
N	PASSAGE	F01	513.31	543.14	594.15	653.81	623.98					
L	BATHROOM	F02	599.65	629.47	680.49	740.14	710.32					
LF, LJ	PRIVACY	F19, F22										
EX	EXIT	F31	554.12	583.95	634.18	694.61	664.79					
DUMMY TRIM												
DI	DUMMY TRIM INSIDE		259.01	273.92	299.04	344.56	314.74					
DO	DUMMY TRIM OUTSIDE											
DT	FULLY DUMMY		517.23	539.21	598.08	657.73	627.90					
KNOBS & LEVERS ARE PACKED 6 PER CASE												
NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory												

DRAKE PLATE DESIGN DR

	ANSI-A156.13 • Grade 2		Series 7 • 2-3/4" Backset Series 9 • 2-1/2" Backset				
	Standard Features		KNOBS		LEVERS		
	• Thru-bolted screwless knob/lever plate • Independent spring loaded captivated spindles • 2-1/2" or 2-3/4" backset • Lever support springs • Lock front Series 7: 1-1/4" x 8", Series 9: 1-1/16" x 7-5/8" • Dimensions: Ext: 11" H x 2-1/2" W, Int: 11" H x 2-1/2" W • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys - Options available on page 9-10		10, 20		002, 031, 037A, 47C, 55, 57, 72, 77, 78, 82, 83, 86, 92, 96		002, 031, 037A, 47C, 82, 86, 92, 96
					*26D N/A 92, 96, 82, 86		
FINISH GROUPS							
MARKS #	FUNCTION	ANSI #	3, 26D, 32D	10, 10B, 32	3, 15, 26D	4, 10, 10B, 14, 19, 26, 32	32D
KEYED SINGLE CYLINDER, NO DEADBOLT							
D	OFFICE VEST.		564.32	593.37	643.60	703.25	673.42
DW	VESTIBULE						
KEYED SINGLE CYLINDER, WITH DEADBOLT							
A	ENTRANCE	F08, F10	573.74	603.57	654.59	715.02	684.41
B	ENTRANCE	F21					
F	DORMITORY	F12					
FS	DORMITORY						
KEYED DOUBLE CYLINDER, WITH DEADBOLT							
AC	ENTRANCE	F35	598.08	627.90		738.57	708.75
C	STOREROOM	F14					
FX	DORMITORY	F33					
KEYLESS							
N	PASSAGE	F01	487.41	517.23	568.25	627.90	598.08
L	BATHROOM	F02	573.74	603.57	668.55	715.02	684.41
LF	PRIVACY	F19					
DUMMY TRIM							
DI	DUMMY TRIM INSIDE		259.01	273.92	299.04	344.56	314.74
DO	DUMMY TRIM OUTSIDE						
DT	FULLY DUMMY		516.87	539.21	598.08	657.73	627.90
KNOBS & LEVERS ARE PACKED 6 PER CASE							
NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory							

KNOBS	Round Knob 10	Ball Knob 20	Commerce Lever 037A	Metropolitan Lever 002
				
	Lucida Lever 47C	Copa Lever 031	Brompton Lever 55	Monaco Lever 57
				
LEVERS	Towne Lever 72	Maxwell Lever 77	Omni Lever 78	Plaza Lever 82
				
	Dayton Lever 83 Specify handing	Crescent Lever 86	American Lever 92	Titan Lever 96
				

LA PLATE DESIGN LA

	ANSI-A156.13 • Grade 1 3 Hour Fire Rating			
	Standard Features		LEVERS	
	• Thru-bolted screwless knob/lever plate assemblies • Independent spring loaded captivated spindles • Reversible mortise lock 2-1/2" or 2-3/4" backset • Lever support springs • Lock front: 1-1/4" x 8" • Dimensions: Ext: 8-1/2" H x 2-3/4" W x 7/16", Int: 8-1/2" H x 2-3/4" W x 7/16" • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys • Thickness: 1/8" Options available on page 9-10		002, 031, 037A, 82, 86, 92, 96,	
			FINISH GROUPS	
MARKS #	FUNCTION	ANSI #	32D	
KEYED SINGLE CYLINDER, NO DEADBOLT				
D	OFFICE VEST.		362.38	
DW	VESTIBULE			
E,K	OFFICE	F04		
EW	STOREROOM	F07		
J	CLASSROOM	F05		
JM, JR	HOSPITAL	F06		
GL	INSTIT. PRIVACY	F26		
EL	ELECTRICALLY LOCKED		873.09	
EU	ELECTRICALLY UNLOCKED			
KEYED SINGLE CYLINDER, WITH DEADBOLT				
A	ENTRANCE	F08, F10	688.44	
B	ENTRANCE	F21		
F	DORMITORY	F12		
FS	DORMITORY			
FW	DORMITORY	F13		
FD	APARTMENT	F20	634.52	
H	HOTEL	F15		
LH	SPECIAL PRIVACY			
KEYED DOUBLE CYLINDER, NO DEADBOLT				
G	APARTMENT	F09	666.77	
GC	INTRUDER LATCHBOLT	F32		
GG	CLASSROOM SECURITY			
GR	CLASSROOM SECURITY w/HOLDBACK			
WW	INSTITUTIONAL	F30		
KEYED DOUBLE CYLINDER, WITH DEADBOLT				
AC	ENTRANCE	F35	666.77	
C	STOREROOM	F14		
FC	INTRUDER DEADBOLT	F34		
FA	DORMITORY	F11		
FX	DORMITORY	F33		
KEYLESS				
N	PASSAGE	F01	555.40	
L	BATHROOM	F02	590.81	
LF	PRIVACY	F19		
LJ	PRIVACY	F22	595.01	
EX	EXIT	F31		
DUMMY TRIM				
DI	DUMMY TRIM INSIDE		278.07	
DO	DUMMY TRIM OUTSIDE			
DT	FULLY DUMMY		529.66	
KNOBS & LEVERS ARE PACKED 6 PER CASE				
NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory				

LA PLATE DESIGN LA

	ANSI-A156.13 • Grade 2		
	Standard Features		LEVERS
	• Thru-bolted screwless knob/lever plate assemblies • Independent spring loaded captivated spindles • Reversible mortise lock 2-1/2" or 2-3/4" backset • Lever support springs • Lock front Series 7: 1-1/4" x 8", Series 9: 1-1/16" x 7-5/8" • Dimensions: Ext: 8-1/2" H x 2-3/4" W x 7/16", Int: 8-1/2" H x 2-3/4" W x 7/16" • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys Options available on page 9-10		002 031, 037A, 47C, 82, 86, 92, 96
MARKS #	FUNCTION	ANSI #	32D
KEYED SINGLE CYLINDER, NO DEADBOLT			
D	OFFICE VEST.		603.42
DW	VESTIBULE		
KEYED SINGLE CYLINDER, WITH DEADBOLT			
A	ENTRANCE	F08, F10	613.11
B	ENTRANCE	F21	
F	DORMITORY	F12	
FS	DORMITORY		
FW	DORMITORY	F13	
KEYED DOUBLE CYLINDER, WITH DEADBOLT			
AC	ENTRANCE	F35	639.15
C	STOREROOM	F14	
FX	DORMITORY	F33	
KEYLESS			
N	PASSAGE	F01	528.28
L	BATHROOM	F02	613.84
LF	PRIVACY	F19	
DUMMY TRIM			
DI	DUMMY TRIM INSIDE		276.79
DO	DUMMY TRIM OUTSIDE		
DT	FULLY DUMMY		553.58
KNOBS & LEVERS ARE PACKED 6 PER CASE			
NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory			

LEVERS	Commerce Lever 002 	Metropolitan Lever 037A 	Lucida Lever 47C 	Copa Lever 031 
	Plaza Lever 82 	Crescent Lever 86 	American Lever 92 	Titan Lever 96 

NEW YORKER PLATE DESIGN NY


	ANSI-A156.13 • Grade 1 3 Hour Fire Rating			Series 5 • 2-3/4" Backset Series 55 • 2-1/2" Backset			
	Standard Features			KNOBS		LEVERS	
	• Thru-bolted screwless knob/lever plate assemblies • Independent spring loaded captivated spindles • Reversible mortise lock 2-1/2" or 2-3/4" backset • Lever support springs • Lock front: 1-1/4" x 8" • Dimensions: Ext: 10" H x 2-3/4" W, *Int: 7" H x 2-1/4" W • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys • Thickness: 1/4" Options available on page 9-10			10, 20		002, 031,037A, 47C, 55, 57, 72, 77, 78, 82, 83, 86, 92, 96	
				FINISH GROUPS			
MARKS #	FUNCTION	ANSI #	3	26D	3	26D	
KEYED SINGLE CYLINDER, NO DEADBOLT							
D	OFFICE VEST.		322.92	352.07	396.92	426.83	
DW	VESTIBULE						
E, K	OFFICE	F04					
EW	STOREROOM	F07					
J	CLASSROOM	F05					
JM, JR	HOSPITAL	F06					
GL	INSTIT. PRIVACY	F26	590.53	620.42	666.03	662.29	
EL	ELECTRICALLY LOCKED						
EU	ELECTRICALLY UNLOCKED						
KEYED SINGLE CYLINDER, WITH DEADBOLT							
A	ENTRANCE	F08, F10	335.63	362.54	410.38	439.53	
B	ENTRANCE	F21					
F	DORMITORY	F12					
FS	DORMITORY						
FW	DORMITORY	F13					
FD	APARTMENT	F20	354.31	383.47	429.81	458.97	
H	HOTEL	F15					
LH	SPECIAL PRIVACY						
KEYED DOUBLE CYLINDER, NO DEADBOLT							
G	APARTMENT	F09	361.04	396.92	435.80	464.95	
GC	INTRUDER LATCHBOLT	F32					
GG	CLASSROOM SECURITY						
GR	CLASSROOM SECURITY w/HOLDBACK						
WW	INSTITUTIONAL	F30					
KEYED DOUBLE CYLINDER, WITH DEADBOLT							
AC	ENTRANCE	F35	361.04	396.92	435.80	464.95	
C	STOREROOM	F14					
FC	INTRUDER DEADBOLT	F34					
FA	DORMITORY	F11					
FX	DORMITORY	F33					
KEYLESS							
N	PASSAGE	F01	239.20	268.36	313.95	343.46	
L	BATHROOM	F02	335.25	362.54	410.38	439.53	
LF,	PRIVACY	F19, F22					
LJ EX	EXIT	F31	284.05	313.20	358.80	388.71	
DUMMY TRIM							
DI	DUMMY TRIM INSIDE		122.59	136.80	161.46	190.61	
DO	DUMMY TRIM OUTSIDE						
DT	FULLY DUMMY		244.44	273.58	318.43	349.08	
KNOBS & LEVERS ARE PACKED 6 PER CASE							
NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory							
★ Large interior plate available (10" H x 2-3/4" W)							

NEW YORKER PLATE DESIGN NY

	ANSI-A156.13 • Grade 2		Series 7 • 2-3/4" Backset Series 9 • 2-1/2" Backset			
	Standard Features		KNOBS		LEVERS	
	• Thru-bolted screwless knob/lever plate assemblies • Independent spring loaded captivated spindles • 2-1/2" or 2-3/4" backset • Lever support springs • Lock front Series 7: 1-1/4" x 8", Series 9: 1-1/16" x 7-5/8" • Dimensions: Ext: 10" H x 2-3/4" W, *Int: 7" H x 2-1/4" W • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys Options available on page 9-10		10, 20		002, 031,037A, 47C, 55, 65, 57, 72, 77, 78, 82, 83, 86, 92, 96	
MARKS #	FUNCTION	ANSI #	3	26D	3	26D
KEYED SINGLE CYLINDER, NO DEADBOLT						
D	OFFICE VEST.		269.59	295.95	344.59	370.94
DW	VESTIBULE					
KEYED SINGLE CYLINDER, WITH DEADBOLT						
A	ENTRANCE	F08, F10	281.08	305.40	348.65	375.67
B	ENTRANCE	F21				
F	DORMITORY	F12				
FS	DORMITORY					
FW	DORMITORY	F13				
KEYED DOUBLE CYLINDER, WITH DEADBOLT						
AC	ENTRANCE	F35	304.05	330.40	371.62	397.97
C	STOREROOM	F14				
FX	DORMITORY	F33				
KEYLESS						
N	PASSAGE	F01	195.27	220.95	262.15	287.83
L	BATHROOM	F02	195.27	220.95	262.15	287.83
LF	PRIVACY	F19				
DUMMY TRIM						
DI	DUMMY TRIM INSIDE		122.59	136.80	161.46	190.61
DO	DUMMY TRIM OUTSIDE					
DT	FULLY DUMMY		244.44	273.58	318.43	349.08

KNOBS & LEVERS ARE PACKED 6 PER CASE

NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory
* Large interior plate available (10" H x 2-3/4" W)



KNOBS	Round Knob 10 	Ball Knob 20 	Commerce Lever SF037A 	Metropolitan Lever 002 
	Lucida Lever 47C 	Copa Lever 031 	Brompton Lever 55 	Monaco Lever 57 Specify handing 
LEVERS	Towne Lever 72 	Maxwell Lever 77 	Omni Lever 78 	Plaza Lever 82 
	Dayton Lever 83 Specify handing 	Crescent Lever 86 	American Lever 92 	Titan Lever 96 

ROSE DESIGN RR, RW, RQ, RS, RX*, RK*, RL*

		ANSI-A156.13 • Grade 1 3 Hour Fire Rating				Series 5 • 2-3/4" Backset Series 55 • 2-1/2" Backset									
2-9/16" Diameter  2-1/4" Diameter 		Standard Features		KNOBS		LEVERS									
		• Thru-bolted screwless knob/lever rose assemblies • Independent spring loaded captivated spindles • Reversible mortise lock 2-1/2" or 2-3/4" backset • Lever support springs • Lock front: 1-1/4" x 8" • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys Options available on page 9-10		10, 20		002, 031,037A, 47C 55, 57, 72, 77, 78, 82, 83, 86, 92, 96 *26D N/A 92, 96, 82,86		002, 031,037A 47C, 82, 86, 92, 96							
				FINISH GROUPS											
MARKS #		FUNCTION		ANSI #		3, 32D		3, 15, 26D		14, 26, 32		4, 10, 10B, 19		32D	
KEYED SINGLE CYLINDER, NO DEADBOLT															
D		OFFICE VEST.				452.87		481.91		511.74		541.56		481.91	
DW		VESTIBULE													
E, K		OFFICE		F04											
EW		STOREROOM		F07											
J		CLASSROOM		F05											
JM, JR		HOSPITAL		F06		707.96		737.00		766.83		788.02		737.00	
GL		INSTIT. PRIVACY		F26											
EL		ELECTRICALLY LOCKED													
EU		ELECTRICALLY UNLOCKED													
KEYED SINGLE CYLINDER, WITH DEADBOLT															
A		ENTRANCE		F08, F10		463.07		492.90		522.73		543.92		492.90	
B		ENTRANCE		F21											
F		DORMITORY		F12											
FS		DORMITORY													
FW		DORMITORY		F13											
FD		APARTMENT		F20		481.13		510.17		539.99		561.19		510.17	
H		HOTEL		F15											
LH		SPECIAL PRIVACY													
KEYED DOUBLE CYLINDER, NO DEADBOLT															
G		APARTMENT		F09		487.41		516.45		546.28		568.25		516.45	
GC		INTRUDER LATCHBOLT		F32											
GG		CLASSROOM SECURITY													
GR		CLASSROOM SECURITY w/HOLDBACK													
WW		INSTITUTIONAL		F30											
KEYED DOUBLE CYLINDER, WITH DEADBOLT															
AC		ENTRANCE		F35		487.41		516.45		546.28		568.25		516.45	
C		STOREROOM		F14											
FC		INTRUDER DEADBOLT		F34											
FA		DORMITORY		F11											
FX		DORMITORY		F33											
KEYLESS															
N		PASSAGE		F01		351.62		441.88		472.49		477.99		441.88	
L		BATHROOM		F02		463.07		492.90		522.73		543.92		492.90	
LF		PRIVACY		F19											
LJ		PRIVACY		F22		416.77		446.60		476.42		497.61		446.60	
EX		EXIT		F31											
DUMMY TRIM															
DI		DUMMY TRIM INSIDE				128.72		143.64		153.77		195.95		109.10	
DO		DUMMY TRIM OUTSIDE													
DT		FULLY DUMMY				256.66		287.26		334.36		366.54		216.63	
KNOBS & LEVERS ARE PACKED 6 PER CASE															
NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory															
*Square Rose RX: Add \$21 / *Square Rose RL: Add \$125 / *Square Rose RK: Add \$125															


ROSE DESIGN RR, RW, RQ, RS, RX*, RK*, RL*

2-9/16" Diameter  2-1/4" Diameter 	ANSI-A156.13 • Grade 2		Series 7 • 2-3/4" Backset Series 9 • 2-1/2" Backset				
	Standard Features		KNOBS		LEVERS		
	• Thru-bolted screwless knob/lever rose assemblies • Independent spring loaded captivated spindles • 2-1/2" or 2-3/4" backset • Lever support springs • Lock front Series 7: 1-1/4" x 8"; Series 9: 1-1/16" x 7-5/8" • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys - Options available on page 9-10		10, 20		002, 031,037A, 47C, 55, 57, 72, 77, 78, 82, 83, 86, 92, 96 *26D N/A 92, 96, 82,86		
FINISH GROUPS							
MARKS #	FUNCTION	ANSI #	3, 32D	3, 15, 26D	14, 26, 32	4, 10, 10B, 19	32D
KEYED SINGLE CYLINDER, NO DEADBOLT							
D	OFFICE VEST.		426.97	456.71	485.84	507.81	456.71
DW	VESTIBULE						
KEYED SINGLE CYLINDER, WITH DEADBOLT							
A	ENTRANCE	F08, F10	437.96	490.55	520.37	542.35	490.55
B	ENTRANCE	F21					
F	DORMITORY	F12					
FS	DORMITORY						
FW	DORMITORY	F13					
KEYED DOUBLE CYLINDER, WITH DEADBOLT							
AC	ENTRANCE	F35	461.51	490.55	520.37	542.35	490.55
C	STOREROOM	F14					
FX	DORMITORY	F33					
KEYLESS							
N	PASSAGE	F01	351.62	380.67	410.49	431.68	380.67
L	BATHROOM	F02	437.96	467.00	545.49	518.02	467.00
LF	PRIVACY	F19					
DUMMY TRIM							
DI	DUMMY TRIM INSIDE		128.72	143.64	153.77	195.95	109.10
DO	DUMMY TRIM OUTSIDE						
DT	FULLY DUMMY		256.66	287.26	334.36	366.54	216.63
KNOBS & LEVERS ARE PACKED 6 PER CASE							
NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory							
*Square Rose RX: Add \$21 / *Square Rose RZ: Add \$125 / *Square Rose RK: Add \$125							


KNOB	Round Knob 10	Ball Knob 20	Commerce Lever 037A	Metropolitan Lever 002	ROSES	RR: 2-9/16" dia.	
						RW: 2-9/16" dia.	
	Lucida Lever 47C	Copa Lever 031	Brompton Lever 55	Monaco Lever 57 Specify handing		RQ: 2-1/4" dia.	
						RS: 2-1/4" dia.	
LEVER	Towne Lever 72	Maxwell Lever 77	Omni Lever 78	Plaza Lever 82			
							
	Dayton Lever 83 Specify handing	Crescent Lever 86	American Lever 92	Titan Lever 96			
						RX: 2-1/2"sq.  Wrought	RK: 2-1/2"sq.  Forged
						RL: 2-1/2"sq. 	

ORNAMENTAL IRON


Series 21 Unilock™

F & FW Function
Single Cylinder Only


Series 9215 Unilock™

F & FW Function
Single Cylinder Only


THINLINE® Series 2750 for 1" doors



Series 22

F & FW Function
Single Cylinder Only

Series 9225

F & FW Function
Single Cylinder Only

Standard Features

- Door thickness: 1"
- Series 9 lock body, Backset: 2-1/2"
- Reversible mortise lock 1" bolt, 1/2" latch projection
- Lock front Series 7: 1-1/4" x 8"; Series 9: 1-1/16" x 7-5/8"
- Thru-bolted solid brass trim assemblies
- Spring loaded captivated spindles
- 5/16" Cylinder: Marks "A" keyway, 5 pin w/ 2 keys; keyed alike-6

**SERIES 21
UNILOCK™
SERIES 22**

**SERIES 9215
UNILOCK™
SERIES 9225**

FINISH GROUPS

MARKS #	FUNCTION	3	10B(19)	5, 26D	3	10B(19)	5, 26D
---------	----------	---	---------	--------	---	---------	--------

KEYED SINGLE CYLINDER, WITH DEADBOLT

DW	SINGLE CYL. PANIC PROOF	210.61	251.52	224.25	281.07	317.44	295.47
F	SINGLE CYL. PANIC PROOF						
FW	SINGLE CYL. PANIC PROOF						

KEYED DOUBLE CYLINDER, WITH DEADBOLT

AC	ENTRANCE	187.13	230.31	200.77	258.34	295.47	271.78
----	----------	--------	--------	--------	--------	--------	--------

DUMMY TRIM

DT	FULL DUMMY	125.00	172.33	134.09	200.77	243.19	210.61
----	------------	--------	--------	--------	--------	--------	--------

ORNAMENTAL IRON LOCKSETS ARE PACKED 6 PER CASE

Standard Features

- Thru-bolted solid brass trim assemblies
- Spring loaded captivated spindles
- Reversible mortise lock 1" backset
- 1" bolt, 1/2" latch projection
- Cylinder: Marks "A" keyway, 5 pin w/ 2 keys; keyed alike - 6

SERIES

**2750
THINLINE®**

FINISH GROUPS

MARKS #	FUNCTION	3	10B(19)	5, 26D
---------	----------	---	---------	--------

KEYED WITH DEADBOLT

B	ENTRANCE CYLINDER x TURNPIECE	156.82	197.93	176.52
C	ENTRANCE DOUBLE CYLINDER			

DUMMY TRIM

DT	FULL DUMMY	94.70	131.02	109.85
----	------------	-------	--------	--------

ORNAMENTAL IRON LOCKSETS PACKED 6 PER CASE

OPTIONS - Series 2750

CODE	PRICE
For 1-3/4" doors	D4 NC
Marks "C" keyway	G5 11


OPTIONS	CODE	PRICE
Lock Front: 1" x 7-1/8" standard	W	NC
Mushroom knob interior; 1-7/8" prj.	A9	4
For 1-3/4" doors	D4	NC
Adjustable spring collars	F10	4

How To Order Example for Ornamental Iron Locksets

9215	AC	/	10B	-	D4
1. Lock Series	2. Marks Function	Slash	3. Finish	Dash	4. Options
LOCK SERIES (Pgs. 49 & 50)	MARKS FUNCTION (Pgs. 57-58)		FINISH (Pg. 10)	OPTIONS	
___ 21 ___ 2750	___ B ___ AC	___ 3 ___ 10B(19)	___ Special		
___ 22 ___ 9215	___ C ___ DT	___ 5 ___ 26D	Specify		
	___ F ___ DW		• Keying • Handing		
			• Door Thickness		


ORNAMENTAL IRON

Knob & Lever Kits




PART #	DESCRIPTION	FUNCTION	FINISH GROUPS			
			3	4	10B(19)	5, 26D
K21AC	Ext./Int. UNILOCK™ knob/plate kit	AC	92.43	–	120.46	102.28
K21AC-M	Ext./Int. UNILOCK™ knob/plate kit (Mushroom Int.)	AC	103.79	–	124.25	106.82
K21F	Ext./Int. UNILOCK™ knob/plate kit assemblies	F	110.61	–	133.34	115.91
K21F-M	Ext./Int. UNILOCK™ knob/plate kit (Mushroom Int.)	F	114.40	–	137.88	120.46
K2750	LEVER PLATE TRIM SET		110.61	–	143.19	125.76
2600B	Thinline lock body, latch, deadbolt US 4 & 26D ONLY - Strike not included		–	91.67	143.19	125.76
K9215AC	Ext./Int. UNILOCK™ lever/plate kit assemblies	AC	139.40	–	165.16	147.73
K9215F	Ext./Int. UNILOCK™ lever/plate kit assemblies	F	139.40	–	181.06	163.64
A9214-M	UNILOCK™ mushroom knob/plate (w/cylinder hole)	AC	51.52	–	71.98	53.79
K9217-M	UNILOCK™ mushroom knob/plate (w/turnpiece)	F	90.15	–	109.85	92.43
K22	Ext./Int. knob/rose kit 1" thru 1-3/4" door		53.79	–	82.58	65.15
K22-M	Ext./Int. knob/rose kit (mushroom int.)		59.10	–	86.37	68.94
K9225	Ext./Int. lever/rose kit		136.37	–	160.61	143.19

Accessories



PART #	DESCRIPTION	FINISH GROUPS		
		NO FINISH	3	5, 26D
K9117	Turnpiece kit	–	35.61	37.88
A9223-M	Interior knob/rose assembly (mushroom knob)	–	30.30	35.61
9273	Spring collar, 7/16" high	–	9.09	11.58
9275	Mortise spacer, wrought brass, 1/8" high	–	4.54	–
A9276	Collar, wrought brass w/insert, 1/2" high	–	15.91	15.91
9277	Plastic spacer ring, 1/16"	0.76	–	–
2635	Curved lip strike, solid brass	–	18.18	11.36
2638	Flat strike, solid brass, no lip	–	11.36	15.30

Cylinders




PART #	DESCRIPTION	FINISH GROUPS	
		3	5, 26D
2122-A	5 Pin mortise cylinder, "A" keyway, 15/16"	28.32	29.70
2621-A	Cylinder x turnpiece unit, "A" keyway	46.28	51.45
2622-A	Double cylinder unit, "A" keyway	33.16	41.45
2122-C	5 Pin mortise cylinder, "C" keyway	28.32	29.70
2621-C	Cylinder x turnpiece unit, "C" keyway	46.28	51.12
2622-C	Double cylinder unit, "C" keyway	33.16	41.45

MORTISE LOCK BODIES

AUTOREVERSE SERIES

GRADE 1
MORTISE LOCKS EXCEEDS
BHMA
SPECIFICATIONS

Mortise Parts, Trim




OPTIONS	CODE	PRICE
1-1/16" x 7-5/8" front	T	17.00
1-1/16" x 7-3/4" front	V	17.00
1-1/16" x 8" front	Q	17.00
Lever override guard outside (Series 5)	B1	28.00
Lever override guard both sides	B2	40.00
Lever support springs w- 5/16" hubs	B4	13.00
Hubs with hollow spacer (Series 55)	B6	12.00
Turnpiece hub on square	B8	8.00
Screws with Dust Box	B10	NC
Solid latch for electric strike	E1	13.00
Hold open latch	E2	24.00
Lead-lined mortise lock	F1	206.00
4-7/8" Strikes: 1 Left / 1 Right	S6	9.00
Request to exit switch (Series 5)	W10	101.00

CYLINDER CAMS REQUIRED

Locks w/o deadbolt	2101 Straight Cam
Locks w/deadbolt	2102 Cloverleaf Cam
G function (ext. only)	2106 "G" Cam
G function (int. only)	2105 "J" Cam
J function	2105 "J" Cam

* 55 Series Lock Bodies are not available in autoreverse and electrified functions EL and EU.



Standard Features

- Backset: 5 Series 2-3/4"; 55 Series 2-1/2"
- Bolt throw: Stainless steel full 1" throw
- Latch throw: 3/4" (anti-friction)
- Auxiliary latch: 1/2" throw
- Case: Stamped steel .090 thick, Zinc dichromate finish
- Front: 1-1/4" x 8", Adjustable bevel
- Hubs: Steel, 9/32" on diamond 5/16" on square w/security separator

Grade 1 for
Knobs & Levers
Series 5 • 2-3/4" Backset
Series 55 • 2-1/2" Backset




FINISH GROUPS

MARKS #		FUNCTION	ANSI #	3, 32D	10, 10B, 32
KEYED SINGLE CYLINDER, NO DEADBOLT					
D		OFFICE / VESTIBULE		248.81	325.73
DW		VESTIBULE			
E, Q, QH		OFFICE	F04		
K		OFFICE	F04		
EW		STOREROOM	F07		
J		CLASSROOM	F05		
JM, JR		HOSPITAL (HOLDBACK)	F06		
GL		INST. PRIVACY	F26		
MT		ArchiTech		899.47	916.74
EL*		ELECTRICALLY LOCKED*		681.27	696.19
EU*		ELECTRICALLY UNLOCKED*			
KEYED SINGLE CYLINDER, WITH DEADBOLT					
A		ENTRANCE	F08, F10	261.37	275.49
B		ENTRANCE	F21		
F		DORMITORY	F12		
FS		DORMITORY			
FW		DORMITORY	F13		
FD		APARTMENT	F20	280.20	295.11
AD			F27		
H		HOTEL	F15		
LH		SPEC. PRIVACY			
KEYED DOUBLE CYLINDER, NO DEADBOLT					
G		ENTRANCE	F09	286.48	300.61
GC		INTRUDER LATCHBOLT	F32		
GG		CLASSROOM SECURITY			
GR		CLASSROOM SECURITY w/HOLDBACK			
WW		INSTITUTION	F30		
KEYED DOUBLE CYLINDER, WITH DEADBOLT					
AC		ENTRANCE	F35	286.48	300.61
C		STOREROOM	F14		
FC		INTRUDER DEADBOLT	F34		
FA		DORMITORY	F11		
FX		DORMITORY	F33		
KEYLESS					
N		PASSAGE		204.86	218.98
L		BATHROOM	F02	261.37	275.49
LF		PRIVACY	F19		
LJ		PRIVACY	F19		
EX		EXIT	F31		

MORTISE LOCK BODIES ARE PACKED 6 PER CASE

* Electrified Functions 5 SERIES ONLY: 2-3/4" Backset ONLY:
100% Duty Cycle 24V/DC, 12V/DC supplied with bridge rectifier (350 ma)



MORTISE LOCK BODIES



OPTIONS	CODE	PRICE
1-1/16" x 7-5/8" front	T	17.00
1-1/4" x 10" front, (A function, US 4 only), no mounting holes	U	69.00
1" x 7-1/8" front, (US 4 only)	W	NC
1-1/4" x 8" front	X	16.00
1-1/4" x 8-5/8" front (A function, US 4 only)	Y	69.00
Screws with Dust Box	B10	NC
Solid latch for electric strike	E1	13.00
4-7/8" Strikes: 1 Left / 1 Right	S6	9.00
Front 1" x 8"	Z	16.00

CYLINDER CAMS REQUIRED

All Functions 2101 Straight Cam



Series 6		Standard Features			
	• Backset: 2-3/4" • Bolt throw: Cast alloy full 1" throw • Latch throw: 5/8" (anti-friction) • Case: High pressure cast Zamac, baked enamel finish • Front: 1-1/4" x 8", Flat or 3° bevel • Hubs: 9/32" (7.2mm) on square				
Series 8		Standard Features			
	• Backset: 2-1/2" • Bolt throw: Cast alloy full 1" throw • Latch throw: Solid brass 1/2" throw, reversible • Case: High pressure cast Zamac, baked enamel finish • Front: 1-1/16" x 7-5/8", Flat or 3° bevel • Hubs: 9/32" on square				
		FINISH GROUPS			
MARKS #		FUNCTION	ANSI #	3, 32D	10, 10B, 32
KEYED SINGLE CYLINDER, NO DEADBOLT					
DW		VESTIBULE		252.73	266.85
KEYED SINGLE CYLINDER, WITH DEADBOLT					
A		ENTRANCE	F08, F10	262.93	276.27
B		ENTRANCE	F21		
F		DORMITORY	F12		
KEYED DOUBLE CYLINDER, WITH DEADBOLT					
AC		ENTRANCE	F35	275.49	289.62
C		STORE DOOR "B BODY"	F25		
SO		STORE DOOR	F25		
MORTISE LOCK BODIES ARE PACKED 6 PER CASE					

Grade 2 for
Handlesets

Series 6
2-3/4" Backset
Series 8
2-1/2" Backset



Mortise Parts, Trim

MORTISE LOCK BODIES




OPTIONS	CODE	PRICE
1-1/16" x 7-5/8" front	T	17.00
1-1/4" x 10" front, (A function, US 4 only), no mounting holes	U	69.00
1" x 7-1/8" front, (US 4 only)	W	NC
1-1/4" x 8" front	X	16.00
1-1/4" x 8-5/8" front (A function, US 4 only)	Y	69.00
1-1/16" x 8"	Q	17.00
Pin and lever springs	B5	24.00
Screws with Dust Box	B10	NC
Solid latch for electric strike	E1	13.00
4-7/8" Strikes: 1 Left / 1 Right	S6	9.00
Front 1" x 8"	Z	16.00

CYLINDER CAMS REQUIRED	
All functions	2101 Straight Cam


Series 7		Standard Features		Grade 2 for Knobs & Levers Series 7 2-3/4" Backset Series 9 2-1/2" Backset	
		• Backset: 2-3/4" • Bolt throw: Cast alloy full 1" throw • Latch throw: 5/8" (anti-friction) • Case: High pressure cast Zamac, baked enamel finish • Front: 1-1/4" x 8", Flat or 3° bevel • Hubs: 9/32" on square steel, w/ security separator			
Series 9		Standard Features			
		• Backset: 2-1/2" • Bolt throw: Cast alloy full 1" throw • Latch throw: Solid brass 1/2" throw, reversible • Case: High pressure cast Zamac, baked enamel finish • Front: 1-1/16" x 7-5/8", Flat or 3° bevel • Hubs: 9/32" on square steel, w/ security separator		FINISH GROUPS	
MARKS #		FUNCTION	ANSI #	3, 32D	10, 10B, 32
KEYED SINGLE CYLINDER, NO DEADBOLT					
D		OFFICE / VESTIBULE		223.69	237.82
DW		VESTIBULE			
KEYED SINGLE CYLINDER, WITH DEADBOLT					
A		ENTRANCE	F08, F10	236.25	248.81
B		ENTRANCE	F21		
F		DORMITORY	F12		
FS		DORMITORY			
FW		DORMITORY	F13		
KEYED DOUBLE CYLINDER, WITH DEADBOLT					
AC		ENTRANCE	F35	260.58	273.92
C		STOREROOM	F14		
FA		DORMITORY	F11		
FX		DORMITORY	F33		
KEYLESS					
N		PASSAGE	F01	179.73	193.08
L		BATHROOM	F02	236.25	248.81
LF		PRIVACY	F19		
MORTISE LOCK BODIES ARE PACKED 6 PER CASE					

MORTISE DEADLOCKS


Series 31		
OPTIONS	CODE	PRICE
Security Strike: 4-7/8" x 1-1/4"	S4	12.00

	Standard Features		Series 31 2-3/4" Backset		
	• Backset: Series 31: 2-3/4" • Bolt throw: 1" stainless steel with hardened roll pins • Case: Stamped Steel, Grade 1 • Front: 1-1/16" x 4-5/8" adjustable bevel • Cylinder: Solid brass cylinder, 6-pin, "C" keyway, 2 keys • Strike: #4035 (Included) 1-1/8" x 3-1/8" • Strike: #4035-1 (Optional) 1-1/8" x 3-1/2"		BHMA CERTIFIED		
			FINISH GROUPS		
MARKS #	FUNCTION	ANSI #	3, 32D	10, 10B, 26, 32	
–	LOCK ONLY	–	145.98	237.82	
K, 31K	CYLINDER x TURNPIECE	E06071	193.08	248.81	
L, 31L	COMMUNICATING SINGLE CYL.	E06081	172.68	273.92	
M, 31M	DOUBLE CYLINDER	E06061	195.44	193.08	
S, 31S	CLASSROOM (Specify Handing)	E06091	218.98	248.81	
X, 31X	TURNPIECE ONLY		154.62	300.61	
MORTISE LOCK BODIES ARE PACKED 6 PER CASE					

Series 2 & 3		
OPTIONS	CODE	PRICE
1-1/16" x 5-5/8" front	R	29.00

	Standard Features		Series 2 • 2-1/2" Backset Series 3 • 2-3/4" Backset	
	• Backset: Series 2: 2-1/2"; Series 3: 2-3/4" • Bolt throw: 1" • Case: High pressure cast • Front: 1-1/16" x 4-5/8" flat or 3° bevel • Cylinder: Solid brass cylinder, 6-pin, "C" keyway, 2 keys • Strike: #4035 Included		FINISH GROUPS	
MARKS #	FUNCTION	ANSI #	3, 32D	10, 10B, 26, 32
–	LOCK ONLY	–	102.82	120.87
K, 2K, 3K	CYLINDER x TURNPIECE	E06071	150.70	166.39
L, 2L, 3L	COMMUNICATING SINGLE CYL.	E06081	131.86	150.70
M, 2M, 3M	DOUBLE CYLINDER	E06061	158.54	175.03
S, 2S, 3S	CLASSROOM (Specify Handing)	E06091	173.46	195.44
X, 2X, 3X	TURNPIECE ONLY		110.67	127.15
MORTISE LOCK BODIES ARE PACKED 6 PER CASE				

Series 5		
Series 55		



Standard Features

- Backset: Series 5: 2-3/4"; Series 55: 2-1/2"
- Bolt throw: Stainless steel full 1" throw
- Case: Stamped steel .090 thick, Zinc dichromate finish
- Front: 1-1/4" x 8" Adjustable bevel

Series 5 • 2-3/4" Backset

Series 55 • 2-1/2" Backset

BHMA™

CERTIFIED

FINISH GROUPS

MARKS #	FUNCTION	ANSI #	3, 32D	10, 10B, 32
T, 5T	DOUBLE CYLINDER	F16	294.33	304.53
P, 5P	CYLINDER x TURNPIECE	F17	270.00	288.05
S, 5S	SINGLE CYLINDER*	F18	248.81	268.43
SC, 5SC	CLASSROOM*	F29	288.05	304.53

MORTISE LOCK BODIES ARE PACKED 6 PER CASE


*NOTE: Specify handing on "S" and "SC" functions

OPTIONS	CODE	PRICE
1-1/16" x 7-5/8" front	T	17.00
1-1/16" x 7-3/4" front	V	17.00
1" x 1/16" x 8"	Q	17.00
Lead lined mortise lock	F1	206.00



MORTISE LOCKSET FUNCTIONS

ANSI #	TYPE	MARKS FUNCTION	ANSI #	TYPE	MARKS FUNCTION	ANSI #	TYPE	MARKS FUNCTION	ANSI #	TYPE	MARKS FUNCTION
F01	Non-Keyed	N	F10	Single Cylinder	A	F19	Non-Keyed	LF	F29	Deadbolt	SC
F02	Non-Keyed	L	F11	Double Cylinder	FA	F20	Single Cylinder	FD	F30	Double Cylinder	WW
F04	Single Cylinder	E	F12	Single Cylinder	F	F21	Single Cylinder	B	F31	Non-Keyed	EX
F05	Single Cylinder	J	F13	Single Cylinder	FW	F22	Non-Keyed	LJ	F32	Double Cylinder	GC
F06	Single Cylinder	JM	F14	Double Cylinder	C	F24	Double Cylinder	G	F33	Double Cylinder	FX
F06	Single Cylinder	JR	F15	Single Cylinder	H	F25	Double Cylinder	C	F34	Double Cylinder	FC
F07	Single Cylinder	EW	F16	Deadbolt	T	F25	Double Cylinder	SO	F35	Double Cylinder	AC
F08	Single Cylinder	A	F17	Deadbolt	P	F26	Single Cylinder	GL			
F09	Double Cylinder	G	F18	Deadbolt	S	F27	Auto Deadbolt	AD			

SINGLE CYLINDER FUNCTIONS

ANSI #	Cam	Strike	MARKS FUNCTION
F04: OFFICE Latch by knob/lever either side except when outside knob/lever locked by stop-button in front; then by key outside. Auxiliary latch deadlocks latch. Inside always open.			 I/S O/S E
F04: OFFICE Latch by knob/lever either side except when outside knob/lever locked by turn piece inside; then by key outside. Auxiliary latch deadlocks latch. Inside always open.			 K
F05: CLASSROOM Latch by knob/lever either side except when outside knob/lever locked by key. When locked, latch bolt retracted by key. Inside always open. Auxiliary latch deadlocks latch.			 J
F06: HOLDBACK "A" Latch by knob/lever either side except when outside knob/lever locked or unlocked by key. Auxiliary latch deadlocks latch. Inside always open. Inside knob/lever unlocks outside lever. Latch bolt can be locked in retracted position by locking inside hub. Can be used with blank outside trim.			 JM
F06: HOLDBACK "B" Latch by knob/lever either side except when outside knob/lever locked or unlocked by key. Auxiliary latch deadlocks latch. Inside always open. Inside knob/lever will not unlock outside knob/lever. Latch bolt can be locked in retracted position by locking outside hub. Can not be used with blank outside trim.			 JR
F07: STOREROOM Latch by knob/lever inside, key outside. Outside knob/lever always rigid. Auxiliary latch deadlocks latch. Inside always open.			 EW
F08, F10: ENTRANCE Latch by knob/lever either side except when outside locked by stop-button; then by key outside, knob/lever inside. Deadbolt by key outside, turnpiece inside. Deadbolt deadlocks latch.			 A
F12: DORMITORY Latch by knob/lever either side except when outside knob/lever locked by stop-button or projected deadbolt. Deadbolt by turnpiece inside. Inside knob/lever retracts latch and deadbolt simultaneously, leaving outside locked. Deadbolt deadlocks latch.			 F
F13: DORMITORY Latch by knob/lever either side except when projected deadbolt locks outside knob/lever and deadlocks latch. Deadbolt and latch by key outside. Deadbolt by turnpiece inside. Inside knob/lever retracts latch and deadbolt simultaneously, automatically unlocking outside knob/lever.			 FW
F15: HOTEL Inside knob/lever always free, outside rigid. Latch by knob/lever inside, key outside. (When deadbolt projected by turnpiece all keys are shut out except emergency key). Inside knob/lever retracts deadbolt and latch simultaneously. Auxiliary latch or deadbolt deadlocks latch. Indicator available.			 H
F20: APARTMENT Latch by knob/lever either side except when outside locked by stop-button or projected deadbolt. Latch deadlocked by auxiliary latch or deadbolt. Deadbolt and latch by key outside. Deadbolt by turnpiece inside. Inside knob/lever retracts latch & deadbolt simultaneously, leaving outside locked.			 FD

SINGLE CYLINDER FUNCTIONS

ANSI #	Cam	Strike	MARKS FUNCTION
F21: ENTRANCE Latch by knob/lever either side. Deadbolt by key outside, turnpiece inside. Deadbolt deadlocks latch.			 I/S O/S B
F26: INSTITUTIONAL PRIVACY Latch by knob/lever either side except when outside knob/lever locked by inside turn piece. Latch deadlocked by auxiliary latch. Key outside opens latch. When outside locked, closing door or rotating inside knob/lever retracting latch, automatically unlocks outside knob/lever.			 GL
OFFICE VESTIBULE: Latch by knob/lever either side except when outside knob/lever locked by stop-button in front; then by key outside.			 D
VESTIBULE: Latch by knob/lever inside, key outside. Outside knob/lever always rigid.			 DW
DORMITORY: Latch by knob/lever inside. Outside knob/lever always rigid. Deadbolt and latch by key outside. Deadbolt by turnpiece inside. When deadbolt is projected, latch is deadlocked. Inside knob/lever retracts latch and deadbolt simultaneously.			 FS
SPECIAL PRIVACY: Inside knob/lever always free, outside rigid. Latch by knob/lever inside, key outside. Deadbolt by turnpiece inside, emergency release outside. Inside knob/lever retracts deadbolt and latch simultaneously. Auxiliary latch deadlocks latch.			 LH
ELECTRIFIED FUNCTIONS			
ELECTRICALLY LOCKED (Fail Safe): Outside always locked electrically. Open by key outside, switch or loss of power. Auxiliary latch deadlocks latch. Inside always open.			 EL
ELECTRICALLY UNLOCKED (Fail Secure): Outside always locked until unlocked by key or electrically energized. Auxiliary latch deadlocks latch. Inside always open.			 EU

MORTISE LOCKSET FUNCTIONS


DOUBLE CYLINDER FUNCTIONS				
ANSI #	Cam	Strike	Marks Function	
F09: ENTRANCE Latch by knob/lever either side except when outside knob/lever locked by key inside, latch retracted by key outside. Outside remains locked. Auxiliary latch deadlocks latch.	I/S 2101 2106	5036	I/S O/S	G
F11: DORMITORY Latch by knob/lever either side except when outside knob/lever locked by stop-button or projected deadbolt. Deadbolt by key either side. Inside knob/lever retracts latch and deadbolt simultaneously leaving outside locked. Deadbolt deadlocks latch.	I/S 2102 2106	9035		FA
F14: STOREROOM Latch by knob/lever either side. Deadbolt by key either side. Deadbolt deadlocks latch.	I/S 2102 2106	9035		C
F30: INSTITUTION Both knob/levers rigid. Auxiliary latch deadlocks latch. Latch by key either side.	I/S 2101 2106	5036		WW
F32: INTRUDER LATCH BOLT Latch by knob/lever either side except when outside knob/lever is locked from inside or outside by key. Latch operated by key from inside or outside. Auxiliary latch, deadlocks latch. Inside always open.	I/S 2105 2105	5036		GC
CLASSROOM SECURITY Latch bolt retracted by knob/lever from either side unless outside is locked by key from either side. Auxiliary latch deadlocks latch bolt when door is locked. Inside knob/lever is always free for immediate egress.	I/S 2105 2105	5036		GG
CLASSROOM SECURITY Latch bolt retracted by knob/lever from either side except when locked by key from either side. Auxiliary latch deadlocks latch	I/S 2101 2105	5036		GW
CLASSROOM SECURITY Latch by lever either side except when outside lever is locked or unlocked by key from either side. With outside locked, exterior key will retract the latch allowing the outside to remain locked. Inside always free for egress. Auxiliary latch deadlocks latch.	I/S 2101 2105	5036		GJ
CLASSROOM SECURITY w/HOLDBACK Latch bolt retracted by knob/lever from either side unless outside is locked by key from either side. When locked, latch bolt retracted by key outside or knob/lever inside. Auxiliary latch deadlocks latch bolt when door is locked. Depress inside knob/lever and turn key 360° for holdback feature. Inside knob/lever always free for immediate egress.	2101 2105	5036		GR JC
DEADLOCK Latch by knob/lever either side. Deadbolt by key either side; latch remained unlocked at all times. Note: With this function deadbolt protrusion is 13/16	2102 2106	9035		CT
F33: DORMITORY Latch by knob/lever either side except when projected deadbolt locks outside knob/lever and deadlocks latch. Deadbolt and latch by key either side. Inside knob/lever retracts latch and deadbolt simultaneously, automatically unlocking outside knob/lever.	I/S 2102 2106	9035		FX, GW

DOUBLE CYLINDER FUNCTIONS (Con't)				
ANSI #	Cam	Strike	Marks Function	
F33: DORMITORY Latch by knob/lever either side except when projected deadbolt locks outside knob/lever and deadlocks latch. Deadbolt and latch by key either side. Inside knob/lever retracts latch and deadbolt simultaneously, automatically unlocking outside knob/lever.	I/S 2102 2106	5035		FC
F35: STORE DOOR Latch by knob/lever either side except when outside knob/lever locked by stop-button in front; then by key outside. Deadbolt by key either side. Deadbolt deadlocks latch.	I/S 2102 2106	9035		AC
NON-KEYED FUNCTIONS				
ANSI #		Strike	Marks Function	
F01: PASSAGE Latch by knob/lever either side.		9035	I/S O/S	N
F02: BATHROOM* Latch by knob/lever either side. Deadbolt by turnpiece inside. Deadbolt deadlocks latch. To unlock from outside, remove emergency button, insert emergency key in access hole & turn. Optional coinkey assembly available.		9035		L
F19: PRIVACY* Latch by knob/lever either side except when projected deadbolt locks outside knob/lever and deadlocks latch. Deadbolt by turnpiece inside. Inside knob/lever retracts latch and deadbolt simultaneously, automatically unlocking outside knob/lever. To unlock from outside, remove emergency button, insert emergency key in access hole and turn. Optional coinkey assembly available.		9035		LF
F22: PRIVACY Latch by knob/lever either side except when outside knob/lever is locked by inside turnpiece. Turning inside knob/lever or closing door unlocks outside lever. To unlock from outside, remove emergency button, insert emergency key in access hole and turn. Optional coinkey assembly available.		9035		LJ
F31: EXIT Latch by knob/lever inside, no trim outside. Auxiliary latch deadlocks latch. None removable blank trim: F26 option		5036		EX
DEADBOLT FUNCTIONS				
F16: DEADLOCK Deadbolt by key either side.	I/S 2102	9035		T
F17: DEADLOCK Deadbolt by key outside and turnpiece inside.	2102	9035		P
F18: DEADLOCK Deadbolt by key one side only.	2102	9035		S
F29: DEADLOCK Deadbolt by key outside. Inside turnpiece will retract but will not project deadbolt.	2102	9035		SC
DEADLOCK FUNCTIONS				
E06072: CYLINDER BY TURNPIECE Deadbolt by inside turnpiece or outside key.	2102			K
E06082: COMMUNICATING SINGLE CYLINDER* Deadbolt by key from one side only.	2102			L
E06062: DOUBLE CYLINDER Deadbolt by key either side.	2102			M
E06092: CLASSROOM Deadbolt by outside key. Turnpiece will retract but not project deadbolt.	2102			S
TURNPIECE Deadbolt by inside turnpiece.	2102			X
*PRIVACY INDICATOR AVAILABLE				

MORTISE LOCKSET PARTS RK, RL

ROSES	RR: 2-9/16" dia.	RW: 2-9/16" dia.	RQ: 2-1/4" dia.	RS: 2-1/4" dia.	RX: 2-1/2" sq.	*RK: 2-1/2" sq.	*RL: 2-1/2" sq.
					 Wrought	 Forged	 Forged

Knob / Rose Kits




KRW10

KRS20

ROSE WITH RING	PLAIN ROSE	SMALL ROSE W/RING	SMALL ROSE	DESCRIPTION	FINISH GROUPS					
					3	10, 10B	15	26	32D	ROSE RK*
KRR10	KRW10	KRQ10	KRS10	Round knob/ball assembly	154.68	—	—	—	147.70	+77
KRR20	KRW20	KRQ20	KRS20	Ball knob/ball assembly	154.68	—	—	—	147.70	
					NO FINISH					
Complete knob/rose assemblies both sides (includes spindles).										

Lever / Rose Kits

* Specify handing



KRW031



KRQ55




KRW78




KRW92




KRR57★



KRW72




KRS82




KRW83★



KRW77



KRW86




KRW96

PART #		DESCRIPTION	FINISH GROUPS							
			3	4	26D	15	10, 10B, 10, 19, 26	32D	ROSE RK, RL	ROSE RX
ROSE WITH RING RR	SMALL ROSE WITH RING RQ	Complete lever/rose assemblies both sides (includes spindles).								
KRR57	KRQ57	Monaco lever/rose kit	167.96	251.95	251.95	251.95	–	–		
KRR55	KRQ55	Brompton lever/rose kit	167.96	251.95	251.95	251.95	–	–		
PLAIN ROSE RW	SMALL ROSE RS	Complete lever/rose assemblies both sides (includes spindles).							ROSE RK, RL	ROSE RX
KRW031	KRS031	Copa lever/rose kit	251.95	251.95	–		251.95	251.95	251.95	+20 FOR ALL FINISHES
KRW37A	KRS037A		X	X	–	X	X	X		
KRW72	KRS72	Towne lever/rose kit	251.95	251.95	251.95	251.95	285.69	-		
KRW77	KRS77	Maxwell lever/rose kit	251.95	251.95	251.95	251.95	285.69	255.65		
KRW78	KRS78	Omni lever/rose kit	251.95	251.95	251.95	251.95	285.69	255.65		
KRW82	KRS82	Plaza lever/rose kit	251.95	251.95	251.95	251.95	285.69	255.65		
KRW83	KRS83	Dayton lever/rose kit	251.95	251.95	251.95	251.95	285.69	255.65		
KRW86	KRS86	Crescent lever/rose kit	251.95	251.95	251.95	251.95	285.69	-		
KRW92	KRS92	American lever/rose kit	251.95	251.95	251.95	251.95	285.69	255.65		
KRW96	KRS96	Titan lever/rose kit	251.95	251.95	251.95	251.95	285.69	255.65		


MORTISE LOCKSET PARTS

Dummy Cylinder, Collars & Turnpieces



PART #	DESCRIPTION	FINISH GROUPS				
		3, 26D	4	10, 10B, 26	32	32D
1604	Emergency hole cover	9.20	–	–	–	–
9271	Tapered collar, solid brass, 5/16" high	20.44	–	22.09	25.34	22.09
9273	Spring collar, 7/16" high	13.81	–	–	–	–
9275	Mortise spacer, wrought brass, 1/8" high	8.29	–	–	–	–
9277	Plastic spacer ring, 1/16"	6.44	–	–	–	–
9279	Tapered collar, wrought brass, 3/8" high	15.65	–	20.25	17.49	15.65
A7271	Square cylinder collar, 1-3/4" x 5/16"	34.06	–	34.06	34.06	59.83
A7616	Square Turnpiece Rose	47.67	62.21	54.95	54.95	62.21
A9276	Collar, wrought brass w/insert, 1/2" high	20.25	–	27.61	27.61	27.51
A9615	Turnpiece	37.98	53.33	45.24	53.33	45.24


Strikes



TYPE	PART #	A	B	C*	D	FINISH GROUPS	
						S3	3, 10, 10B, 32, 32D
No Lip	4035	1-1/8"	3-1/8"	–	–	7.68	13.27
	4035-1	1-1/8"	3-1/2"	3-1/2"	2-1/2"		
	9038	1-1/8"	4-7/8"	–	2-1/2"	8.38	–
	3135	1-1/4"	4-7/8"	–	–	–	17.45
Curved Lip	5035 †	1-1/4"	4-7/8"	1-1/4"	4-1/8"	–	18.85
	5036 †	1-1/4"	4-7/8"	1-1/4"	4-1/8"	–	20.95
	9035	1-1/4"	4-7/8"	1-1/4"	4-1/8"	7.68	20.95
	9035-1.5	1-1/4"	4-7/8"	1-1/2"	4-1/8"	–	29.32
Straight Lip	5035M †	1-1/4"	4-7/8"	7/8"	4-1/8"	–	23.04
	5036M †	1-1/4"	4-7/8"	7/8"	4-1/8"	–	23.04
	9035M	1-1/4"	4-7/8"	7/8"	4-1/8"	–	23.04
Dust Box	9036	Dust box for 9038 strike, plastic				7.68	–
	4036	Dust box for 4035 strike, plastic				6.28	–

† Specify handing.
Extended lip strikes from 1-1/4" - 2", Add \$16.
★Extended lip strikes over 2", consult factory.

Spindles



PART #	DESCRIPTION	
9287	2-1/2" LONG, HOOK SPINDLE, 2 PIECE	13.96
9289	4-3/4" LONG, SWIVEL SPINDLE	13.96
A5611	SPINDLE/SPRING ASSEMBLY FOR LEVERS, 5/16", 1" L	13.96
A5613	SPINDLE/SPRING ASSEMBLY FOR LEVERS, 5/16", 1-5/8" L	13.96
A5685-BE	CAM/SPINDLE SPRING ASSEMBLY EXTERIOR	23.02
A5684-BE	CAM/SPINDLE SPRING ASSEMBLY INTERIOR	23.02

MORTISE LOCK INDICATORS

Indicators



Use with Mortise Lock
SK500
(Sold Separately)



SK500CYL/15,
outside indicator
with Cylinder hole
\$250.00 list
Handing is required



SK500CK/15,
outside indicator
w/Coin key slot
\$250.00 list




SK500TP/15,
inside indicator
with Turn Piece
\$250.00 list


OPTION CODE	DESCRIPTION	PRICE
A60	SK500CYL/15 Outside Indicator with cylinder hole	250.00
A61	SK500CK/15 Outside Indicator with Coin Key Slot	250.00
A62	SK500 TP/15 Inside Indicator with Turn Piece	250.00
A63	SK500CYL/15, Cylinder Outside X SKA500TP/15 Turn piece inside - Combo A60X A62 - CYL X TP	500.00
A65	SK500CYL/15, Cylinder Outside X SK500CYL/15, Cylinder Inside - Combo A60 X A65 - CYL X CYL	500.00
A66	SK500-TB. Thu bolt kit	
A67	SK500CK/15, Coin turn outside X SKA500TP/15 Turn piece inside - Combo A61 X A62 - CK X TP	500.00
Non Deadbolt Privacy Locks		
LG	Latch by knob/lever either side except when outside knob/ lever is locked by inside turnpiece. Turning inside knob/ lever unlocks outside lever. To unlock from outside, key outside or Optional coin key assembly available	
Dead Bolt Function		
LF	F19: PRIVACY* Latch by knob/lever either side except when projected deadbolt locks outside knob/lever and deadlocks latch. Deadbolt by turnpiece inside. Inside knob/lever retracts latch and deadbolt simultaneously, automatically unlocking outside knob/lever. To unlock from outside, remove emergency button, insert emergency key in access hole and turn. Optional coinkey assembly available.	
Example of Part number	All Dead Bolt functions will work with the SK 500 series indicators	
5RW82LG/32D-A67-LH	ASK500-TB, Thu bolt kit \$447.08 Lock + \$500 Indicator =	947.08

Prelim Data Subject to change without notice. Note Pricing quoted in USD, subject to change without prior notice; surcharges and tariffs may apply

PART #	DESCRIPTION	OPTION CODE	Finish Groups				
			3, 26D	4	10, 10B, 19, 26	32	32D
SKA200/32D	Indicator	A50	—	—	—	—	221.65
SKA200-CK/32D	Indicator with Coin Turn	A51	—	—	—	—	221.65
SKA200-TP/32D	Indicator with Turn Piece	A52	—	—	—	—	221.65
SKA210/32D	Indicator with Cylinder Prep	A53	—	—	—	—	221.65
SKA210-CK/32D	Indicator with Cylinder Prep and Coin Turn	A54	—	—	—	—	221.65
SKA210-TP/32D	Indicator with Cylinder Prep and Turn Piece	A55	—	—	—	—	221.65
	Phillip Head Screws only	A56					
A1605	Emergency coin key	A15	58.18	58.18	58.18	58.18	—
A7615	Occupancy indicator, coin key round	A17	—	—	—	—	58.00
A9119H	Occupancy indicator, teardrop for rose trim coin key	A42	—	91.90	—	—	—
	SKA 200 Series will work with all lock Mortise functions. These indicators can be used with sectional trim or mounted on top of Drake plate and LA plate designs						
	Examples of Ordering						
	5RW031LF/32D-A51-A51 Grade one mortise lockset section trim privacy dead bolt lockset with an Indicator w/ cylinder hole outside & Indicator inside with Thumb Turn						



SKA200



SKA200-CK
(Rose Trims Only)



SKA200-TP




SKA200-CK




SKA210-CK
(Rose Trims Only)



SKA210-TP
(Rose Trims Only)



A7615
ONLY 32D



A1605



A9119H

TRIM LOCK PARTS

How to Order Example for Knob & Lever Assemblies					
DR	02	-	30	/	15
1. Plate/Rose Design	2. Trim Description	Dash	3. Knob/Lever Design	Slash	4. Finish

PLATE/ROSE DESIGN		TRIM DESCRIPTION	KNOB DESIGN		FINISH
___ CL	___ RR	___ 01 Outside knob/lever/cylinder	___ 10		___ 3
___ CP	___ RW	___ 02 Inside knob/lever/turnpiece	___ 20		___ 4
___ CR	___ RQ	___ 03 Inside knob/lever/cylinder			___ 10
___ DR	___ RS	___ 04 Inside knob/lever only			___ 10B
___ NY	___ RX	___ 05 Outside cylinder only			___ 15
___ NS		___ 06 Outside knob/lever/emergency coinkey			___ 26
		___ 07 Outside hotel			___ 26D
		___ 08 Outside knob/lever only			___ 32D
			LEVER DESIGN		___ Special
			___ 44	___ 82	___ 32
			___ 55	___ 83	
			___ 57	___ 86	
			___ 72	___ 92	
			___ 77	___ 96	
			___ 78	___ 031	
				___ 037A	
				___ 002	

Mortise Parts, Trim

TRIM LOCK PARTS

PLATE/ROSE DESIGN		3	19	10	10B	15	26D	32D
CLASSIC CL		-	-	-	-	-	-	75.48
CAPITOL CP		122.43	120.59	120.59	120.59	-	-	112.30
CROWN CR		154.65	176.74	176.74	176.74	154.65	154.65	154.65
DRAKE DR		186.87	203.44	203.44	203.44	186.87	186.87	193.31
SCHOOL LA		-	-	-	-	-	-	176.74

TRIM LOCK PARTS

PLATE/ROSE DESIGN		3	19	10	10B	15	26D	32D
NEW YORKER NY 10" PLATE		43.27	–	–	–	–	53.39	–
NEW YORKER NS 7" PLATE		31.52	–	–	–	–	43.27	–
2-9/16" DIA. ROSE W-RING RR		102.18	123.35	123.35	123.35	113.23	102.18	102.18
2-9/16" DIA. PLAIN ROSE RW		102.18	123.35	123.35	123.35	113.23	102.18	102.18
2-1/4" DIA. SMALL ROSE W-RING RQ		102.18	123.35	123.35	123.35	113.23	102.18	102.18
2-1/4" DIA. SMALL ROSE RS		102.18	123.35	123.35	123.35	113.23	102.18	102.18
2-1/2" SQ. SQUARE ROSE RX		102.18	123.35	123.35	123.35	113.23	102.18	102.18
2-1/2" SQ. SQUARE ROSE RK		171.22	190.55	190.55	190.55	181.35	171.22	171.22
SQUARE TURNPIECE ROSE A7616	OUTSIDE 	174.90	201.60	201.60	201.60	201.60	182.27	182.27
	INSIDE	56.16	62.60	62.60	62.60	62.60	62.60	62.60
2-1/2" SQ. SQUARE ROSE RL		182.27	201.60	201.60	201.60	201.60	182.27	182.27

TRIM LOCK PARTS

Knob / Lever Design

KNOB/LEVER	FINISH GROUPS									
		3	19	4	10	10B	15	26	26D	32D
ROUND KNOB  10		91.13	–	–	111.38	111.38	–	111.38	111.38	91.13
BALL KNOB  20		91.13	–	–	111.38	111.38	–	111.38	111.38	91.13
METROPOLITAN LEVER  002		154.65	185.95	185.95	204.36	204.36	185.95	204.36	204.36	194.24
COMMERCE LEVER  037A		154.65	185.95	185.95	204.36	204.36	185.95	204.36	204.36	194.24
LUCIDA LEVER  47C		–	185.95	185.95	204.36	204.36	185.95	204.36	204.36	182.27
COPA LEVER  031		154.65	185.95	185.95	204.36	204.36	185.95	204.36	204.36	–
MONACO LEVER  57		185.95	185.95	185.95	204.36	204.36	185.95	204.36	204.36	–
BROMPTON LEVER  55		185.95	185.95	185.95	204.36	204.36	185.95	204.36	204.36	–
TOWNE LEVER  72		154.65	185.95	185.95	204.36	204.36	185.95	204.36	204.36	–
MAXWELL LEVER  77		154.65	185.95	185.95	204.36	204.36	185.95	204.36	204.36	182.27
OMNI LEVER  78		154.65	185.95	185.95	204.36	204.36	185.95	204.36	204.36	–
PLAZA LEVER  82		154.65	185.95	185.95	204.36	204.36	185.95	204.36	204.36	182.27
DAYTON LEVER  83		154.65	185.95	185.95	204.36	204.36	185.95	204.36	204.36	185.95
CRESCENT LEVER  86		154.65	185.95	185.95	204.36	204.36	185.95	204.36	204.36	182.27
AMERICAN LEVER  92		154.65	185.95	185.95	204.36	204.36	185.95	204.36	204.36	182.27
TITAN LEVER  96		154.65	185.95	185.95	204.36	204.36	185.95	204.36	204.36	182.27

How To Order CYLINDRICAL LOCKSETS

How To Order Example for Cylindrical Locksets					
195	AB	/	26D	-	G3
<i>1. Lockset Series</i>	<i>2. Marks Function</i>	<i>Slash</i>	<i>3. Finish</i>	<i>Dash</i>	<i>4. Options</i>

1	SERIES
Cylindrical Locksets:	110, 110R, 175, 175R, 195, 195R, 295, 295R, 495, 495R

2	CYLINDRICAL FUNCTIONS		
MARKS #	FUNCTION	ANSI #	
N	-	PASSAGE	F75
L	-	PRIVACY	F76
LK	-	HOSPITAL/PRIVACY	F76 MOD.
P	-	PATIO	F77
DC	RDC	COMMUNICATING	F80
A	RA	ENTRY	F81
B	RB	ENTRY	F82A
AQ	-	EXIT	F83
S	RS	CLASSROOM	F84
F	RF	STOREROOM	F86
DW	RDW	INSTITUTION	F87
DA	RDA	VESTIBULE	F88
FQ	-	EXIT	F89
T	RT	CORRIDOR	F90
TO	-	TIME OUT	
TK	-	HOSPITAL/PRIVACY	F90 MOD.
GB	RGB	STORE DOOR (95 SERIES ONLY)	F91
BS	-	SERVICE STATION LOCK	F92
H	-	HOTEL	F93
AB	RAB	ENTRANCE	F109
DB	RDB	CLASSRM. INTRUDER	F110
NB	-	COMMUNICATING PASSAGE	F111
FB	-	COMMUNICATING STOREROOM	F112
SB	RSB	COMMUNICATING CLASSROOM	F113
FEL	RFEL	ELECTRONICALLY LOCKED	
FEU	RFEU	ELECTRONICALLY UNLOCKED	
DUMMY TRIM			
DO	DUMMY TRIM OUTSIDE		
DT	FULL DUMMY		

4	OPTIONS	
TRIM MODIFICATIONS	CODE	PRICE
Tactile knob/lever, coated ext. only	A1	38.00
Tactile knob/lever, knurled	A4	38.00
Tactile knob/lever, coated int. & ext.	A18	78.00
DOOR THICKNESS	CODE	PRICE
2" (50 mm)	D1	NC
2-1/4" (57mm)	D2	48.00
Over 2-3/8" - 4"	D9	409.00
LATCH	CODE	PRICE
2-3/4" backset, 1-1/8" x 2-1/4" face	E4	NC
2-3/8" backset, 1" x 2-1/4" face	E6	NC
5" backset, 9/16" throw, Gr. 1	E9	30.00
3-3/4" backset, 9/16" throw, Gr. 1	E10	120.00
2-3/8" backset, 1-1/8" x 2-1/4" face	E11	9.00
2-3/4" backset, 1" x 2-1/4" face	E12	9.00
TRIM CHANGES	CODE	PRICE
Yale/Accentra conventional	F7	15.00
Sargent conventional cylinder	F8	15.00
Corbin Russwin conventional cylinder	F9	15.00
Corbin Russwin 6 pin IC core (LFIC)	F12	22.00
Corbin Russwin 7 pin IC core (LFIC)	F13	22.00
Yale/Accentra 6 pin IC core (LFIC)	F14	15.00
Yale/Accentra 7 pin IC core (LFIC)	F15	15.00
Schlage 6 pin IC core (LFIC)	F19	15.00
Sargent IC core (LFIC)	F20	15.00
Medeco IC core large format	F21	15.00
CYLINDER	CODE	PRICE
Special optional keyway	G2	24.00
Less cylinder	G3	Deduct 10.00
STRIKE	CODE	PRICE
4-7/8" ASA strike	S1	9.00
2-3/4" "T" strike	S3	NC

10 LINE GRADE 2 CYLINDRICAL KNOBSETS

		ANSI-A156.2 • Grade 2 Plus 3 Hour Fire Rating				Series 110/110R • 2-3/8" Backset Series 210/210R • 2-3/8" Backset	
10 Series Knobsets Shown Below				Standard Features			
110 210				• Backset: 2-3/8" • Latch #1138, Front: 1" x 2-1/4"; Throw: 1/2"; Stainless steel nose • Knobs: 2-1/4" dia. (110) round; 2-3/16" dia. (210) ball • Roses: Adjustable both sides; Steel reinforced 2-3/4" dia. • Strike: #1136, 2-3/4" "T" strike • Door thickness: 1-5/8" to 1-7/8" • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys			
MARKS #		FUNCTION	ANSI #	FINISH GROUPS			
				COMM CYL		SFIC PREP	
COMM.CYL.	SFIC PREP			32D	3, 10, 10B, 32	32D	3, 10, 10B, 32
N	–	PASSAGE	F75	118.52	151.48		
L	–	PRIVACY	F76	142.06	173.46		
P	–	PATIO	F77	142.06	175.81		
DC	RDC	COMMUNICATING	F80	189.94	222.12	422.47	493.47
A	RA	ENTRY	F81	167.96	199.36	422.47	493.47
B	RB	ENTRY	F82A	167.96	199.36	336.48	407.58
AB	RAB	ENTRY	F109	167.96	199.36	336.48	407.58
AQ	–	EXIT	F83	156.97	188.37		
S	RS	CLASSROOM	F84	167.96	199.36	336.48	407.58
F	RF	STOREROOM	F86	167.96	199.36	336.48	407.58
DW	RDW	INSTITUTION	F87	190.72	222.90	422.47	493.47
DA	RDA	VESTIBULE	F88	190.72	222.90	422.47	493.47
FQ	–	EXIT	F89	156.97	188.37		
DO	–	DUMMY TRIM OUTSIDE	–	124.01	139.71		
DT	–	FULL DUMMY TRIM	–	130.29	160.90		
NB	–	COMMUNICATING PASSAGE	F111	127.15	142.85		
FB	RFB	COMMUNICATING STOREROOM	F112	178.16	197.00	295.16	325.00
SB	RSB	COMMUNICATING CLASSROOM	F113	178.16	197.00	295.16	325.00


KNOBS ARE PACKED 12 PER CASE

NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory

• SFIC Core Models: Tailpieces included, core not included

❖ SFIC Core Models in US3 Finish: Add \$42.00 to list price

OPTIONS	CODE	PRICE
For 2" doors	D1*	NC
For 2-1/4" doors	D2*	48.00
2-3/4" backset, 1-1/8" x 2-1/4" face	E4	8.00
3-3/4" backset, 9/16" throw, Gr. 1	E10	68.00
Less cylinder	G3	-10.00
4-7/8" ASA strike with curved lip	S1	9.00



*Prices are for centered on door. For offset, call for price.




★ Standard & HI-SECURITY™ SFIC Core Models:

Interchangeable Core models for 6 or 7 pin cores (not included).



Accepts: Marks, Marks HI-SECURITY™, Medeco®, KeyMark™, Falcon, Schlage® small format & Best®. **SFIC Core Tailpieces ARE Included.**

95 LINE GRADE 1 CYLINDRICAL SURVIVOR LEVERSETS




BHMA CERTIFIED				ANSI-A156.2 • Grade 1 3 Hour Fire Rating				SURVIVOR SERIES Series 195/195R, 295/295R, 495/495R • 2-3/4" Backset		
95 Series Leversets Shown Below								Standard Features		
								• Backset 2-3/4" • Latch #1834, Front: 1-1/8" x 2-1/4"; Throw: 9/16"; Stainless steel nose • Levers: Solid cast Zamac; w/ 1/2" return (except 395 & 495) • Roses: Thru-bolted, 3-7/16" dia., spring loaded 2-#10 thru-bolts • Strike: #1135, 4-7/8" ASA curved lip strike • Door thickness: 1-5/8" to 1-7/8"; For 1-3/8" door use K1904 spacer - Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys		
MARKS #		FUNCTION		ANSI #	FINISH GROUPS					
COMM. CYL.	SFIC				26D, 19	4, 10, 10B, 26	3			
N	–	PASSAGE	F75	319.93	381.98	391.90				
L	–	PRIVACY	F76	337.87	403.65	403.65				
LK	–	HOSPITAL/PRIVACY	F76 MOD.	360.30	424.58	424.58				
P	–	PATIO	F77	334.13	399.16	399.17				
DC	RDC	COMMUNICATING	F80	388.62	450.74	450.74				
A	RA	ENTRY	F81	352.07	416.36	416.36				
B	RB	ENTRY	F82A	352.07	416.36	416.36				
AB	RAB	ENTRY	F109	352.07	416.36	416.36				
AQ	–	EXIT	F83	341.61	407.39	420.54				
S	RS	CLASSROOM	F84	352.07	416.36	416.36				
F	RF	STOREROOM	F86	352.07	416.36	416.36				
DW	RDW	INSTITUTION	F87	387.95	444.09	444.10				
DA	RDA	VESTIBULE	F88	387.95	444.09	444.10				
FQ	–	EXIT	F89	341.61	407.39	407.39				
T	RT	CORRIDOR	F90	360.30	424.58	424.58				
TO	–	TIME OUT		334.13	399.16	399.17				
TK	–	HOSPITAL/PRIVACY	F90 MOD.	335.46	399.16	399.17				
GB	RGB	STORE DOOR	F91	478.40	521.75	521.76				
BS	RBS	SERVICE STATION LOCK	F92	360.30	424.58	424.58				
H	–	HOTEL	F93	396.18	458.96	458.97				
DB	RDB	CLASSROOM INTRUDER	F110	427.57	492.60	520.96				
DO	–	DUMMY TRIM OUTSIDE	–	89.44	117.34	182.31				
DT	–	FULL DUMMY TRIM	–	284.05	348.34	348.34				
NB	–	COMMUNICATING PASSAGE	F111	301.99	364.78	364.78				
FB	RFB	COMMUNICATING STOREROOM	F112	355.07	411.13	411.13				
SB	RSB	COMMUNICATING CLASSROOM	F113	355.07	411.13	411.13				
FEL	RFEL	ELECTRICALLY LOCKED*	–	514.28	579.31	579.31				
FEU	RFEU	ELECTRICALLY UNLOCKED*	–	514.28	579.31	579.31				
Marks USA Antimicrobial Finish Available - Option Code: AM - Add \$24						LEVERS ARE PACKED 6 PER CASE				
NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory										
*ELECTRIFIED FUNCTIONS: 100% Duty Cycle 24V AC/DC, supplied with bridge rectifier : EU - 210 ma; EL - 125 ma						• SFIC Models: Tailpieces included, core not included				
OPTIONS		CODE	PRICE - 195	295	495	195 Series Leverset Shown Below		295 Series Leverset Shown Below		
For 2" doors		D1*	NC	NC	NC					
For 2-1/4" doors		D2*	48.00	48.00	48.00					
Over 2-1/4" - 4" thickness		D9*	409.00	409.00	409.00					
2-3/8" backset, 1" x 2-1/4" face		E6	NC	NC	NC					
5" backset, 9/16" throw, Gr. 1		E9	30.00	30.00	30.00					
3-3/4" backset, 9/16" throw, Gr. 1		E10	30.00	30.00	30.00					
Less cylinder		G3	-10.00	-10.00	-10.00					
2-3/4" "T" strike		S3	NC	NC	NC					
AMERICAN LEVER ONLY Accepts:										
Yale/Accentra conventional cylinder		F7	15.00	–	–					
Sargent conventional cylinder		F8	15.00	–	–					
Corbin Russwin conventional cylinder		F9	15.00	–	–					
Corbin Russwin 6 pin IC core		F12	22.00	–	–					
Corbin Russwin 7 pin IC core		F13	22.00	–	–					
Yale/Accentra 6 pin IC core		F14	15.00	–	–					
Yale/Accentra 7 pin IC core		F15	15.00	–	–					
Schlage 6 pin IC core		F19	15.00	–	–					
Sargent IC core		F20	15.00	–	–					
Medeco IC core large format		F21	15.00	15.00	–					
★ Standard & HI-SECURITY™ SFIC Models: Interchangeable Core models for 6 or 7 pin cores (not included). Accepts: Marks, Marks HI-SECURITY™, Medeco®, KeyMark™, Falcon, Schlage® small format & Best®. SFIC Tailpieces ARE Included.										

*Prices are for centered on door. For offset, call for price.

75 LINE GRADE 2 CYLINDRICAL SURVIVOR LEVERSETS

BHMA CERTIFIED			ANSI-A156.2 • Grade 2 Plus 3 Hour Fire Rating			SURVIVOR SERIES Series 175/175R, 275/275R, 475/475R • 2-3/4" Backset	
75 Series Leverset Shown Below						Standard Features	
175 American 275 475 Titan Crescent						• Backset: 2-3/4" • Latch #1134, Front: 1-1/8" x 2-1/4"; Throw: 1/2"; Stainless steel nose • Levers: Solid cast Zamac; w/ 1/2" return (except 475) • Roses: Thru-bolted, 3-1/4" dia., spring loaded 2-#10 thru-bolts • Strike: #1145, ASA strike • Door thickness: 1-5/8" to 1-7/8"; For 1-3/8" door use K1904 spacer • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys	
MARKS #		FUNCTION	ANSI #	175	275, 475		
COMM. CYL.	SFIC PREP			26D, 19	26D		
N	–	PASSAGE	F75	139.72	151.59		
L	–	PRIVACY	F76	168.36	180.94		
P	–	PATIO	F77	150.20	162.78		
DC	RDC	COMMUNICATING	F80	199.10	211.68		
A	RA	ENTRY	F81	168.36	180.94		
B	RB	ENTRY	F82A	168.36	180.94		
AB	RAB	ENTRY	F109	168.36	180.94		
AQ	–	EXIT	F83	161.37	173.25		
S	RS	CLASSROOM	F84	168.36	180.94		
F	RF	STOREROOM	F86	168.36	180.94		
DW	RDW	INSTITUTION	F87	201.90	215.87		
DA	RDA	VESTIBULE	F88	203.29	215.87		
FQ	–	EXIT	F89	161.37	173.25		
DO	–	DUMMY TRIM OUTSIDE	–	86.84	99.08		
DT	–	FULL DUMMY TRIM	–	116.67	128.54		
NB	–	COMMUNICATING PASSAGE	F111	120.96	132.74		
FB	RFB	COMMUNICATING STOREROOM	F112	176.75	183.03		
SB	RSB	COMMUNICATING CLASSROOM	F113	176.75	183.03		

OPTIONS	CODE	PRICE - 175	275	475
2-3/8" backset, 1" x 2-1/4" face	E6	NC	NC	NC
5" backset, 9/16" throw, Gr. 1	E9	68.00	68.00	68.00
3-3/4" backset, 9/16" throw, Gr. 1	E10	120.00	120.00	120.00
Less cylinder	G3	-10.00	-10.00	-10.00
2-3/4" T strike	S3	NC	NC	NC
AMERICAN LEVER ONLY Accepts:				
Yale/Accentra conventional cylinder	F7	15.00	—	—
Sargent conventional cylinder	F8	15.00	—	—
Corbin Russwin conventional cylinder	F9	15.00	—	—
Corbin Russwin 6 pin IC core	F12	22.00	—	—
Corbin Russwin 7 pin IC core	F13	22.00	—	—
Yale/Accentra 6 pin IC core	F14	15.00	—	—
Yale/Accentra 7 pin IC core	F15	15.00	—	—
Schlage 6 pin IC core	F19	15.00	—	—
Sargent IC core	F20	15.00	—	—
Medeco IC core large format	F21	15.00	15.00	—


175 Series Leverset Shown Below	275 Series Leverset Shown Below
	
475 Series Leverset Shown Below	
	

★ **Standard & HI-SECURITY™ SFIC Models:** Interchangeable Core models for 6 or 7 pin cores (not included). **Accepts:** Marks, Marks HI-SECURITY™, Medeco®, KeyMark™, Falcon, Schlage® small format & Best®. **SFIC Tailpieces ARE Included.**



CYLINDRICAL LOCK ACCESSORIES

Latches, Strikes, Etc.




LATCH	THROW	Backset: 2-3/8" Front: 1" x 2-1/4"	Backset: 2-3/4" Front: 1-1/8" x 2-1/4"	FUNCTION	FINISH GROUPS		
					26D	3, 32D	10, 10B
GRADE 2	1/2"	1138A	1134A	ENTRANCE	–	41.42	50.63
		1138L	1134L	PRIVACY	–	30.38	41.42
		1138N	1134N	PASSAGE	–	30.38	41.42
		1138P	1134P	PATIO	–	41.42	50.63
GRADE 1	9/16"	–	1834A	ENTRANCE	–	84.69	92.06
		–	1834L	PRIVACY	–	70.88	84.69
		–	1834N	PASSAGE	–	70.88	84.69
		–	1834P	PATIO	–	84.69	92.06




1135




1136



1136-M




1997

1835
1855


1904



K2804



1901




J190


PART	#	DESCRIPTION	FINISH GROUPS	
			3, 32D	10, 10B
STRIKES	1135	4-7/8" ASA strike, curved lip	21.17	21.17
	P1136	2-3/4" "T" strike w/dust box, curved lip	12.89	20.25
	1136-M	2-3/4" "T" strike w/dust box, straight lip	13.81	21.17
SURVIVOR SERIES ALUMINUM SPACER RINGS	K1904	For 1-3/8" door (2 per set), 3-7/16" dia.	36.82	46.02
KNOB SPACER RINGS	K2804	For 1-3/8" door (2 per set), 2-3/4" dia.	36.82	46.95
PART	#	DESCRIPTION	NO FINISH	
EXTENSION LINK For use with 2-3/4" Grade 1 backset latch	1835	3-3/4"	30.38	
	1855	5"		
BRIDGE RECTIFIER	1901	Bridge rectifier 24 V AC/DC (no finish)	46.02	
CYLINDER RETAINER	1997	Lever handle cylinder retainer	5.54	
INSTALLATION TOOL	J295	175/195 installation drill jig	176.74	

CYLINDRICAL LOCK ACCESSORIES

Cylinders



Conventional
Cylinder



SFIC Cylinder
(Will Fit Best® Housings)

FOR
KEYS & KEYING,
SEE PAGE 67

PART #	DESCRIPTION	PRICE
1982	6 Pin, w/2 nickel-silver keys	32.12
*RC1182	6 Pin core, construction core (SFIC)	42.59
RC1187	Plastic core turnknob (SFIC)	7.68

IC core pricing includes KA, KD or MK Keying.

*Consult Factory on pricing of IC Cores when ordered with Locksets.

Specify Tailpiece; Tailpiece Not Included.

Cylindrical Lock Tailpieces



1903



1903S




1903-L



1903S-L




F1903-C




F1903S-C

PART #	CODE	FUNCTION	CYLINDER	PRICE
1903	9	AB, B, DA (ext.), DW, F, FEL, FEU	MARKS 1982	6.98
1903S	S9	S, DA (int.), DB, DC, SB, T		
1903-L	L9	AB, B, DA (ext.), DW, F, FEL, FEU	Arrow PK 100C, Ilco 705, Sargent 13-3266, Abloy, ASSA 65673, 65691	6.98
1903S-L	SL9	S, DA (int.), DB, DC, SB, T		
F1903-C	-	AB, B, DA (ext.), DW, F, FEL, FEU	Schlage 23-001, Primus, GMSK001 Corbin-Russwin 2000-034	6.98
F1903S-C	-	S, DA (int.), DB, DC, SB, T		


Cylindrical IC Core Tailpieces




HR1984



HR1984S



HR1984-G



HR1984S-G



AR1989-Y




AR1989S-Y




AR1999-M



AR1999S-M



F1903C-F19



F1903S-F19



R1981



R1983

For Keying information see Pages 68

PART #	CODE	FUNCTION	CORE	PRICE
HR1984	R1	AB, B, DA (ext.), DW, F, FEU, FEL	6 or 7 pin Marks, KSP, Best*, Falcon, Medeco*, Keymark*, Sargent*, Schlage* Small Format SFIC	6.98
HR1984S	RS	S, DA (int.), DB, DC, SB, T		
HR1984-G	RG9	AB, B, DA (ext.), DW, F, FEU, FEL	6 or 7 pin Corbin Russwin LFIC	6.98
HR1984S-G	RSG	S, DA (int.), DB, DC, SB, T		
AR1989-Y	9MY	AB, B, DA (ext.), DW, F, FEU, FEL	6 or 7 pin Yale/Accentra LFIC	8.38
AR1989S-Y	9SY	S, DA (int.), DB, DC, SB, T		
AR1999-M	9M	AB, B, DA (ext.), DW, F, FEU, FEL	Medeco* LFIC	8.38
AR1999S-M	9SM	S, DA (int.), DB, DC, SB, T	Medeco* LFIC	8.38
F1903C-F19	–	AB, DW, F	6 pin Schlage* Large Format LFIC	8.38
F1903S-F19	–	S, DA, DB, DC, SB, T		
R1981	Spacer			6.98
R1983	Security Disc			6.98

TAILPIECES FOR 195BH

P/N	FITS	OPTION CODE	PRICE
MH119	YALE/ACCENTRA / MEDECO IC CORE	F14, F15, F21	8.38
MH140	CONVENTIONAL (K.I.L.) CYL	N/A	8.38
MH144	SFIC	R, F20	8.38
MH146	CORBIN RUSSWIN LFIC	F12, F13	8.38
MH1903S-C	SCHLAGE IC / CORBIN RUSSWIN K.I.L.	F19, F9	8.38

CYLINDRICAL KNOB/LEVER FUNCTIONS


ANSI# CODE	MARKS FUNCTION
F75.....	N
F76.....	L
F76 (MOD.).....	LK
F77.....	P
F80.....	DC
F81.....	A

ANSI# CODE	MARKS FUNCTION
F82A.....	B
F83.....	AQ
F84.....	S
F86.....	F
F87.....	DW
F88.....	DA

ANSI# CODE	MARKS FUNCTION
F89.....	FQ
F90.....	T
F90 (MOD.).....	TK
F91 (95 Series Leverset ONLY).....	GB
F92.....	BS
F93.....	H

ANSI# CODE	MARKS FUNCTION
F109.....	AB
F110.....	DB
F111.....	NB
F112.....	FB
F113.....	SB

ANSI # CODE	MARKS FUNCTION
F75 PASSAGE: Latch by knob/lever either side.	I/S O/S  N
F76 PRIVACY: Latch by knob/lever either side unless outside knob/lever locked by push-button from inside. Outside unlocks by turning inside knob/lever, outside emergency turn or closing door.	 L
F76 (MOD.) HOSPITAL/PRIVACY: Latch by knob/lever either side unless outside knob/lever locked by push-button from inside. Outside unlocks by turning inside knob/lever, outside turn or closing door. Emergency turn-knob A5 option.	 LK
F77 PATIO: Deadlocking latch by knob/lever either side unless outside knob/lever locked by push-button inside. Unlocks by turning inside knob/lever or closing door.	 P
F80 COMMUNICATING: Key both sides. Locks or unlocks either knob/lever independent of the other. Deadlocking latch.	 DC
F81 ENTRY: Deadlocking latch bolt by knob/lever either side except when outside locked by turn-button inside. When outside locked, key outside or knob/lever inside opens lock. Turn-button operated manually.	 A
F82A ENTRY: Deadlocking latch by knob/lever either side. Outside locked by push-button inside. When outside locked by push-button inside, key opens lock, unlocks push-button. Inside knob/lever always opens latch. Closing door does not release push-button.	 B
F83 EXIT: Deadlocking latch by knob/lever either side except when outside locked by turn-button inside. Inside knob/lever always opens latch. Turn-button operated manually.	 AQ
F84 CLASSROOM: Deadlocking latch by knob/lever inside. Outside knob/lever locked or unlocked by key.	 S
F86 STOREROOM: Deadlocking latch by knob/lever inside, key outside. Outside knob/lever always locked.	 F
F87 INSTITUTION: Both knob/levers always locked. Deadlocking latch by key both sides.	 DW
F88 VESTIBULE: Deadlocking latch by knob/lever either side, except when outside knob/lever locked by key inside. Key outside retracts deadlocking latch. Inside always open.	 DA
F89 EXIT: Deadlocking latch by knob/lever inside. Outside always locked.	 FQ
F90 CORRIDOR: Deadlocking latch by knob/lever either side unless outside locked by key or inside push-button. Unlock by key, turning inside knob/lever or closing door.	 T
TIME OUT LOCK Deadlocking latch by knob/lever either side unless inside knob/lever locked by holding push-button outside. Releasing push-button unlocks inside.	 TO

ANSI # CODE	MARKS FUNCTION
F90 (MOD.) HOSPITAL/PRIVACY: Deadlocking latch by knob/lever either side unless outside locked by knob/lever or inside push-button. Unlock by turn-knob, turning inside knob/lever or closing door. Emergency turn-knob A5 option.	I/S O/S  TK
F91 STORE DOOR (95 Series Leverset ONLY): Deadlocking latch by knob/lever either side except when both knob/levers are locked by key from either side.	 GB
F92 SERVICE STATION LOCK: Deadlocking latch by knob/lever either side unless outside locked by key or inside push-button. Unlock by key, turning inside knob/lever or closing door, except when slotted push-button is turned in locked position. Inside knob/lever always opens latch.	 BS
F93 HOTEL: Deadlocking latch by knob/lever inside. Outside knob/lever always locked. Inside push-button projects indicator on cylinder face shutting out all keys except emergency key. Turning inside knob/lever or closing door releases push-button.	 H
F109 ENTRY: Outside locked by pushing turn-button inside. Key outside opens lock. Rotating inside knob/lever releases button and outside knob/lever. By pushing and turning inside button, outside knob/lever remains locked. Deadlocking latch.	 AB
F110 CLASSROOM INTRUDER: Deadlocking latch by knob/lever either side, except when outside locked by key inside. Key outside locks or unlocks outside. Inside always open	 DB
DUMMY TRIM: Outside only, rigid.	 DO
DUMMY TRIM: Both sides, rigid.	 DT
F111 COMMUNICATING PASSAGE: Blank outside. Deadlocking latch by knob/lever inside.	 NB
F112 COMMUNICATING STOREROOM: Blank outside. Deadlocking latch by key only. Knob/lever always locked.	 FB
F113 COMMUNICATING CLASSROOM: Blank outside. Inside knob/lever locked or unlocked by key. Deadlocking latch.	 SB
ELECTRICALLY LOCKED - FEL (Fail Safe): Outside always locked electrically. Open by key outside, switch or loss of power. Deadlocking latch by lever inside. Lever only.	 FEL
ELECTRICALLY UNLOCKED - FEU (Fail Secure): Outside always locked until unlocked by key or electrically energized. Deadlocking latch by lever inside. Lever only.	 FEU

HOW TO ORDER TUBULAR LOCKSETS

How To Order Example for Tubular Locksets

1	RW	92	N	/	32D	–	S3
1. Lockset Series	2. Rose Design	3. Knob/Lever	4. Marks Function	Slash	5. Finish	Dash	6. Options

1	SERIES
Tubular Locksets	1
Cylindrical Cartridge	1

2	ROSES
ROSES	DESIGN
9602-R	Rose with ring 2-9/16" dia. RR
9602	Plain rose 2-9/16" dia. RW
5602-R	Small rose with ring 2-1/4" dia. RQ
5602	Small rose 2-1/4" dia. RS
7602	Square rose 2-9/16" square RX
7607	Square forged rose 2-9/16" square RK

3	KNOB/LEVER
KNOB	DESIGN
1153	Round, wrought 10
1253	Ball, wrought 20
9631	Ball, forged 30
9609	Eclipse, forged 60
LEVER	DESIGN
SF031	Copa 031
5657	Monaco 57
5672	Towne 72
5677	Maxwell 77
5678	Omni 78
5682	Plaza 82
5683	Dayton 83
5686	Crescent 86
5692	American 92
5696	Titan 96

4	TUBULAR FUNCTIONS
MARKS #	ANSI #
TUBULAR LOCKSETS	
N	PASSAGE F75
L	PRIVACY F76
NB	COMMUNICATING F111
DI	DUMMY TRIM INSIDE
DO	DUMMY TRIM OUTSIDE
DT	FULL DUMMY

5	FINISH
MARKS	ANSI #
US 3	Polished Brass, Clear Coated 605
US 4	Satin Brass, Clear Coated 606
US10	Satin Bronze, Clear Coated 612
US 10B	Dark Bronze, Clear Coated 613
US15	Satin Nickel 619
US 26	Polished Chrome, Plated 625
US 26D	Satin Chrome, Plated 626
US 32	Polished Stainless Steel 629
US 32D	Satin Stainless Steel 630

6	OPTIONS	
TRIM MODIFICATIONS	CODE	PRICE
Tactile knob/lever, coated ext. only	A1	38
Tactile knob/lever, knurled	A4	38
Tactile knob/lever, coated int. & ext.	A18	78
DOOR THICKNESS	CODE	PRICE
1-3/4"	D4	NC
1-3/8"	D5	NC
LATCH	CODE	PRICE
2-3/4" backset, 1-1/8" x 2-1/4" face	E4	8
2-3/4" backset, 9/16" throw, Gr. 1, UL Listed With Cylindrical Cartridge★	E7	68
2-3/8" backset, 1-1/8" x 2-1/4" face	E11	9
2-3/4" backset, 1 x 2-1/4" face	E12	9
Adjustable latch 1-1/8" x 2-1/4" face	E13	8
TRIM CHANGES	CODE	PRICE
For 1-1/2" bore	F6	13
STRIKE	CODE	PRICE
4-7/8" ASA strike	S1	9
2-3/4" "T" strike	S3	NC
3-5/8" Security strike	S4	8
2-1/4" Curved lip strike	S5	NC




★ E7 Option Available: 2-3/8", 2-3/4", 3-3/4" & 5" Backset, for N Function ONLY.

TUBULAR KNOB/LEVER FUNCTIONS

ANSI # CODE	Marks Function
F75 PASSAGE: Latch by knob/lever either side.	I/S O/S  N
F76 PRIVACY: Latch by knob/lever either side unless outside knob/lever locked by push-button from inside. Outside unlocks by turning inside knob/lever, outside emergency turn or closing door.	 L
F111 COMMUNICATING: Blank outside. Deadlocking latch by knob/lever inside.	 NB


ANSI # CODE	Marks Function
DUMMY TRIM INSIDE: Dummy trim inside ONLY.	I/S O/S  DI
DUMMY TRIM OUTSIDE: Dummy trim outside ONLY.	 DO
FULL DUMMY TRIM: Dummy trim both sides.	 DT

ROSE DESIGN RR, RW, RQ, RS, RX*, RK*, RL*

ANSI-A156 • Grade 2			Series 1 • 2-3/8" Backset			
Standard Features			KNOBS	LEVERS		
2-9/16" Diameter RRRWRX 2-1/4" Diameter RQRSL • Backset: 2-3/8", 2-3/4" optional • Front: 1" x 2-1/4" • Thru-bolted screwless knob/lever rose • Concealed mounting screws • Lever support springs • Independent spring loaded captivated spindles • Strike: 2-1/4" full curved lip • Latch support housing • Door thickness: 1-3/8" to 1-3/4" • Privacy function - interior with automatic release			10, 20	002, 031, 037A, 44, 55, 57, 72, 77, 78, 82, 83, 86, 92, 96 *26D N/A 92, 96, 82,86		002, 037A, 82, 86, 92, 96, 031, 037A,
			FINISH GROUPS			
MARKS #	FUNCTION	ANSI #	3, 32D	3, 15, 26D	4, 10, 10B, 19 14, 26	32, 32D
KEYLESS						
N	PASSAGE	F75	180.90	242.94	272.09	233.97
L	PRIVACY	F76	189.12	251.16	280.31	242.19
NB	COMMUNICATING	F111	222.01	234.72	263.12	226.49
DUMMY TRIM						
DI	DUMMY TRIM INSIDE		84.47	116.61	130.06	110.63
DO	DUMMY TRIM OUTSIDE					
DT	FULLY DUMMY		168.94	230.98	259.38	222.01
KNOBS & LEVERS ARE PACKED 16 PER CASE						
NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory *Square Rose RX: Add \$21 / *Square Rose RZ: Add \$125 / *Square Rose RK: Add \$125						
KNOBS	Round Knob 10	Ball Knob 20	Commerce Lever 037A	Metropolitan Lever 002	RR: 2-9/16" dia.	
						
					RW: 2-9/16" dia.	
						
LEVERS	Lucida Lever 47C	Copa Lever 031	Brompton Lever 55	Monaco Lever 57 Specify handing	RQ: 2-1/4" dia.	
						
	Towne Lever 72	Maxwell Lever 77	Omni Lever 78	Plaza Lever 82	RS: 2-1/4" dia.	
						
	Dayton Lever 83 Specify handing	Crescent Lever 86	American Lever 92	Titan Lever 96	RX: 2-1/2" sq. RK: 2-1/2" sq. RL: 1-1/2" sq.	
					 Wrought  Forged 	
OPTIONS			CODE	PRICE	NOTE	
1-3/8" door thickness			D5	0.00		
2-3/4" backset, 1-1/8" x 2-1/4" face			E4	8.00		
2-3/4" backset, 9/16" throw, Gr. 1, UL Listed WITH CYLINDRICAL CARTRIDGE *			E7	84.00	N Function Only	
2-3/8" backset, 1-1/8" x 2-1/4" face			E11	9.00		
2-3/4" backset, 1" x 2-1/4" face			E12	9.00		
4-7/8" ASA strike			S1	9.00		
2-3/4" "T" strike			S3	0.00		
* E7 Option Available: 2-3/8", 2-3/4", 3-3/4" & 5" Backset, for N Function ONLY.						

INTERIOR TUBULAR LOCKSETS

60 Series, Stainless Steel, Commercial Locksets				
Standard Features				
• Latch Face: 1" x 2-1/4" standard		• Backset: 2-3/4" with 2-3/4" T-strike with square corners		• Door thickness: 1-3/8" to 1-3/4"
• Roses: 2-9/16" diameter		• Backset: 2-3/8" with 2-1/4", radius corner full lip strike, option E6, N/C		• Privacy Function with kick-off latch
MARKS #	FUNCTION	ANSI #	FINISH GROUPS (160, 260 & 360)	
			32, 32D	19
N	PASSAGE	F75	146.29	184.40
L	PRIVACY	F76	156.26	194.38
DO	DUMMY TRIM OUTSIDE	-	73.14	92.58
LEVERS ARE PACKED 9 PER CASE Additional finishes, consult factory				


160 Series Finishes: 32D	260 Series Finishes: 32D	360 Series Finishes: 32D
		
		

Square Rose			Round Rose 2 1/4"		
	RX160 RX260 RX360	Add \$34		RS160 RS260 RS360	Add \$34

TUBULAR LOCKSET ACCESSORIES


Strikes, Latches, Support Housing

Tubular Locksets



PART #	DESCRIPTION	BACKSET FRONT	FINISH GROUPS		
			NO FINISH	3, 26	10, 10B, 32, 32D
1631	Support housing	–	8.76	–	–
1536	"T" Strike, 2-3/4" curved lip	–	–	8.77	14.02
1145	4-7/8" ASA strike	–	–	10.52	19.28
1634	Tubular deadbolt	2-3/4"	–	93.81	99.95
1636	Strike, 2-1/4" full curved lip	–	–	8.77	14.02
1634N	Passage latch w/ strike	2-3/4"	–	66.63	85.04
1634L	Privacy latch w/ strike	1" x 2-1/4"	–	79.78	88.54
1638N	Passage latch w/ strike	2-3/8"	–	42.96	54.35
1638L	Privacy latch w/ strike	1" x 2-1/4"	–	54.35	64.88

Latches & Cylindrical Cartridge



LATCH	THROW	Backset 2-3/8"; Front 1" x 2-1/4"	Backset 2-3/4"; Front 1-1/8" x 2-1/4"	FUNCTION	FINISH GROUPS	
					3, 32D	10, 10B
GRADE 2	1/2"	1138A	1134A	ENTRANCE	39.45	48.22
GRADE 1	9/16"	–	1834A	ENTRANCE	80.66	87.67

PART #	DESCRIPTION	NO FINISH
A1430	Cylindrical Cartridge	56.99

HOW TO ORDER DEFENDER LOCKSETS

How To Order Example for Defender Locksets					
145	K	/	32D	–	D1
1. Lockset Series	2. Marks Function	Slash	3. Finish	Dash	4. Options Specify: Keying, Handing & Door Thickness

1	SERIES			
Defender Tubular Deadbolt Locksets			130, 130R	
Defender Cylindrical Cartridge Deadlatch Locksets			145, 145R	
2	TUBULAR FUNCTIONS			
DEADBOLT/DEADLATCHES (* indicates IC Core)			130 Series	145 Series
K	RK*	CYLINDER x TURNPIECE	E0151	E01101
KK	RKK*	CYLINDER x KNOB		
L	RL*	COMM. SINGLE CYLINDER	E0161	E0131
KL	RKL*	CYLINDER x LEVER		E01101
M	RM*	DOUBLE CYLINDER	E0141	E01111
S	RS*	CLASSROOM	E0171	
X		TURNPIECE	E0191	E01121
3	FINISH			
MARKS			ANSI #	
US 3		Polished Brass, Clear Coated	605	
US10		Satin Bronze, Clear Coated	612E	
US 10B		Dark Bronze, Clear Coated	613E	
US 19		Black	622	
US 26D		Satin Chrome, Plated	626	
US 32		Polished Stainless Steel	629	
US 32D		Satin Stainless Steel	630	

DEADBOLT/DEADLATCH FUNCTIONS

ANSI # CODE	MARKS # FUNCTION
----------------	---------------------

130 SERIES:

E0151	 K
E0161	 L
E0141	 M
E0171	 S
E0191	 X

ANSI # CODE	MARKS # FUNCTION
----------------	---------------------


145 SERIES:

E01101	 K
E0131	 L
E01101	 KL
E01111	 M
E01121	 X

ANSI # CODE	Marks Function	
	I/S	O/S
CYLINDER x TURNPIECE: Deadbolt/deadlatch by inside turnpiece or outside key.		K
COMMUNICATING SINGLE CYLINDER: Deadbolt/deadlatch by key from one side only.		L
CYLINDER x LEVER: Deadlatch by key outside. Inside lever always opens latch.		KL

ANSI # CODE	Marks Function	
	I/S	O/S
DOUBLE CYLINDER: Deadbolt/deadlatch by key either side.		M
CLASSROOM: Deadbolt by outside key. Turnpiece will retract but not project deadbolt.		S
TURNPIECE x BLANK PLATE: Deadbolt/deadlatch by inside turnpiece. Blank plate outside.		X


130 SERIES "DEFENDER" TUBULAR DEADBOLTS

ANSI 156.5				Standard Features	
				- Bolt: 1" throw - Unitized assemblies for 2-1/8" bore - Strike: #1335, 2-3/4" x 1-1/8" strike - Door thickness: 1-3/8" to 1-7/8" - Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys 2-3/8" Backset - Latch front: 1" x 2-1/4"	
MARKS #		FUNCTION	ANSI #	FINISH GROUPS	
COMM. CYL.	IC CORE CYL.*			3, 32D, 19	10, 10B, 32
K	RK	CYLINDER x TURNPIECE	E0151	164.82	304.46
L	RL	COMMUNICATING SINGLE CYL	E0161	164.82	304.46
M	RM	DOUBLE CYLINDER	E0141	159.33	298.96
S	RS	CLASSROOM	E0171	143.63	283.27
X	—	TURNPIECE x BLANK PLATE	E0191	115.38	255.01

DEADBOLTS ARE PACKED 24 PER CASE

NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory
• IC Core Models: Core not included

OPTIONS	CODE	PRICE
For 2" door	D1	NC
For 2-1/4" door	D2	48.00
For 1-1/4" - 1-1/2" door	D8	NC
2-3/4" backset, 1-1/8" x 2-1/4" face	E4	8.00
Sargent original cylinder or core	F8	15.00
Less cylinder	G3	-10.00
3-5/8" x 1-1/4" Security strike	S4	8.00



★ Standard IC Core Models: 
Interchangeable Core models for 6 or 7 pin cores (not included).
Accepts: Marks, Medeco KeyMark™, Falcon & Best®. **IC Core Tailpieces ARE Included.**

145 SERIES "DEFENDER" CYLINDRICAL CARTRIDGE DEADLATCHES


ANSI 156.5 • 3 Hour Fire Rating				Standard Features	
				- Series 1 Cylindrical Cartridge - Latch: Grade 1, 9/16" throw, 2-3/4" backset - Unitized assemblies for 2-1/8" bore - Strike: #1136, 2-3/4" strike - Door thickness: 1-3/4"; For 1-3/8" doors use spacer rings K1442/32D - Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys - Latch front: 1-1/8" x 2-1/4"	
MARKS #		FUNCTION	ANSI #	FINISH GROUPS	
COMM. CYL.	IC CORE CYL.*			3, 32D, 19	10, 10B, 32
K	RK	CYLINDER x TURNPIECE	E01101	178.16	317.80
L	RL	COMMUNICATING SINGLE CYL	E0131	178.16	317.80
M	RM	DOUBLE CYLINDER	E01111	193.08	332.72
X	—	TURNPIECE x BLANK PLATE	E01121	151.48	291.12
KL	RKL	CYLINDER x LEVER	E01101	301.39	441.03
KK	RKK	CYLINDER x KNOB		313.17	452.80

DEADLATCHES ARE PACKED 24 PER CASE

NOTE: Split designs and/or finishes are priced at the highest design and/or finish • Special finishes, consult factory
• IC Core Models: Core not included


OPTIONS	CODE	PRICE
For 2" door	D1	NC
For 2-1/4" door	D2	48.00
2-3/8" backset, 1-1/8" x 2-1/4" face	E11	9.00
Sargent original cylinder or core	F8	15.00
Less cylinder	G3	-10.00
4-7/8" ASA strike	S1	9.00

★ Standard IC Core Models: 
Interchangeable Core models for 6 or 7 pin cores (not included).
Accepts: Marks, Medeco KeyMark™, Falcon & Best®. **IC Core Tailpieces ARE Included.**




DEFENDER SERIES ACCESSORIES

Strikes, Latches & Spacers



PART #	DESCRIPTION	FINISH GROUPS		
		NO FINISH	3, 32D	10, 10B, 32
1135	4-7/8" ASA STRIKE	—	21.17	21.17
1136	2-3/4" "T" STRIKE W/DUST BOX	—	9.20	13.82
1137	DUST BOX, PLASTIC, LATCH	5.52	—	—
1335	2-3/4" x 1-1/8" STANDARD STRIKE	—	7.37	9.20
1336	DUST BOX, PLASTIC, DEADBOLT	5.52	—	—
1337	3-5/8" x 1-1/4" HIGH SECURITY STEEL STRIKE, PLATED FINISH	—	62.60	—
K1342	1-3/8" DOOR, ROSE EXTENDERS, 130 Series	—	49.71	61.68
DEADBOLTS				
1334	2-3/4" BACKSET FRONT 1-1/8" x 2-1/4"	—	32.22	40.50
1338	2-3/8" BACKSET FRONT 1-1/8" x 2-1/4"	—	32.22	40.50
K1442	1-3/8" DOOR, 145 SERIES	—	142.68	—

Latches & Cylindrical Cartridge




1834

A1420 Cylindrical Cartridge for use with 145 Series
NOTE: Cylindrical Cartridge is for use with E7* Option ONLY.

LATCH	THROW	Backset 2-3/8" Front 1" x 2-1/4"	Backset 2-3/4" Front 1-1/8" x 2-1/4"	FUNCTION	FINISH GROUPS	
					3, 32D	10, 10B
GRADE 2	1/2"	1138A	1134A	ENTRANCE	41.42	50.63
GRADE 1	9/16"	—	1834A	ENTRANCE	84.69	92.06

PART #	DESCRIPTION	NO FINISH
A1420	Cylindrical Cartridge for use with 145 Series	101.26

Tailpieces & Cylinders



PART #	TAILPIECES FOR 130 DEADBOLTS	PRICE
DOUBLE CYLINDER		
1373	1-5/16" to 1-3/8"	4.89
1374	1-5/8" to 2"	4.89
1375	2-1/8" to 2-3/8"	4.89
SINGLE CYLINDER		
1389	1-3/4" to 2-1/4"	4.89
TAILPIECES FOR 145 DEADLATCHES		
1403	1-5/8" to 1-7/8"	4.19
EF1903-C	2" to 2-1/4"	5.59
F1403-C	1-5/8" to 1-7/8"	5.59
1403-L	1-5/8" to 1-7/8"	5.59
1405-L	2" to 2-1/4"	5.59

REQUEST TO EXIT (REX) CYLINDRICAL ELECTRIFIED LEVERSET






ANSI-A156.2 • Grade 1
3 Hour Fire Rating

 **UL** LISTED

EA195 Series Leverset w/American Lever

Marks USA has developed the Grade 1 "Survivor" Series Cylindrical Lockset incorporating a Request to Exit (REX) switch in both Electrified and Storeroom functions. Activating the inside lever for egress initiates the built-in REX output, providing a momentary signal for the access control REX input, for alarm shunt during egress.



Standard Features

- Backsets: 2-3/4"; 2-3/8", 3-3/4" or 5" optional
- Latch #1834, Front: 1-1/8" x 2-1/4"; Throw: 9/16"; Stainless steel nose
- Levers: Solid cast Zamac w/ 1/2" return (except 395 & 495)
- Rose: Thru-bolted, 3-7/16" dia., spring loaded 2-#10 thru-bolts
- Strike: #1135, 4-7/8" ASA curved lip
- Door thickness: 1-5/8" to 1-7/8" (For 1-3/8" door use K1704 spacer)
- Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys
- Request to Exit Switch: Single pole, double throw, 3 amp, 125 AC, wired either normally open or normally closed
- Electrified functions - 100% duty cycle, 24V/DC standard, supplied with bridge rectifier; 3 watts, .25amps
- 12V/DC Optional, Contact factory for additional options
- Features "The Clutch" • UL Listed, 3 hour fire rating

LOCKSET & LEVER DESIGN	CON. CORE	IC CORE	FUNCTION	ANSI #	DESCRIPTION	FINISH GROUPS	
						26D, 19	3, 4, 10, 10B, 26
EA195 American lever	F	RF	STOREROOM	F86	Latch by lever inside. Outside lever always locked.	499.18	566.68
EA295 Crescent lever							
EA495 Titan lever							
EA195 American lever	FEL	RFEL	ELECTRICALLY LOCKED	—	Outside always locked electrically. Open by key outside, switch or loss of power. Latch by lever inside.	685.20	737.00
EA295 Crescent lever							
EA495 Titan lever							
EA195 American lever	FEU	RFEU	ELECTRICALLY UNLOCKED	—	Outside always locked until unlocked by key or electrically energized. Latch by lever inside.	680.20	737.00
EA295 Crescent lever							
EA495 Titan lever							

LEVERSETS ARE PACKED 6 PER CASE

★ **Standard IC Core Models:** Interchangeable Core models for 6 or 7 pin cores (not included).
Accepts: Marks, Medeco KeyMark™, Falcon & Best®.
IC Core Tailpieces ARE Included.



How To Order Example for REX Leversets

EA195	F	/	26D	—	G3
1. Lockset Series	2. Marks Function	Slash	3. Finish	Dash	4. Options
LOCK SERIES	MARKS FUNCTION		FINISH		OPTIONS
___ EA195	___ F ___ RFEL		___ 3 ___ 4		_____
___ EA295	___ RF ___ FEU		___ 10 ___ 10B		_____
___ EA395	___ FEL ___ RFEU		___ 26 ___ 26D		_____
___ EA495					


Swinging Gate Locks

US PAT.#4,875,725 "NO FALL OUT" FEATURE:

Parts will not fall out when cover is removed.

Replaces Multilock gate locks.

- Easily reversible
- Case, cast aluminum 3-5/8" x 6-1/4" x 1"
- Bronze powder coat finish
- Groove: 1/2" wide x 3/16" deep, all sides for wire gate insertions
- 5 pin cylinder(s)
- Lock only, no keeper furnished




Single
Cylinder Model
*With cylinder
Suffix K
Add \$20

Double
Cylinder Model
*With cylinders
Suffix M
Add \$38

GATE LOCKS ARE PACKED 12 PER CASE

- Easily reversible
- Case, cast aluminum 3-5/8" x 6-1/4" x 1"
- Bronze powder coat finish
- Groove: 1/2" wide x 3/16" deep, all sides for wire gate insertion
- 5 pin cylinder(s)
- Lock only, no keeper furnished













Custom nameplate available.
Consult factory.

Single
Cylinder Model
*With cylinder
Suffix K
Add \$20

Double
Cylinder Model
*With cylinders
Suffix M
Add \$38

GATE LOCKS ARE PACKED 12 PER CASE

W3703




PART #	DESCRIPTION	PRICE
--------	-------------	-------

SERIES HA113 CUSTOM LOCK DIVISION

HOUSING AUTHORITY MORTISE LOCKSET

SERIES HA113			BHMA CERTIFIED
			FINISH GROUPS
MARKS #	FUNCTION	ANSI #	20A
KEYED SINGLE CYLINDER, NO DEADBOLT			
D	OFFICE VESTIBULE		453.66
DW	VESTIBULE		
E	OFFICE	F04	
EW	STOREROOM	F07	
GL	INST. PRIVACY	F26	
J	CLASSROOM	F05	
JM, JR	HOSPITAL (HOLDBACK)	F06	904.18
EL	ELECTRICALLY LOCKED		
EU	ELECTRICALLY UNLOCKED		
KEYED SINGLE CYLINDER, WITH DEADBOLT			
A	ENTRANCE	F08, F10	465.43
B	ENTRANCE	F21	
F	DORMITORY	F12	
FS	DORMITORY		
FW	DORMITORY	F13	499.18
FD	APARTMENT	F20	
H	HOTEL	F15	
LH	SPEC. PRIVACY		
KEYED DOUBLE CYLINDER, NO DEADBOLT			
G	ENTRANCE	F09	499.18
GC	INTRUDER LATCHBOLT	F32	
GG	CLASSROOM SECURITY		
GR	CLASSROOM SECURITY w/HOLDBACK		
WW	INSTITUTION	F30	
KEYED DOUBLE CYLINDER, WITH DEADBOLT			
AC	ENTRANCE	F35	499.18
C	STOREROOM	F14	
FC	INTRUDER DEADBOLT	F34	
FA	DORMITORY	F11	
FX	DORMITORY	F33	
KEYLESS			
N	PASSAGE	F01	396.36
L	BATHROOM	F02	438.75
LF	PRIVACY	F19	
LJ	PRIVACY	F22	481.91
EX	EXIT	F31	453.66
For pricing, finishes and availability, consult factory			

For pricing, finishes and availability, consult factory



Performance Specifications:

Life Test: 1,500,000 cycles minimum.

ANSI Test: Meets or exceeds all operational and security tests of ANSI specifications A156.13-2005 for series 1000, Grade 1.

Fire Test: UL Listed, 3 hour fire rated.

Meets ADA requirements.



Trim Specifications:

"Barrier" Thru-bolted steel lever/plate assemblies with brass machined lever bearings. Screwless forged American levers, 4-1/2" long to meet ADA requirements, fastened to plates with hardened snap rings. Spring loaded 5/16" spindles (no set screws). Dark bronze powder coated finish.

Exterior: Wrought steel lever/plate assembly.

10-1/8" x 4" x 5/64" with 3 concealed welded thru-posts. Center post braces lock body for proper alignment in 1-3/4" thick door. Plate covers cylinder with only the keyway exposed.

Optional Exterior: Plate prepared for IC core cylinder.

Interior: Flat steel lever/plate assembly. 10-3/4" x 3-1/8" x 3/32" thick with 3 each 1/4"-20 mounting bolts. Center bolt passes through lock body to integrate trim with lock.


Cylinder: 1-1/8" long, 6 pin, solid brass with spacing collar concealed under exterior "Barrier" plate; 2 keys.

Strike: 4-7/8" x 1-1/4" x 3/32" thick, 5/8" curved lip. Conforms to ANSI spec., A115.1.

Door Thickness: 1-3/4" standard. Extended range available.

Lock Specifications: 5 Series (2-3/4" Backset)

- Lock Front:** Adjustable bevel steel backplate 1-1/4" x 8" x 7/64" thick. Cover plate 1/16" thick.
- Deadbolt:** Stainless steel w/hardened roll pins, 1" throw.
- Latch:** Solid stainless steel with antifriction latch lever, 3/4" throw (reversible).
- Auxiliary deadlatch:** 1/2" throw (reversible) - (not shown).
- Hubs:** Steel, 9/32" on diamond, 5/16" on square w/security separator.
- Independent exterior and interior lever support springs.
- Hub Follower:** (to lock hub) steel 1/8" thick.
- Hub Stop:** (to limit lever travel) steel 1/8" thick.
- Case:** Stamped steel 3/32" thick, zinc dichromate finish.
- Spindles:** Independent spring-loaded spindles, 5/16" square.



CUSTOM LOCK DIVISION

MAXIMUM SECURITY MORTISE LOCKSET

Series LA318GJ LA318GS

LocDown™
by MARKSUSA®

PERFORMANCE SPECIFICATIONS:

- LIFE TEST:** 1,500,000 cycles, minimum
- STRENGTH TEST:** 530 inch lbs. torque on exterior lever. When applied, lockset remains locked. (Torque of over 550 inch lbs. will cause spindle failure. However, lockset remains locked once spindle is replaced, lockset is fully operational.)
- ANSI TEST:** Certified to meet or exceed all operational and security tests of ANSI/BHMA A156.13-2012 for series 1000, Grade 1
- FIRE TEST:** UL listed, 3 hour fire rated.
Meets ADA requirements.
- WARRANTY:** Lifetime mechanical limited warranty
All other functions available with latch, deadlatch and deadbolt combinations



FUNCTION SPECIFICATION: LA318GJ CLASSROOM INTRUDER

Latch by lever either side except when outside lever is locked from inside or outside by key. When locked, exterior key will retract latchbolt. Outside key locks or unlocks exterior lever. Inside key is single acting in one direction and will lock exterior lever only; will not unlock exterior lever. Auxiliary latch deadlocks latch. Inside always free for egress

TRIM: Cast satin stainless steel escutcheon 8-1/2"x2-3/4"x7/16". Recess in escutcheon to accept cylinder with rotating security cylinder ring. Cast screwless satin stainless steel lever handles to within 1/2" from face of door secured to escutcheon plate with hardened steel retainer ring. Lever handle, with spring-loaded torque sensitive 5/16" spindle. Integral torque override preventer recessed into escutcheon plate. Spindle will yield if excessive torque applied, preventing any damage to lock body.

EXTERIOR: Two 1/4" diameter threaded thru posts.

Two 1/4" diameter center posts pass thru lock body, automatically aligning trim.

INTERIOR: Two #10-32 phillips head stainless steel mounting thru bolts. Escutcheon with "LOCK" and directional arrow engraved and black filled near cylinder location. Occupancy indicator recessed into escutcheon plate. Indicator window to display unlocked (green day-glo) and LocDown™ (red day-glo) positions.

CYLINDERS:

LA318GJ

Two 1-1/8", 6-pin solid brass with 2101 cam int., 2105 cam ext., with two keys. Outside cylinder rotates in both directions. Inside cylinder rotates in one direction only. Cams supplied to accommodate Corbin™, Sargent™ and Schlage™ cylinders.

LA318GS

One mortise thumbturn with "straight" cam #2101 and one 1-1/8", 6-pin solid brass with "J" cam W2105 cam with two keys. Outside cylinder rotates in both directions. Inside thumbturn rotates in one direction only. Cams supplied to accommodate Corbin™, Sargent™ and Schlage™ cylinders.

STRIKE: 4-7/8" X 1-1/4" X 3/32" thick, 5/8" curved lip.

Conforms to ANSI spec. 115.1.

DOOR THICKNESS: 1-3/4"


Lock Body: 5 series "GJ" function double cylinder lock. Lock handing completely reversible without opening lock case.

1. Lock Front - Adjustable bevel steel backplate 1 1/4" x 8 x 7/64" thick. Cover plate 1/16" thick, with phillips screws
2. Latch - solid stainless steel w/ antifriction latch lever 3/4" throw
3. Auxiliary Deadlatch - 1/2" throw
4. Case - stamped steel 3/32" thick
5. Hubs - Steel, 9/32" on diamond, 5/16" on square w/ security separator
6. Independent exterior and interior lever support springs



LA318			FINISH GROUPS
MARKS #	FUNCTION	ANSI #	32D
KEYED SINGLE CYLINDER, NO DEADBOLT			
GS	CLASSROOM SECURITY T-TURN		727.58
KEYED DOUBLE CYLINDER, NO DEADBOLT			
GJ	CLASSROOM SECURITY		727.58

For pricing, finishes and availability, consult factory




INTERIOR TRIM

SERIES BE101 & LA118 CUSTOM LOCK DIVISION

MAXIMUM SECURITY MORTISE LOCKSET

SERIES BE101 & LA118			BHMA CERTIFIED	
			FINISH GROUPS	
MARKS #	FUNCTION	ANSI #	32D	3, 10, 10B
KEYED SINGLE CYLINDER, NO DEADBOLT				
D	OFFICE VESTIBULE		630.26	657.73
DW	VESTIBULE			
E	OFFICE	F04		
EW	STOREROOM	F07		
GL	INST. PRIVACY	F26		
J	CLASSROOM	F05		
JM, JR	HOSPITAL (HOLDBACK)	F06	896.33	964.61
EL	ELECTRICALLY LOCKED			
EU	ELECTRICALLY UNLOCKED			
KEYED SINGLE CYLINDER, WITH DEADBOLT				
A	ENTRANCE	F08, F10	642.03	671.07
B	ENTRANCE	F21		
F	DORMITORY	F12		
FS	DORMITORY			
FW	DORMITORY	F13	660.86	689.91
FD	APARTMENT	F20		
H	HOTEL	F15		
LH	SPEC. PRIVACY			
KEYED DOUBLE CYLINDER, NO DEADBOLT				
G	ENTRANCE	F09	669.50	696.19
GC	INTRUDER LATCHBOLT	F32		
GG	CLASSROOM SECURITY			
GR	CLASSROOM SECURITY w/HOLDBACK			
WW	INSTITUTION	F30		
KEYED DOUBLE CYLINDER, WITH DEADBOLT				
AC	ENTRANCE	F35	669.50	696.19
C	STOREROOM	F14		
FC	INTRUDER DEADBOLT	F34		
FA	DORMITORY	F11		
FX	DORMITORY	F33		
KEYLESS				
N	PASSAGE	F01	547.06	573.74
L	BATHROOM	F02	642.03	671.07
LF	PRIVACY	F19		
LJ	PRIVACY	F22	594.15	622.41
EX	EXIT	F31	594.15	622.41
DUMMY TRIM				
DI, DO	DUMMY TRIM INSIDE/OUTSIDE		276.27	290.40
DT	DUMMY TRIM		553.34	622.41
For pricing, finishes and availability, consult factory				

For pricing, finishes and availability, consult factory



Performance Specifications:

Life Test: 1,500,000 cycles minimum.

ANSI Test: Meets or exceeds all operational and security tests of ANSI specifications A156.13-2005 for series 1000, Grade 1.

Fire Test: UL Listed, 3 hour fire rated.

Meets ADA requirements.



Trim Specifications:

"Barrier" Thru-bolted steel lever/plate assemblies with brass machined lever bearings. Screwless forged American levers, 4-1/2" long to meet ADA requirements, fastened to plates with hardened snap rings. Spring loaded 5/16" spindles (no set screws). Dark bronze powder coated finish.

Exterior: Wrought steel lever/plate assembly.

10-1/8" x 4" x 5/64" with 3 concealed welded thru-posts. Center post braces lock body for proper alignment in 1-3/4" thick door. Plate covers cylinder with only the keyway exposed.

Optional Exterior: Plate prepared for IC core cylinder.

Interior: Flat steel lever/plate assembly. 10-3/4" x 3-1/8" x 3/32" thick with 3 each 1/4"-20 mounting bolts. Center bolt passes through lock body to integrate trim with lock.

Cylinder: 1-1/8" long, 6 pin, solid brass with spacing collar concealed under exterior "Barrier" plate; 2 keys.

Strike: 4-7/8" x 1-1/4" x 3/32" thick, 5/8" curved lip. Conforms to ANSI spec., A115.1.

Door Thickness: 1-3/4" standard. Extended range available.

Lock Specifications: 5 Series (2-3/4" Backset)

1. Lock Front: Adjustable bevel steel backplate 1-1/4" x 8" x 7/64" thick. Cover plate 1/16" thick.

2. Deadbolt: Stainless steel w/hardened roll pins, 1" throw.

3. Latch: Solid stainless steel with anti-friction latch lever, 3/4" throw (reversible).

4. Auxiliary deadlatch: 1/2" throw (reversible) - (not shown).

5. Hubs: Steel, 9/32" on diamond, 5/16" on square w/security separator.


6. Independent exterior and interior lever support springs.

7. Hub Follower: (to lock hub) steel 1/8" thick.

8. Hub Stop: (to limit lever travel) steel 1/8" thick.

9. Case: Stamped steel 3/32" thick, zinc dichromate finish.

10. Spindles: Independent spring-loaded spindles, 5/16" square.



CUSTOM LOCK DIVISION

MAXIMUM SECURITY MORTISE LOCKSET

LocDown™
by MARKSUSA®

PERFORMANCE SPECIFICATIONS:

- LIFE TEST:** 1,500,000 cycles, minimum
- STRENGTH TEST:** 530 inch lbs. torque on exterior lever. When applied, lockset remains locked. (Torque of over 550 inch lbs. will cause spindle failure. However, lockset remains locked once spindle is replaced, lockset is fully operational.)
- ANSI TEST:** Certified to meet or exceed all operational and security tests of ANSI/BHMA A156.13-2012 for series 1000, Grade 1
- FIRE TEST:** UL listed, 3 hour fire rated.
Meets ADA requirements.
- WARRANTY:** Lifetime mechanical limited warranty
All other functions available with latch, deadlatch and deadbolt combinations



Specially Locksets

Contact Customer Service for Prices

Model #: LA318VJM/32D




Lock Function: Deadlock

Deadlocking latch by key outside. inside lever retracts deadlocking latch. Latch is in hold-back by turning inside lever and inserting key in outside mortise cylinder. Indicator on inside escutcheon shows green when in latch hold-back. Turning key in inside mortise cylinder in the direction of the arrow will the release the latch, change the indicator to red and secure the main door from the outside.

Price \$2195.00

Model #: LA118VCR/32D




Lock Function: Deadlock

Latch retracted by key outside and lever inside accept when locked by key either side. Inside lever retracts and holds latch in retracted position by rotating key in inside or o/s cylinder. Inside lever can be locked (rigid) or unlocked. Deadlocking latch.

Price \$2295.00

Model #: LA118CTF/32D




Lock Function: Deadlock

Deadbolt by key either side. Inside knob/lever retracts deadbolt for emergency egress, outside knob/lever always rigid

Price \$682.50

GRADE 1 195BH LifeSaver™ D-Lig SLIDE CYLINDRICAL LOCKSETS

BHMA CERTIFIED		ANSI-A156.2 • Grade 1 3 Hour Fire Rating		195BH SERIES	
195SS Series Leversets Shown Below				Standard Features	
				• Rating: ANSI A156.2 Grade 1, UL Listed 3Hr Fire Rating • 5- Point Ligature Resistant slide Trim • Backset: 2 3/4" Standard, 2 3/8", 3 3/4" and 5" available • Latch: #1834, stainless Steel Nose • Ergonomic solid cast Stainless Steel Slide, Slides down freely in the locked or unlocked position • Escutcheon Plate solid cast Stainless Steel thru bolted for strength and easy installation • Designed to meet BHMA 156.34 Anti Ligature Trim Standard • Tamper Resistant mounting screws • Strike: #1135, 4 7/8" ASA curved lip Strike • Door Thickness: 1 3/4" • Cylinder: Marks C Keyway, 6 pin w/2 keys - Available in IC and All OEM cylinder preps • Marks Hi-Security Cylinder available • Marks Stainless Steel Retractor - Long life 3X the BHMA Grade 1 cycle Standard • Antimicrobial Finish available - Code AM • Marks Lifetime Mechanical Warranty • Available in Most BHMA ANSI Functions	

SERIES 195BH					
MARKS #		DESCRIPTION	ANSI #	FINISH	PRICE
COMM. CYL.	ACCEPTS IC CORE CYL.*				
N	—	PASSAGE	F75	32D	943.85
L	—	PRIVACY	F76		943.85
B	RB	ENTRY	F82A		1066.96
S	RS	CLASSROOM	F84		1066.96
F	RF	STOREROOM	F86		1066.96
DW	RDW	INSTITUTION	F87		1190.07
DB	RDB	CLASSROOM INTRUDER	F110		1149.03
DO	—	DUMMY TRIM OUTSIDE	—		451.41
DT	—	FULL DUMMY TRIM	—		902.81
NB	—	COMM. PASSAGE	F111		919.23
FB	RFB	COMM. STOREROOM	F112		976.68
SB	RSB	COMM. CLASSROOM	F113		976.68
FEL	RFEL	ELECTRICALLY LOCKED			1190.07
FEU	RFEU	ELECTRICALLY UNLOCKED			1190.07
PACKED 6 PER CASE					

OPTIONS	CODE	PRICE	OPTIONS	CODE	PRICE
For 2" doors	D1	NC	Sargent conventional cylinder	F8	15.00
For 2-1/4" doors, Consult Factory	D2	48.00	Corbin Russwin conventional cylinder	F9	15.00
Over 2-1/4" - 4" thickness	D9	409.00	Corbin Russwin 6 pin IC core	F12	22.00
2-3/8" backset, 1" x 2-1/4" face	E6	NC	Yale/Accentra 6 pin IC core	F14	15.00
5" backset, 9/16" throw, Gr. 1	E9	30.00	Sargent IC core	F20	15.00
3-3/4" backset, 9/16" throw, Gr. 1	E10	30.00	Medeco IC core large format	F21	15.00
Less cylinder	G3	-10.00	Schlage Large Format IC Core	F19	15.00
2-3/4" "T" strike	S3	NC	7-Pin Yale/Accentra IC Core	F15	15.00

TAILPIECES FOR 195BH			
P/N	FITS	OPTION CODE	PRICE
MH119	YALE/ACCENTRA / MEDECO IC CORE	F14, F15, F21	7.98
MH140	CONVENTIONAL (K.I.L.) CYL	N/A	7.98
MH144	SIFC	R, F20	7.98
MH146	CORBIN RUSSWIN IC	F12, F13	7.98
MH1903S-C	SCHLAGE IC / CORBIN K.I.L.	F19, F9	7.98

★ **Standard & HI-SECURITY™ IC Core Models:** Interchangeable Core models for 6 or 7 pin cores (not included). **Accepts:** Marks, Marks HI-SECURITY™, Medeco®, KeyMark™, Falcon, Schlage® small format & Best®. **IC Core Tailpieces ARE Included.**



HI-SECURITY
OPTION

Antimicrobial Finish Available
Option Code: AM

GRADE 1 SERIES 5BH29 D-LIG SLIDE MORTISE LOCKSET

INSTITUTIONAL LifeSaver™ MORTISE LOCKSETS

		SERIES 5				FINISH 32D	
MARKS #		FUNCTION		ANSI #		5BH	
KEYED SINGLE CYLINDER, NO DEADBOLT							
D	OFFICE VEST.			1395.25			
DW	VESTIBULE						
E	OFFICE		F04				
EW	STOREROOM		F07				
J	CLASSROOM		F05				
GL	INSTIT. PRIVACY		F26	1666.10			
EL	ELECTRICALLY LOCKED						
EU	ELECTRICALLY UNLOCKED						
KEYED SINGLE CYLINDER, WITH DEADBOLT							
A	ENTRANCE		F08, F10	1406.75			
B	ENTRANCE		F21				
F	DORMITORY		F12				
FS	DORMITORY						
FW	DORMITORY		F13				
KEYED DOUBLE CYLINDER, NO DEADBOLT							
G	APARTMENT		F09	1433.01			
GC	INTRUDER LATCHBOLT		F32				
GG	CLASSROOM SECURITY						
WW	INSTITUTIONAL		F30				
KEYED DOUBLE CYLINDER, WITH DEADBOLT							
AC	ENTRANCE		F35	1433.01			
C	STOREROOM		F14				
CT							
FA	DORMITORY		F11				
FX	DORMITORY		F33				
KEYLESS							
N	PASSAGE		F01	1315.65			
L	BATHROOM		F02	1406.75			
LF	PRIVACY		F19				
LJ	PRIVACY		F22	1361.60			
EX	EXIT		F31				
DUMMY TRIM							
DI	DUMMY TRIM INSIDE			410.37			
DO	DUMMY TRIM OUTSIDE						
DT	FULLY DUMMY			919.23			



★ Standard & HI-SECURITY™ IC Core Models:

Interchangeable Core models for 6 or 7 pin cores (not included).

Accepts: Marks, Marks HI-SECURITY™, Medeco®, KeyMark™, Falcon, Schlage® small format & Best®. **IC Core Tailpieces ARE Included.**




**Antimicrobial
Finish Available
Option Code: AM**



Performance Specifications:


- **Rating:** ANSI A156.13 Grade 1, UL Listed 3Hr Fire Rating
- 5- Point Ligature Resistant slide Trim
- **Backset:** 2 3/4" Standard, 2 1/2" Consult Factory
- **Latch:** #1834, stainless Steel Nose
- **Ergonomic solid cast Stainless Steel Slide,** Slides down freely in the locked or unlocked position
- **Escutcheon Plate solid cast Stainless Steel** thru bolted for strength and easy installation
- Designed to meet **BHMA 156.34 Anti Ligature Trim Standard**
- Tamper Resistant mounting screws
- Ligature Resistant ADA Thumbturn available where applicable
- **Strike:** #1135, 4 7/8" ASA curved lip Strike
- **Door Thickness:** 1 3/4"
- **Cylinder:** Marks C Keyway, 6 pin w/2 keys
- Available in IC
- Marks Hi-Security Cylinder available
- **Marks Stainless Steel Retractor** - Long life 3X the BHMA Grade 1 cycle Standard
- Antimicrobial Finish available - Code AM
- **Marks Lifetime Mechanical Warranty**
- Available in Most BHMA ANSI Functions



How To Order

5BH29	J	/	32D	-	G3
1. Lockset Series	2. Marks Function	Slash	3. Finish	Dash	4. Options

GRADE 1 195SS LifeSaver™ CYLINDRICAL LEVERSETS

BHMA CERTIFIED		ANSI-A156.2 • Grade 1 3 Hour Fire Rating		195SS SERIES
195SS Series Leversets Shown Below				Standard Features
				• ANSI-A156.2 Grade 1, UL listed 3 Hr. Fire Rating • Backset: 2-3/4" Standard, 2-3/8", 3-3/4", 5" Available • Latch #1834, stainless steel nose • Levers: Solid cast stainless steel. Levers Rotate up & down freely in locked or unlocked position • Levers recessed into solid stainless steel roses eliminating any open gap • Roses: Thru-bolted, spring loaded, #10 thru-bolts • Strike: #1135, 4-7/8" ASA curved lip strike • Door thickness: 1-3/4" +/- 1/16" • Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys • Stainless steel retractor

SERIES 1SS19					
MARKS #		DESCRIPTION	ANSI #	FINISH	PRICE
COMM. CYL.	ACCEPTS IC CORE CYL.*				
N	—	PASSAGE	F75	32D	687.76
L	—	PRIVACY	F76		705.83
LK	—	PRIVACY	F76 MOD.		728.00
P	—	PATIO	F77		701.73
DC	RDC	COMMUNICATING	F80		755.08
B	RB	ENTRY	F82A		719.78
AQ	—	EXIT	F83		709.94
S	RS	CLASSROOM	F84		719.78
F	RF	STOREROOM	F86		719.78
DW	RDW	INSTITUTION	F87		755.08
DA	RDA	VESTIBULE	F88		755.08
FQ	—	EXIT	F89		709.94
T	—	CORRIDOR	F90		728.00
TK	—	HOSPITAL/PRIV.	F90 MOD.		701.73
GB	RGB	STORE DOOR	F91		728.00
BS	RBS	SVC. STATION LOCK	F92		763.29
DO	—	DUMMY TRIM OUTSIDE	—		567.95
DT	—	FULL DUMMY TRIM	—		652.49
NB	—	COMM. PASSAGE	F111		670.54
FB	RFB	COMM. STOREROOM	F112		714.05
SB	RSB	COMM. CLASSROOM	F113		714.05
FEL	RFEL	ELECTRICALLY LOCKED			861.78
FEU	RFEU	ELECTRICALLY UNLOCKED			861.78
PACKED 6 PER CASE					

OPTIONS	CODE	PRICE
For 2" doors Consult Factory	D1	NC
For 2-1/4" doors, Consult Factory	D2	48.00
Over 2-1/4" - 4" thickness	D9	409.00
2-3/8" backset, 1" x 2-1/4" face	E6	NC
5" backset, 9/16" throw, Gr. 1 Consult Factory	E9	30.00
3-3/4" backset, 9/16" throw, Gr. 1	E10	30.00
Less cylinder	G3	-10.00
2-3/4" "T" strike	S3	9.00
Spacer for K1904GB/SS1	195SS	263.00

OPTIONS	CODE	PRICE
Sargent conventional cylinder	F8	15.00
Corbin Russwin conventional cylinder	F9	15.00
Corbin Russwin 6 pin IC core	F12	22.00
Yale/Accentra 6 pin IC core	F14	15.00
Sargent IC core	F20	15.00
Medeco IC core large format	F21	15.00

How To Order					
195SS	F	/	32D	-	G3
1. Lockset Series	2. Marks Function	Slash	3. Finish	Dash	4. Options

★ **Standard & HI-SECURITY™ IC Core Models:** Interchangeable Core models for 6 or 7 pin cores (not included). **Accepts:** Marks, Marks HI-SECURITY™, Medeco®, KeyMark™, Falcon, Schlage® small format & Best®. **IC Core Tailpieces ARE Included.**



HI-SECURITY
OPTION

Antimicrobial Finish Available
Option Code: AM

SERIES 5SS19 LEVER


INSTITUTIONAL LifeSaver™ MORTISE LOCKSETS

		SERIES 5				FINISH 32D	
MARKS #		FUNCTION		ANSI #		SS19 Lever	
KEYED SINGLE CYLINDER, NO DEADBOLT							
D	OFFICE VEST.			901.17			
DW	VESTIBULE						
E	OFFICE		F04				
EW	STOREROOM		F07				
J	CLASSROOM		F05				
GL	INSTIT. PRIVACY		F26	1163.81			
EL	ELECTRICALLY LOCKED						
EU	ELECTRICALLY UNLOCKED						
KEYED SINGLE CYLINDER, WITH DEADBOLT							
A	ENTRANCE		F08, F10	1045.88			
B	ENTRANCE		F21				
F	DORMITORY		F12				
FS	DORMITORY						
FW	DORMITORY		F13				
KEYED DOUBLE CYLINDER, NO DEADBOLT							
G	APARTMENT		F09	925.79			
GC	INTRUDER LATCHBOLT		F32				
GG	CLASSROOM SECURITY						
WW	INSTITUTIONAL		F30				
KEYED DOUBLE CYLINDER, WITH DEADBOLT							
AC	ENTRANCE		F35	925.79			
C	STOREROOM		F14				
FA	DORMITORY		F11				
FX	DORMITORY		F33				
KEYLESS							
N	PASSAGE		F01	868.34			
L	BATHROOM		F02				
LF	PRIVACY		F19	1032.54			
LJ	PRIVACY		F22				
EX	EXIT		F31				
1057.11							
DUMMY TRIM							
DI	DUMMY TRIM INSIDE			479.31			
DO	DUMMY TRIM OUTSIDE						
DT	FULLY DUMMY			956.16			

★ Standard & HI-SECURITY™ IC Core Models:

Interchangeable Core models for 6 or 7 pin cores (not included).

Accepts: Marks, Marks HI-SECURITY™, Medeco®, KeyMark™, Falcon, Schlage® small format & Best®. **IC Core Tailpieces ARE Included.**



Performance Specifications:

Life Test: 1,500,000 cycles minimum.

ANSI Test: Meets or exceeds all operational and security tests of ANSI specifications A156.13-2005 for series 5000, Grade 1.

Trim Specifications:

Exterior & Interior Trim:

- Solid stainless steel interior and exterior tapered levers recessed into thru-bolted roses.
- Safety lever for handicapped access on clutch operated Mortise lock.
- Ergonomically designed grooved turn knob for deadbolt functions.

Cylinder: Solid stainless steel cylinders with solid stainless steel security collars; Optional HI-SECURITY™ cylinders available

Strike: 4-7/8" curved lip stainless steel w/tamperproof screws

Door Thickness: 1-3/4" standard; Extended range available

Door Prep: ANSI A115.1 lock face cutout, with 2-1/8" through hole for knob/rose assembly

Lock Specifications: 5 Series (2-3/4" Backset)

Lock Front: Adjustable bevel steel backplate 1-1/4" x 8" x 7/64" thick, Cover plate 1/16" thick with tamper proof screws

Latch: Solid stainless steel with antifriction latch lever, 3/4" throw (reversible)

Levers: Solid cast stainless steel. Levers Rotate up & down freely in locked or unlocked position


Aux. Deadlatch: 1/2" throw, (reversible)

Case: Stamped steel 3/32" thick, zinc dichromate finish

Hubs: Steel, 9/32" on diamond, 5/16" on square w/security separator

Hub Lock Arm: (to lock hub) Steel 1/8" thick


Spindles: Independent spring-loaded spindles



**Antimicrobial
Finish Available
Option Code: AM**

How To Order

5SS19 Lever	J	/	32D	-	G3
1. Lockset Series	2. Marks Function	Slash	3. Finish	Dash	4. Options





SERIES 31SS55 INSTITUTIONAL LifeSaver™ LOCKSETS

INSTITUTIONAL LIFE SAFETY MORTISE DEADLOCK

SERIES 31SS55			BHMA CERTIFIED
			FINISH GROUPS
MARKS #	FUNCTION	ANSI #	32D
KEYED SINGLE CYLINDER, WITH DEADBOLT			
K	CYLINDER x KNOB	E06071	377.03
S	CLASSROOM	E06091	403.16



31SS55K: Function E06071;

Deadbolt by outside key.
Interior safety knob will retract
but not project deadbolt.



31SS55S: Function E06091;

Deadbolt by outside key.
Turnpiece will retract
but not project deadbolt.




Performance Specifications:

Life Test: 1,500,000 cycles minimum.

ANSI Test: Meets or exceeds all operational and security tests of ANSI/BHMA Certified A156.5-2001 for series 31, Grade 1.

Fire Test: UL Listed, 3 Hour fire rated.



Trim Specifications:

Interior Trim: Solid stainless steel interior trim including finger indented safety knobs which recess into solid brass through-bolted roses.

Series 31 Deadlock Specifications:

Backset: 2-3/4"

Bolt throw: 1" stainless steel w/hardened roll pins

Case: Stamped Steel

Front: 1-1/16" x 4-5/8" adjustable bevel

Cylinder: Solid brass cylinder, 6-pin, "C" keyway, 2 keys.
Optional HI-SECURITY™ cylinders available.

Strike: #4035 Included

Antimicrobial Finish
Option Code: AM

★ Standard & HI-SECURITY™ IC Core Models:

Interchangeable Core models for 6 or 7 pin cores (not included).

Accepts: Marks, Marks HI-SECURITY™, Medeco®, KeyMark™, Falcon, Schlage® small format & Best®. **IC Core Tailpieces ARE Included.**



SERIES 180PD & 5PD HOSPITAL LifeSaver™ LOCKSETS


CYLINDRICAL & MORTISE PUSH/PULL PADDLESETS


Hospital Push/Pull Standard Features					
• 1-3/4" door thickness, self adjusting for thicker doors • Variable mounting positions		• Non-Handed • Easily reversible configuration for push or pull styles			
180PD Cylindrical Standard Features		SERIES 180PD • ANSI-A156.2 • Grade 1			
• 2-3/4" backset std., 2-3/8", 3-3/4" & 5" optional • 2-3/4" "T" strike; 4-7/8" ASA strike optional • Government standard #161 door prep			ENGRAVING AVAILABLE		
MARKS #	FUNCTION			ANSI #	FINISH: 32D Standard Consult Factory for Additional Finishes
N	PASSAGE			F75	232.57
PUSH/PULLS ARE PACKED 6 PER CASE					

5PD, 55PD Mortise Standard Features			SERIES 5PD, 55PD • ANSI-A156.13 • Grade 1	
• 5 Series Backset: 2-3/4"; 55 Series Backset: 2-1/2"			ENGRAVING AVAILABLE	
• Strike: #9035, 4-7/8" ASA curved lip strike				
MARKS #	FUNCTION	ANSI #	FINISH: 32D Standard Consult Factory for Additional Finishes	
KEYED SINGLE CYLINDER, NO DEADBOLT				
D	OFFICE VEST.		621.30	
DW	VESTIBULE			
E	OFFICE	F04		
EW	STOREROOM	F07		
J	CLASSROOM	F05		
JM, JR	HOSPITAL	F06		
GL	INSTITUTIONAL PRIVACY	F26	899.53	
EL	ELECTRICALLY LOCKED			
EU	ELECTRICALLY UNLOCKED			
KEYED SINGLE CYLINDER, WITH DEADBOLT				
A	ENTRANCE	F08, F10	634.43	
B	ENTRANCE	F21		
F	DORMITORY	F12		
FS	DORMITORY			
FW	DORMITORY	F13		
FD	APARTMENT	F20	653.31	
H	HOTEL	F15		
LH	SPECIAL PRIVACY			
KEYED DOUBLE CYLINDER, NO DEADBOLT				
G	APARTMENT	F09	661.51	
GC	INTRUDER LATCHBOLT	F32		
GG	CLASSROOM SECURITY			
GR	CLASSROOM SECURITY w/ HOLDBACK			
WW	INSTITUTIONAL	F30		
KEYED DOUBLE CYLINDER, WITH DEADBOLT				
AC	ENTRANCE	F35	661.51	
C	STOREROOM	F14		
FC	INTRUDER DEADBOLT	F34		
FA	DORMITORY	F11		
FX	DORMITORY	F33		
KEYLESS				
N	PASSAGE	F01	535.12	
L	BATHROOM	F02	634.43	
LF	PRIVACY	F19		
LJ	PRIVACY	F22	581.91	
EX	EXIT	F31		
PUSH/PULLS ARE PACKED 6 PER CASE				


How To Order					
5PD or 180PD	F	/	32D	-	G3
1. Lockset Series	2. Marks Function	Slash	3. Finish	Dash	4. Options


180PD Cylindrical Paddleset



5PD Mortise Paddleset







Hospital Push/Pull Paddlesets

MORTISE LOCK CYLINDERS


Cylinders



Mortise

Concealed

IC Core Cylinder Housings



R662

Small Format
IC Core
6 or 7 Pin

RA3182
Schlage® format
IC Core

R2181

R2183

R4182

*Standard & HI-SECURITY™ IC Core Models:

Interchangeable Core models for 6 or 7 pin cores (not included).

Accepts: Marks, Marks HI-SECURITY™, Medeco®, KeyMark™, Falcon, Schlage® small format & Best®. **IC Core Tailpieces ARE Included.**



PART #	DESCRIPTION	PINS	LENGTH	FINISH GROUPS	
				3, 26D	5, 10, 10B, 15, 19, 26, 32D
2181	Mortise	6	2-7/8"	300.57	—
2182	Mortise	6	1-1/8"	75.77	84.44
2183	Mortise	6	1-1/4"	75.77	84.44
2193	Concealed	5	15/16"	101.05	—
2194	Concealed	6	1-1/8"	106.59	—
2196	Mortise	6	2-3/8"	419.44	—
2197	Mortise	6	1-3/4"	162.00	170.26
2198	Mortise	6	1-1/2"	130.11	134.28
662	Rim	6	—	76.13	84.44
R2181	Mortise SFIC Housing	6	1"	76.13	84.44
R2182	Mortise SFIC Housing	6	1-1/4"	69.21	73.37
R2183	Mortise SFIC Housing	6 or 7	1-3/8"	69.21	73.37
R2184	Mortise SFIC Cylinder Housing	6 or 7	1-3/4"	160.58	160.58
R3182	Schlage® type IC Core, 1 Bitted	6	—	160.58	—
R4182	Schlage® type IC Core Housing	6	1-1/2"	185.49	191.03
R662	Rim SFIC Housing	6 or 7	1-3/8"	80.29	84.44
R1182	6 Pin SFIC, Uncombined			60.90	—
R1183	7 Pin SFIC, Uncombined			60.90	—
RA1182	6 Pin SFIC, Combined			89.98	92.75
RA1183	7 Pin SFIC, Combined			89.98	92.75
RA3182	Schlage® type IC Core, Combined	6	—	191.03	—
RC1182	6 Pin SFIC, Construction Core			63.67	—
RC1187	Plastic SFIC Turn Knob			12.46	—
RC3182	Schlage® type Construction Core			160.58	—
RM1182	Marketing SFIC, Red			66.45	—

Cylinder Cams



2101



2102



2104



2105



2106



2107-CL

PART #	DESCRIPTION	USE WITH OEM MORTISE CYLINDER	CODE	PRICE	PART #	DESCRIPTION	USE WITH OEM MORTISE CYLINDER	CODE	PRICE
2101	STRAIGHT CAM	MARKS	1	6.98	2104	ADAMS-RITE CAM	MARKS	4	6.98
2101-A		ARROW/SARGENT	A1	6.98	2105	"J" FUNCTION CAM	MARKS	5	6.98
2101-C		CORBIN RUSSWIN	C1	6.98	2105-A		ARROW/SARGENT	A5	6.98
2101-S		SCHLAGE NON-MODULAR	S1	6.98	2105-C		CORBIN RUSSWIN	C5	6.98
2102	CLOVERLEAF CAM	MARKS	2	6.98	2105-S		SCHLAGE NON-MODULAR	S5	6.98
2102-A		ARROW/SARGENT	A2	6.98	2107-CL	"J-CL" FUNCTION CAM	MARKS	7	6.98
2102-C		CORBIN RUSSWIN	C2	6.98	2106	"G" CAM Exterior only	MARKS	6	6.98
2102-S		SCHLAGE NON-MODULAR	S2	6.98	2106-A		ARROW/SARGENT	A6	6.98
					2106-C		CORBIN RUSSWIN	C6	6.98
					2106-S		SCHLAGE NON-MODULAR	S6	6.98

How To Order Example for Mortise Lock Cylinders

2182	/	32D	—	1C
1. Cylinder	Slash	2. Finish	Dash	3. Options
See List Of ___ Cylinders ___ Available		FINISH (Pg. 8) ___ 3 ___ 5 ___ 10 ___ 10B ___ 15 ___ 26 ___ 26D ___ 32D	___ Special ___	Specify ___ Keying ___ Door Thickness Cam and keying information must be included in the option section.


KEYS & KEYING

Keys

Can Stamp A Maximum Of 6 Characters On Key.



MARKS Keys



IC Core Keys


STANDARD KEYWAYS	PIN LENGTH ACCEPTS	SHOULDER INCREMENTS	PIN TO PIN TO 1st PIN	PLUG DISTANCE	DIAMETER
MARKS "A"	Arrow Kwikset Segal 9	.015"	.264"	.156"	.504"
MARKS "C"	Schlage "C"	.015"	.231"	.156"	.504"

PART #	DESCRIPTION	PRICE	
		EACH	CUT
2164A	MARKS "A" 5 PIN BRASS	7.18	7.54
2164C	MARKS "C" 5 PIN BRASS, NICKEL PLATED	7.18	7.54
2184A	MARKS "A" 6 PIN NICKEL SILVER	8.37	8.79
2184C	MARKS "C" 6 PIN NICKEL SILVER	8.37	8.79
R1164	IC CORE 6 OR 7 PIN (SMALL FORMAT)	8.37	8.79
R3164	SCHLAGE® IC CORE CONTROL KEY	8.37	8.79

Construction Master Keying:


The construction master key (CMK) is to be used temporarily while the building is under construction. When construction is completed, the end user defeats the CMK's operation by turning the change key in each cylinder, rather than replace or re-keying the cylinder.

Marks USA uses a program which is called the "lost ball" program. When construction key system is set up, three small ball bearings (construction balls) are placed between the bottom pin and master pin, normally in the last chamber as a "temporary master pin". The construction key is usually the same cut as the top master key with the exception of the sixth cut which is two increments higher. The construction master key will work in any cylinder until cylinder is "defeated" by making one full rotation in the cylinder with the change key. The cylinder plug requires a small diameter "pocket" drilled on one side of one pin chamber so when rotating the cylinder with the change key the pocket will capture the construction balls. The construction pocket in the plug is smaller than a pin chamber. This prevents any top pins or master pins from entering as the plug rotates. Once the cylinder is defeated, there is no way for the cylinder to be construction keyed again without disassembling it.



BEST® A thru M keyway. Please specify.

PART #	DESCRIPTION	PRICE	
		REGULAR	IC CORE
KA	KEYED ALIKE	NC	NC
KD	KEYED DIFFERENT	NC	NC
MK	MASTER KEYED	15.00	17.00
CMK	CONSTRUCTION MASTER KEYED (Includes GMK or MK)	22.00	—
GMK	GRAND MASTER KEYED	15.00	17.00
GGMK	GREAT GRAND MASTER KEYED	15.00	17.00
GGGMK	GREAT GREAT GRAND MASTER KEYED	15.00	—
STAMPING		PRICE	
LETTERS/NUMBERS ON KEY - PER KEY		6.00	
US PROPERTY - "DO NOT DUPLICATE" - PER KEY		6.00	
VISUAL KEY CONTROL (VKC)		12.00	
CONCEAL KEY CONTROL		12.00	
EXTRA CUT KEYS WITH LOCKSET		SEE KEYS ABOVE	
KEY BITTING CODE LIST		N/C	



★ Standard & HI-SECURITY™ IC Core Models:

Interchangeable Core models for 6 or 7 pin cores (not included).

Accepts: Marks, Marks HI-SECURITY™, Medeco®, KeyMark™, Falcon, Schlage® small format & Best®. IC Core Tailpieces ARE Included.



HI-SECURITY™ CYLINDERS: NON-UL




HI-SECURITY™ MORTISE CYLINDERS				
	NON-UL "0" Bitted x 2 Keys; "0" Bitted "NO KEYS" - Deduct \$7		FINISH GROUPS	
	PART #	DESCRIPTION	3, 26D	4, 5, 10, 10B, 15, 26, 32D
	BXXX-D001A0N2	1-1/8" Mortise Cylinder	102.09	110.74
	CXXX-D001A0N2	1-1/4" Mortise Cylinder	110.74	120.43
	DXXX-D001A0N2	1-3/8" Mortise Cylinder	128.74	135.66
	NON-UL KD x 2 Keys			
	BXXX-D001A1N2	1-1/8" Mortise Cylinder	112.13	123.20
	CXXX-D001A1N2	1-1/4" Mortise Cylinder	123.20	128.74
	DXXX-D001A1N2	1-3/8" Mortise Cylinder	139.81	146.73
	HI-SECURITY™ CYLINDERS ARE PACKED 24 PER CASE			

HI-SECURITY™ MORTISE/RIM COMBO CYLINDERS				
	NON-UL "0" Bitted x 2 Keys; "0" Bitted "NO KEYS" - Deduct \$7		FINISH GROUPS	
	PART #	DESCRIPTION	3, 26D	4, 5, 10, 10B, 15, 26, 32D
	EXXX-D001A0N2	1" Combo Cylinder	92.75	99.67
	FXXX-D001A0N2	1-1/8" Combo Cylinder	110.74	120.42
	NON-UL KD x 2 Keys			
	EXXX-D001A1N2	1" Combo Cylinder	103.82	110.74
	FXXX-D001A1N2	1-1/8" Combo Cylinder	123.20	128.74
	HI-SECURITY™ CYLINDERS ARE PACKED 24 PER CASE			

HI-SECURITY™ KIK CYLINDERS			
	NON-UL "0" Bitted x 2 Keys; "0" Bitted "NO KEYS" - Deduct \$6		FINISH GROUPS
	PART #	DESCRIPTION	26D
	G26D-D001X0N2	Key-In-Knob Cylinder	84.44
	NON-UL KD x 2 Keys		
	G26D-D001X1N2	Key-In-Knob Cylinder	92.75
	HI-SECURITY™ CYLINDERS ARE PACKED 24 PER CASE		

HI-SECURITY™ MARKS SFIC CORES			
	NON-UL "0" Bitted x 2 Keys x 1 Control Key; "0" Bitted "NO KEYS" - Deduct \$6		FINISH GROUPS
	PART #	DESCRIPTION	26D
	H26D-D001X0N2	6 Pin SFIC	92.75
	J26D-D001X0N2	7 Pin SFIC	96.90
	NON-UL KD x 2 Keys x 1 Control Key		
	H26D-D001X1N2	6 Pin SFIC	107.97
	J26D-D001X1N2	7 Pin SFIC	112.13
	HI-SECURITY™ CYLINDERS ARE PACKED 24 PER CASE		

HI-SECURITY™ Schlage® LARGE FORMAT IC CORES			
	NON-UL "0" Bitted x 2 Keys x 1 Control Key; "0" Bitted "NO KEYS" - Deduct \$6		FINISH GROUPS
	PART #	DESCRIPTION	26D
	K26D-D001X0N2	6 Pin Schlage® IC Core	117.67
	NON-UL KD x 2 Keys x 1 Control Key		
	K26D-D001X1N2	6 Pin Schlage® IC Core	131.50
	HI-SECURITY™ CYLINDERS ARE PACKED 24 PER CASE		

HI-SECURITY™ Medeco® LARGE FORMAT IC CORES			
	NON-UL "0" Bitted x 2 Keys x 1 Control Key; "0" Bitted "NO KEYS" - Deduct \$6		FINISH GROUPS
	PART #	DESCRIPTION	26D
	P26D-D001X0N2	6 Pin Medeco® IC Core	143.97
	NON-UL KD x 2 Keys x 1 Control Key		
	P26D-D001X1N2	6 Pin Medeco® IC Core	159.19
	HI-SECURITY™ CYLINDERS ARE PACKED 24 PER CASE		

HI-SECURITY™ SPECIAL APPLICATION CYLINDERS			
	KA Pair w/ 2 Keys, NON-UL, Straight Cam		FINISH GROUPS
	PART #	DESCRIPTION	3, 26D
	2122XXXHSM	15/16" Mortise Cylinders	143.99
	HI-SECURITY™ SPECIAL APPLICATION CYLINDERS ARE PACKED 24 PER CASE		

HI-SECURITY™ CYLINDERS

Security-Mate™ & SPECIAL APPLICATION CYLINDERS



Security-Mate™ MORTISE CYLINDERS				
	"0" Bitted "NO KEYS"		FINISH GROUPS	
	PART #	DESCRIPTION	3, 26D	4, 5, 10, 10B, 15, 26, 32D
	BXXX-DXXXA0N0	1-1/8" Mortise Cylinder	80.29	110.74
	CXXX-DXXXA0N0	1-1/4" Mortise Cylinder	87.21	120.43
	DXXX-DXXXA0N0	1-3/8" Mortise Cylinder	102.44	135.66
Security-Mate™ CYLINDERS ARE PACKED 24 PER CASE				

Security-Mate™ MORTISE/RIM COMBO CYLINDERS				
	"0" Bitted "NO KEYS"		FINISH GROUPS	
	PART #	DESCRIPTION	3, 26D	4, 5, 10, 10B, 15, 26, 32D
	EXXX-DXXXA0N0	1" Combo Cylinder	66.96	76.13
	FXXX-DXXXA0N0	1-1/8" Combo Cylinder	87.21	92.75
	Security-Mate™ CYLINDERS ARE PACKED 24 PER CASE			

Security-Mate™ KIK CYLINDERS			
	"0" Bitted "NO KEYS"		FINISH GROUPS
	PART #	DESCRIPTION	26D
	G26D-DXXXX0N0	Key-In-Knob Cylinder	62.29
	Security-Mate™ CYLINDERS ARE PACKED 24 PER CASE		

Security-Mate™ MARKS IC CORES			
	"0" Bitted "NO KEYS"		FINISH GROUPS
	PART #	DESCRIPTION	26D
	H26D-DXXXX0N0	6 Pin IC Core	69.21
	J26D-DXXXX0N0	7 Pin IC Core	76.13
	Security-Mate™ CYLINDERS ARE PACKED 24 PER CASE		

Security-Mate® Schlage™ LARGE FORMAT IC CORES			
	"0" Bitted "NO KEYS"		FINISH GROUPS
	PART #	DESCRIPTION	26D
	K26D-DXXXX0N0	6 Pin Schlage® IC Core	95.51
	Security-Mate™ CYLINDERS ARE PACKED 24 PER CASE		

Security-Mate® Medeco™ LARGE FORMAT IC CORES			
	"0" Bitted "NO KEYS"		FINISH GROUPS
	PART #	DESCRIPTION	26D
	P26D-DXXXX0N0	6 Pin Medeco® IC Core	123.20
	Security-Mate™ CYLINDERS ARE PACKED 24 PER CASE		

HI-SECURITY™
Cylinders

HI-SECURITY™ CYLINDERS

HOW TO ORDER HI-SECURITY™ CYLINDERS AND KEYS

How To Order Example for HI-SECURITY™ Cylinders								
D	3	—	D	001	A	3	U	2
1. Cylinder Type	2. Finish	Dash	3. Keyway	4. Security Code	5. Cam Tail	6. Keying	7. NON-UL / UL437	8. # of Keys
CYLINDER TYPE ___ B = 1-1/8" Mortise ___ C = 1-1/4" Mortise ___ D = 1-3/8" Mortise ___ L = 1-1/2" Mortise ___ M = 1-3/4" Mortise ___ E = 1" Combo ___ F = 1-1/8" Combo ___ G = KIK Cylinder ___ H = IC Core Marks 6 Pin ___ J = IC Core Marks 7 Pin ___ K = IC Core Schlage® Large Format ___ P = IC Core Medeco® Large Format	FINISH ___ 3 ___ 4 ___ 5 ___ 10 ___ 10B ___ 15 ___ 26 ___ 26D ___ 32 ___ 32D		KEYWAY ___ D = HS	SECURITY CODE ___ 001 = MARKS	CAM TAIL MORTISE ___ A = 2101 ___ B = 2102 ___ D = 2104 ___ E = 2105 ___ F = 2106 KIK ___ A = Standard Tail ___ B = Classroom Tail ___ C = i-Que Electronic IC CORE ___ A = 6 Pin IC ___ B = 7 Pin IC	KEYING ___ 0 = "0" Bitted ___ 1 = KD ___ 2 = KA ___ 3 = CMK ___ 4 = GMK ___ 5 = MK ___ 6 = GGMK	UL or NON-UL ___ U = UL 437 ___ N = NON UL	KEYING ___ 0 = "0" Bitted ___ 1 = 1 Key ___ 2 = 2 Keys ___ 3 = 3 Keys Up to 9, Then as separate line item

HI-SECURITY™
Cylinders

How To Order Example for HI-SECURITY™ Keys				
HS	6	D	001	C
1. Key Type	2. Pins	3. Keyway	4. Security Code	5. Special Key Type
KEY TYPE ___ HS = HI-SECURITY™ ___ RS = IC Core	PINS ___ 5 Pin ___ 6 Pin ___ 7 Pin	KEYWAY ___ D = HS	SECURITY CODE ___ 001 = Marks	SPECIAL KEY TYPE ___ C = Control Key

HI-SECURITY™ CYLINDERS






KEYS, CAMS & TAILPIECES

KEYS			
	PART #	DESCRIPTION	PRICE
	HS5D001	5 Pin Key Blank	13.16
	HS6D001	6 Pin Key Blank	13.16
	RS6D001	6 Pin SFIC Key Blank	13.16
	RS7D001	7 Pin SFIC Key Blank	13.16
	Schlage® IC CORE CONTROL KEY		
	HSR3184	Control Key Blank	13.16
CUT KEYS			
Conventional Cylinder			17.94
SFIC Core Cylinder			17.94

KEYING CHARGES			
PART #	DESCRIPTION	REG PRICE	IC CORE
KA, KD	Keyed Alike, Keyed Different	NC	NC
MK	Master Keyed	17.94	20.34
GMK	Grand Master Keyed	17.94	20.34
GGMK	Great Grand Master Keyed	17.94	20.34
VKC	Visual Key Control	14.35	

MORTISE CYLINDER CAMS			
PART #		DESCRIPTION	PRICE
	2101HS	Straight Cam	9.08
	2102HS	Clover Cam	9.08
	2104HS	Adams Rite Cam	9.08
	2105HS	J - Cam	9.08
	2106HS	G - Cam	9.08
	2107-CLHS	Straight Cam	9.08

Schlage® LARGE FORMAT IC CORE HOUSING CAMS			
PART #		DESCRIPTION	PRICE
	2101 HSPM	Straight Cam	9.08
	2102 HSPM	Clover Cam	9.08
	2104 HSPM	Adams Rite Cam	9.08
	2105 HSPM	J - Cam	9.08
	2106 HSPM	G - Cam	9.08
	2107-CL HSPM	Straight Cam	9.08

CYLINDRICAL TAIL PIECES			
PART #		FUNCTIONS	PRICE
	F1903-C	AB, DW, F	7.68
	F1903S-C	S, DA, DB, DC, SB, T	7.68
IC CORE TAILPIECES			
	HR1984-HS	AB, B, DA (ext.), DW, F, FEU, FEL	7.68
	HR1984S-HS	S, DA (int.), DB, DC, SB, T	7.68

HI-SECURITY™
Cylinders

HI-SECURITY™ CYLINDERS



PARTS LIST

PARTS LIST			
PART #	DESCRIPTION	PRICE	PACKED
P2031	Finger Pins #1 (Silver)	36.31	25 per pack
P2032	Finger Pins #2 (Copper)	36.31	25 per pack
P2033	Finger Pins #3 (Black)	36.31	25 per pack
P2034	Finger Pins #4 (Gold)	36.31	25 per pack
P2035	Sidebar - Schlage® IC	36.31	25 per pack
P2036	Sidebar - Combo, KIK, Mortise	36.31	25 per pack
P2051	Sidebar - Best® IC	36.31	25 per pack
P2037	Sidebar Springs	36.31	50 per pack
P2044	Mortise Cam Screws	20.95	12 per pack
P2045	IC Mortise Cam Screws - SCHLAGE® ONLY	20.95	12 per pack
P2041	Schlage® IC Cap Pin	36.31	12 per pack
P2042	Schlage® IC Cap Pin Spring	36.31	12 per pack
P2046	Schlage® IC Screw Cap	36.31	6 per pack
P2048	KIK Screw Cap	36.31	6 per pack
P2043	Best® IC Clip	36.31	12 per pack
P2039	Top Hex Screws (HI-SECURITY™ Mortise)	20.95	12 per pack
P2029	Top Hex Screws (HI-SECURITY™ Best® IC)	20.95	12 per pack
P2047	HI-SECURITY™ Registration Card	55.37	10 cards
R2984	7 Pin IC Tailpiece (AB, DW, F)	8.38	–
R2984S	7 Pin IC Tailpiece (S, DA, DB, DC, SB, T, TS)	8.38	–
R1981	Spacer	8.38	–
2049	Plug Holder	55.37	–
HSICT	Shear Tool	314.88	–
HSC387	HPC Card C387	69.82	–

SERIES M9900 EXIT DEVICE

RIM MOUNT



- EXTRUSION HEAVY GAGE 32D FINISH
- LIFETIME MECHANICAL WARRANTY

- PANIC PROTECTOR™ END CAP
- EASY INSTALLATION, ECONOMICAL




MARKS #	FUNCTION	PRICE	
		32D	19
M9900	Rim Panic	516.58	600.84
M9900F	Fire Rated Rim Panic	582.34	667.25
M9900H	Hurricane Rated Rim Panic	582.34	667.25
M9900 - 48	Rim Panic - 48"	569.19	654.09
M9900F - 48	Fire Rated Rim Panic - 48"	637.35	722.25
M9900H-48	Hurricane Rated Rim Panic - 48"	637.35	722.25

INFORMATION	
M9900	33" Length for 38" Door
M9900-48"	42" Length for 48" Door

SPECIFICATIONS
• Doors: 1 3/4" thick standard • End Cover: Stainless steel beveled "Panic Protector" design • Strike: Roller strike • Rail Assembly: Heavy Gauge Stainless Steel • Dead latch Bolt: Stainless Steel 3/4" throw. • Dead latch Bolt: Stainless Steel 5/8". • Dogging feature: Allen Key (M9900) • UL listed: For "Panic Hardware" and Fire Rated Model 3 hour fire doors up to 38" x 86". • ANSI: ANSI 156.3 (2001), requirements for Grade 1 • 3 Hour Fire Rating

SERIES M9900 VR EXIT DEVICE

SURFACE VERTICAL ROD



MARKS #	FUNCTION	PRICE	
		32D	19
M9900 VR	Rim Panic Vertical Rod	686.38	764.10
M9900F VR	Fire Rated Rim Panic Vertical Rod	754.54	839.44
M9900 - 48 VR	Rim Panic Vertical Rod - 48"	719.54	804.76
M9900F - 48 VR	Fire Rated Rim Panic Vertical Rod - 48"	788.02	868.14

SPECIFICATIONS
• Device Head Cover: Zinc alloy or stainless steel • Chassis: Steel, plated • Mechanism Housing: Extruded aluminum • Push Bar Base: Extruded aluminum • Touch Plate: Stainless Steel • End Cap: Stainless Steel • Top Latch: Stainless Steel 37/64" (14.8mm) • Top Strike: Included • Bottom Latch: Stainless Steel 37/64" (14.8mm) • Bottom Strike: Included • Latch Case Covers: Steel, stainless steel or brass • Vertical Rods: Aluminum tube • Hand: Non-handed • Mounting: Machine screws standard. Sex bolts optional. Order "SNB" for wood or unreinforced metal doors • Dogging: Allen-type key furnished • Outside Trim: Order separately • Standard Height: 7' doors • UL listed: ANSI/BHMA Grade 1 Panic Exit Hardware • 3-Hour Fire Rated

APPLICATION
• For use on single door or pair of doors • 1 3/4" (44 mm) door thickness standard. Specify thickness other than 1 3/4" • RHR or LHR hollow metal, wood and mineral core doors • Minimum Stile Width: 3 1/2" (89 mm)

SERIES M9900 EXTERIOR TRIM

M411	Lever/Rose	Rim Panic Vandal Pull
	 M195F	 MVP/32D
MES600A	Cylindrical Dogging Kit - 32D	Rim Panic Vandal Pull w/ cylinder hole
	 M9901	 MVPCC/32D (cylinder not included)

MARKS #	DESCRIPTION	PRICE	
		26D	19
M411	Finger Pill - no cylinder	30.32	34.27
MESC600A	Lever / Escutcheon Trim Entry	174.02	230.71
MESC600F	Lever / Escutcheon Trim Storeroom	174.02	230.71
MESC600N	Lever / Escutcheon Trim Passage	150.29	209.62
MESC600DT	Lever / Escutcheon Trim Dummy Trim	150.29	209.62
MESC600FEU/EL		967.49	
MESC350A	Lever / Escutcheon Trim Entry	174.02	
MESC350F	Lever / Escutcheon Trim Storeroom	174.02	
M9901	Panic Device Dogging Kit	108.11	129.20
MVR8	Vertical Rod 8 ft - Code 8	54.05	61.19
MVR10	Vertical Rod 10 ft - Code 10	87.02	96.04
MVRB	Vertical Rod - Bottom Rod	36.91	
MVRT	Vertical Rod - Top Rod	36.91	
MVP/32D	Rim Panic Vandal Pull	498.71	
MVPCC/32D	Rim Panic Vandal Pull w/ cylinder hole	565.20	
M9927	HEX DOGGING MECHANISM (M9900)	52.50	
M8827	HEX DOGGING MECHANISM (M8800)	52.50	
M9915	ROLLER STRIKE	42.00	
M9907	CAM FOR MESC6000A ENTRY	6.65	
M9908	CAM FOR MESC6000F STOREROOM	6.65	
R2183/26D-9	IC CORE HOUSING FOR ESCF	60.75	64.40
R2183/26D-10	IC CORE HOUSING FOR MESCA	60.75	64.40
M9917	SHORT ADAPTOR 2" DOOR	36.75	
M9916	LONG ADAPTOR 2-1/4" DOOR	36.75	
M9911	HEX DOGGING KEY 5/32"	15.75	
M9905/15	END CAP	42.00	
M9925		115.50	
DDS/32D	DOUBLE DOOR STRIKE	37.80	

MARKS #	DESCRIPTION	Price	
		32D	19
M992A/32D	Lever / Escutcheon Trim Entry	262.08	
M992F/32D	Lever / Escutcheon Trim Storeroom	262.08	
M992N/32D	Lever / Escutcheon Trim Passage	227.08	

Marks 92 and 86 levers standard, consult factory for other designs

- * Dimensions: 2 3/4" wide x 9" high . Overall depth w/Lever 2 1/8"
- * Standard Marks "C" Keyway KNK cylinder for panic device .
- Cylinder locks or unlocks lever, rigid when locked; when unlocked retracts latch bolt .
- Marks 26D Finish / Standard 1 3/4" Door Thickness • IC Prep Code G1, Less Cylinder G3
- * Thru bolt design • Non Handed design . Easily field reversible .
- Marks 32D Finish / Standard 1 3/4" Door Thickness
- Standard Marks "C" Keyway 1 1/4" Mortise cylinder with special cam
- IC Prep Code G1 • Less Cylinder G3

ENTRY LEVER TRIM

- Standard Marks "C" Keyway KNK cylinder for panic device.
- Cylinder locks or unlocks lever, rigid when locked; when unlocked retracts latch bolt.
- Marks 26D Finish / Standard 1-3/4" Door Thickness
- IC Prep Code G1, Less Cylinder G3

ESCUTCHEON LEVER DESIGN

- Thru bolt design
- Non Handed design. Easily field reversible.
- Marks 32D Finish / Standard 1-3/4" Door Thickness
- Standard Marks "C" Keyway 1-1/4" Mortise cylinder with special cam
- IC Prep Code G1
- Less Cylinder G3

ELECTRIFIED TRIM - M9900

- Available Fail Safe (EL) Fail Secure (EU)
- Standard Voltage 24VDC 150mA
- Optional 12V 250mA
- 26D Finish

MARKS #	DESCRIPTION	PRICE
		26D, 19
MESC350FEL	Fail Safe Trim 24VDC	967.80
MESC300FEU	ail Secure Trim 24VDC	967.81
MESC600FEL	Fail Safe Trim 24VDC	967.81
MESC600FEU	Fail Secure Trim 24VDC	967.81
OPTION H2	12VDC Option	NC



M992



M986

SERIES M8800 EXIT DEVICE

THIN LINE TM RIM MOUNT



*Use MESC350 for Trim

MARKS #	FUNCTION	PRICE	
		32D	19
M8800	Rim Panic	557.25	699.71
M8801		660.21	822.82

Specifications

Specification:	Conforms to ANSI BHMA A156.3 Grade 1 Exit Device Requirement Standard ANSI/UL305 Standard for Safety for Panic Hardware 2013 California Building Code Sec. 11B-309.4
For Doors:	(Please specify when ordering non standard size doors) Thickness: Standard 1 3/4", may fit with door thickness up to 2" Width: Standard 36", may fit door width 30"
Mounting:	Furnished Standard with Wood and Machine Screws
Head Cover:	Zinc Alloy
Chassis:	Aluminum
Rail Assembly:	Heavy Gauge extruded aluminum with stainless steel on top of touch bar
End Cap:	Zinc Alloy
Hand:	Non-handed
Latch Bolt:	Stainless Steel, 3/4" (18mm) throw
Strike:	Roller Strike (Stainless Steel)
Dogging:	Allen Key (equipped on panic rate devices only)
Dimension:	Touch bar height from finished floor: 41" (1041mm) from center of touch bar Touch Bar Projection: Neutral: 3 5/16" (84mm) Depressed: 2 19/32" (66mm) Head Cover: LxWxH: 206mm x 76mm x 71mm Device Length: 34 5/8" (88cm) for 36" door width

M99LD SERIES LOCKDOWN EXIT DEVICE



Clear View Visual Lockdown
Indicator on Inside Door





Exit Devices

SPECIFICATIONS:

- **Device Head Cover:** Zinc alloy
- **Chassis:** Steel, plated
- **Mechanism Housing:** Extruded aluminum
- **Push Bar Base:** Extruded aluminum
- **Touch Plate:** Solid
- **Activation:** Choice of Key or Thumbturn
- **TRIM INCLUDED**

Field-Reversible
Suits Every Application



Locked

Unlocked

MARKS #	Function	Price	
		32D	19
M99LD92	With Marks C Rim Cylinder	2125.60	2550.72
M99LD92-48	With SFIC Rim Cylinder Housing	2178.21	2613.85
M99LD86	With Cylinder hole - Less Cylinder	2125.60	2550.72
M99LD86-48	Dummy Trim	2178.21	2613.85
M992			
M986			

Options(Prep)	Code	Price
Yale/Accentra Conventional	F7	15.00
Sargent Conventional Cylinder	F8	15.00
Corbin Russwin Conventional Cylinder	F9	15.00
Corbin Russwin 6 Pin IC Core	F12*	22.00
Corbin Russwin 7 Pin IC Core	F13*	22.00
Yale/Accentra 6 Pin IC Core	F14*	15.00
Yale/Accentra 7 Pin IC Core	F15*	15.00
Schlage 6 Pin IC Core	F19*	15.00
Sargent IC Core	F20*	15.00
Medeco IC Core Large Format	F21*	15.00
Small Format IC Core	G1	0.00
Less Cylinder	G3	-10.00
T Turn	G12	0.00

*F12, F13, F14, F15, F19, F20, F21 - Specify Handing.

SERIES M195 EXIT DEVICE TRIM

Specifications


Levers: Solid cast Zamac, with 1/2" return (except 495)
Roses: Thru-bolted, 3-7/16" spring loaded Roses
Door Thickness: 1-5/8" - 1-7/8"
Clutch: Standard
Chassis: Steel
Cylinder: MARKS "C" keyway, 6 pin w/ 2 keys
 SFIC model - Core not included

Lifetime Mechanical Warranty


MARKS #	Trim	26D	19
M195S/295/495	Entry	216.21	272.89
M195RS/295/495	Entry for SFIC	216.21	272.89
M195F/295/495	Storeroom	216.21	272.89
M195RF/295/495	Storeroom for SFIC	216.21	272.89
M195N/295/495	Passage	200.39	243.89
M195DT/295/495	Dummy	200.39	243.89
M195SS/32D		574.29	

OPTIONS	CODE	PRICE - 195	295
Yale/Accentra Conventional	F7	15.00	-
Sargent conventional cylinder	F8	15.00	-
Corbin Russwin conventional cylinder	F9	15.00	-
Corbin Russwin 6 pin IC core	F12	22.00	-
Corbin Russwin 7 pin IC core	F13	22.00	-
Yale/Accentra 6 pin IC core	F14	15.00	-
Yale/Accentra 7 pin IC core	F15	15.00	-
Schlage 6 pin IC core	F19	15.00	-
Sargent IC core	F20	15.00	-
Medeco IC core large format	F21	15.00	15.00
Less Cylinder	G3	-10.00	-10.00


M195 Series Leverset



M295 Series Leversetw



M495 Series Leverset



★ **Standard & HI-SECURITY™ SFIC Models:** Interchangeable Core models for 6 or 7 pin cores (not included). **Accepts:** Marks, Marks HI-SECURITY™, Medeco®, KeyMark™, Falcon, Schlage® small format & Best®. **SFIC Tailpieces ARE Included.**



SEE PAGE 43
FOR TAILPIECES



Exit Devices

SERIES M99 NIGHT LATCH TRIM

SPECIFICATIONS

- Fixed pull for Marks USA rim panic devices.
- US32D stainless steel material
- US 32D finish
- Supplied with cylinder collar and mounting cylinder cup.
 *Available in Marks USA "C" conventional rim cylinder and Marks USA "Best size" SFIC rim cylinder (less core)
- Available in Dummy trim, less cylinder hole

MARKS #	Night Latch Trim	32D	19
M99F/32D	With Marks C Rim Cylinder	257.08	247.44
M99F/32D-G1	With SFIC Rim Cylinder Housing	257.08	247.44
M99F/32D-G3	With Cylinder hole - Less Cylinder	237.30	229.20
M99DO/32D	Dummy Trim	224.12	217.06



ELECTRIC LATCH RETRACTION

WITH SIMULTANEOUS DOGGING



DEVICE SPECIFICATIONS	
ER	Electric Latch Retraction with simultaneous dogging
For:	M9900
Operation:	Momentary or maintained latch bolt and push pad retraction. Automatic re-triggering of latch retraction
Voltage:	24VDC @ 450 mA activation, 180 mA continuous
EMC	2-station sequencer required for automatic doors only.
Monitoring Available	Latch status and REX output available

MARKS #	DESCRIPTION	32D	10B (19)
M9900ER	Electric Latch Retraction	1462.40	1525.73
M9900ER-48	Electric Latch Retraction	1517.45	1644.10
M9900 VR ER	Fire Rated Rim Panic Vertical Rod 36"	1671.70	1779.33
M8800ER	Electric Latch Retraction	1562.40	1625.20
M9900VRER-48		1711.70	1819.33

EXIT ALARM

**EMERGENCY
EXIT ONLY**
DOOR ALARM WILL SOUND



DEVICE SPECIFICATIONS	
EA	Exit Alarm, 9V battery powered
EB	Exit Alarm, 12-24V AC/DC input, 9V battery backup
For:	M9900
	100 dB alarm; visual and audible On/Off status: Armed - green LED blinks every 4 seconds, Alarm mode - red LED, Bypass - no LED - Remote status output 15 or 60 second arming delay 2 modes: Continuous alarm with manual key reset; Automatic re-arm 2 minutes after door closes with any manual key reset before 2 minutes.
Options:	- Push pad sign 6, 10 & 20 minutes alarm; 1 or 5 second re-arm delay - Remote access control, arm, disarm inputs - REX and latch status outputs

MARKS #	DESCRIPTION	PRICE
M9900EA	Exit Alarm 9VDC	1619.04
M9900EB	Exit Alarm 9VDC w 12/24 AC/DC Input	1721.92

Exit Devices

ELECTRIC DOGGING



DEVICE SPECIFICATIONS
DG Electric Dogging (failsecure) M9900, When energized by optional built-in or remote switch manual, depressing the pushpad, causes the pushpad and latch to remain retracted (unlocked) providing push-pull door operation. When de-energized or signaled by a fire alarm, the pushpad and latch are released. Voltage: 170/100 mA @ 12/24VDC Monitoring Available: Latch status and REX output available

MARKS #	DESCRIPTION	PRICE
M9900DG	Electric Dogging, Fail Secure	1721.89
P6-Rex	Request to Exit	39.26

DELAYED EGRESS

Exit Devices



DEVICE SPECIFICATIONS
DE Wall mount delayed egress controller with keypad and electrified exit device, M9900, M9900VR Example: M9900F/32D-DE DEK Keypad controller with redundant key switch capable of all keypad control features 602RF 1 Amp power supply - User PIN codes may be assigned to 1, 2 or all control functions. Reset, sustained bypass and momentary bypass (RES) - Audible alarm voice release time, warning or safety message - Visual display countdown, locked/unlocked, egress executed 15 or 30 second exit delay, 1 or 2 second nuisance delay 2 minutes Monitoring Available: Latch status available

MARKS #	DESCRIPTION	PRICE
M9900DE	Delayed Egress	4198.95
M9900KDE	Delayed Egress w Keyswitch	4494.93
M9900VRDE	Delayed Egress	4389.70
M9900VRKDE	Delayed Egress w Keyswitch	4664.73



Smart Deadbolts for Growing Multifamily

Marks USA's new line of N-Series Deadbolt Locks is the opportunity locksmiths have been waiting for—built for the booming multifamily and multitenant markets—400,000 MDU units built in 2024 alone. Designed to help you secure every door more efficiently—and profitably—these smart solutions make it easy to work with architects, builders, and property managers.

- One-motion egress keeps you ADA code compliant
- Keyless access with standalone and interconnected models
- No key distribution costs or hassles
- No cylinder to pick—for greater security
- Less expensive door prep with deadbolt strength—saving time and labor (vs mortise)
- Proven, low-maintenance design with ANSI/BHMA hardware
- Exceptional battery life—up to 3 years on AA batteries with Power-Saver circuit
- Easy management with choice of 3 native Napco Access software platforms, enterprise, cloud, PC-free or App-only; for up to 5000 users & 7K time/date audit trail
- Flexible credential options—prox, fob, smart cards, or mobile access + Construction Mode

Keyless Interconnected & Smart Deadbolts



SMART DEADBOLT & INTERCONNECTED DEADBOLT

SPECIFICATIONS

- Maximum number of Audit Lock can hold: 7000
- Maximum number of Badges: 5000
- Maximum number of Time Schedules: 254
- Maximum number of Facility Codes: 10
- Maximum number of Holidays: 30
- Estimated Battery Life is 2-5 Years
- Available in Mifare or Prox Reader
- BAA Meets guidelines of the Buy American Act F
- ADA Compliant
- Weather Resistant
- Lifetime Mechanical Warranty
- Supported by MVP EZ, MVP Access and CA4K platforms
- Finishes US15 & US19 Standard -
Additional Architectural finishes are available upon request

NDB SERIES (SMART DEADBOLT)

- Deadbolt Standard 1" (25mm)
- Throw Handling Field Reversible
- Clutching O/S turn piece design - Provides extended battery life for less maintenance

NIC SERIES (INTERCONNECT LOCKSET)

- Handing Field Reversible
- Deadbolt Standard 1" (25.4mm) Throw
- Pressing inside lever on Interconnect Series lockset will retract deadbolt and latch simultaneously
- Variety of lever designs to choose from
- Door thickness 1 3/4" standard, extended range is available
- Latch: Grade one passage 2 3/8" and 2 3/4" backsets available
- Clutching O/S turn piece design - Provides extended battery life for less maintenance




Outside Deadbolt Housing





Inside Thumb Turn w/ Matching Optional Trim

NDBTF15 shown

STANDALONE



INTERCONNECT




NICTF8615 shown

SMART DEADBOLT & INTERCONNECTED DEADBOLT

MARKS #	DESCRIPTION	15, 19
NDB	Smart Deadbolt	666.67
NIC	Interconnect Lockset	983.33
Accessories		
	Prox Card	
	Prox Fobs	
	Mifare Cards	
	Mifare Fobs	
	Gateways Gen 3	

LOCK MODEL ORDERING CONFIGURATION:




MVP EZ

- NO computer required, cloud based App
- 50 Door max.
- 200 users
- System retains last 2 months of Audit Trails
- Communicates to locks via BLE from cell phone
- Monthly subscription is required



MVP ACCESS

- 50K + doors
- Unlimited users
- Supports Alarm Lock, Architech Locks & Napco Pro Panels
- Monthly subscription is required



PLATFORM - NETWORKED ON PREMISES SERVERS

- Supports up to 5000 Key-Free Users
- Smartphone Mifare/EV1/EV2/EV3
- Manual credential enrollment capability
- Supports 254-time schedules and 30 holidays held in the lock
- Provides 7,000 Event Audit Trail, with time and date stamp of access by user (stored in the lock)
- Supports Programming via Gen 3 Network Gateways
- Long-range wireless Programming



Smart Deadbolt & Interconnected

ARCHITECH™ SERIES NETWORKX LOCKS

Ideal access control solution; elegantly blending advanced wireless access control convenience within any decor, in attractive, infinitely customizable designer locking form, in choice of trims and finishes.



N90L - Ideal for School and Campus



Back

Features


- 5000 Users, 500 Scheduled Events & 40,000 Event Audit Trail
- Surface-Mount or Mortised - in Electronics and Battery Pack
- Lock available in Mortise and Cylindrical versions
- Real Time Clock - Uses 4 AA Batteries - 3 to 4 year battery life
- Operated via access card, fob, key fob etc
- DL-Windows Software for programming
- USB Radio Key Programming Method or Via NetworkX Gateways
- Manual Card Enrollment Option for Quick Installation
- Wireless programming range: up to 20 ft. from lock
- Easily, securely networked via 802.11 or ethernet, spanning a few or thousands of doors, in one building, a campus or multiple sites in an enterprise (also available in standalone model)
- Emergency LocDown Keyfobs & Flashing Strobe Indicator, Available
- Programmable Lockdown/Unlock Privileges
- Cylindrical ArchiTech Locks neatly, quickly retrofit any standard door lock, with easy surface mount electronics, for use in all applications - Including wood and metal doors, for new and existing applications
- Customizable oval or square Access ID Reader, in black or silver and three levers to choose from - American 195, Crescent 295 & Titan 495
- Future-Proof Multi-Technology Access ID Credentials Replace Cumbersome Keys - HID® Prox, Mag Stripe, Smart Cards, PIV, keyfobs and remote buttons
- Powered by 4 off-the-shelf AA Batteries. 3 to 4 years, typ.
- Flexible System Monitoring, Control & Programming - Program locally using a USB Gateway or remotely across a wireless network (using free Alarm Lock DL-WINDOWS Windows- based software). Or, in Real-Time Enterprise platforms, using either Continental Access CA4K®, Lenel® OnGuard®

Specifications

- ANSI / BHMA Grade 1 Certified, UL Listed 3 Hours
- Includes standard lever rose hardware design
- Compatible with all 300+ optional architectural trim / lever or knob designs
- Stainless steel latch, 2-3/4" backset
- Auto-Reverse lock body tested to 6 million cycles
- Lock Body - Self cleaning long life motor
- Door closure monitor / electronic deadbolt monitor
- Key override standard or high-Security
- Optional integrated door position indicator switch

ARCHITech™ SERIES NETWORKX LOCKS

Electronics



MORTISED
NETWORKX CONTROL
MODULE

I - Inserted

J - Inserted BLE

S - Surface


T - Inserted BLE

L - Lockdown

M - Lockdown BLE

P - Privacy

Q - Privacy BLE



"SURFACE-MOUNTED" NETWORKX
CONTROL UNIT
AND ITS MOUNTING PLATE

Wired Readers



1 - Prox Oval

2 - Prox Square



A - iClass Oval

B - iClass Square



C - Concealed

(Wood or Composite doors only)



M - Multi-Class
iClass/Prox

7 - Keypad Prox

Wireless Readers



F - Oval Wireless Prox



H - Horizontal KP/Prox



V - Vertical
KP/Prox



W - Square Glass
KP/Prox



Concealed
Electronics

Mortise-In Electronics
& Batteries

Cylindrical; Surface
Mounted Electronics

Mortise; Surface
Mounted Electronics

Keypad

Architech Series
Network Locks

ARCHITECH™ SERIES NETWORK LOCKS

ArchiTech Series Cylindrical Locks

Models	Base Price	Electronics	Add On	Reader	Add On	Trim Type	Add On	Finish	Add On	Option	Add On
N90	1502.46	I	–	1	–	195	–	3	150.00	F7	15.00
R90	1502.46	J	74.93	2	–	295	–	4	80.65	F8	15.00
		S	–	7	74.93	495	–	10	80.65	F12	22.00
		T	74.93	A	74.93			10B	80.65	F13	22.00
		L	74.93	B	74.93			19	42.65	F14	15.00
		M	149.86	C	–			26	42.65	F15	15.00
		P	74.93	D	149.86			26D	–	F19	15.00
		Q	149.86	E	149.86					F20	15.00
				F	149.86					F21	15.00
				H	149.86					G3	-10.00
				V	149.86						
				W	238.00						

Choice of Levers - Cylindrical Models



195 - American Lever



295 - Crescent Lever




495 - Titan Lever

No up-charge for Marks (Best) SFIC. Specify "RF" for SFIC

*Note: Please consult factory for availability of other finishes. Round rose place only available with cylindrical version (3.5" diameter). IC core models: tail piece included, core not included.

How to order ArchiTech Cylindrical Models



Base distribution cylindrical model P/N scheme



ARCHITECH™ SERIES NETWORKX LOCKS

ArchiTech Series Mortise Locks

Models	Base Price	Electronics	Add On	Reader	Add On	Trim	Add On	Lever	Add On	Finish	Add On	Option	Add On
N95	1878.07	I	—	1	—	RQ	—	002	—	3	130.00	G1	—
R95	1878.07	J	81.30	2	—	RR	—	031	—	4	80.65	G3	-10.00
		S	—	7	81.30	RS	—	037A	—	10	80.65	G6	—
		T	81.30	A	81.30	RW	—	47C	—	10B	80.65	G7	51.00
		L	81.30	B	81.30	RX	20.26	55	—	14	49.27	G8	—
		M	162.60	C	—	RK	46.86	57	—	15	49.27		
		P	81.30	D	162.60	RL	66.49	72	—	19	49.27		
		Q	162.60	E	162.60	LA	169.51	77	—	20A	49.27		
				F	162.60	CR	119.59	78	—	26	49.27		
				H	162.60	DR	169.51	82	—	26D	—		
				V	162.60			83	—	32	—		
				W	238.00			86	—	32D	—		
								92	—				
								96	—				
								BH29	1254.77				

KNOB	Round Knob 10	Ball Knob 20	Commerce Lever 037A	Metropolitan Lever 002	ROSES	RR: 2-9/16" dia.
						
						RW: 2-9/16" dia.
						
LEVERS	Lucida Lever 47C	Copa Lever 031	Brompton Lever 55	Monaco Lever 57 Specify handing	ROSES	RQ: 2-1/4" dia.
						
	Towne Lever 72	Maxwell Lever 77	Omni Lever 78	Plaza Lever 82		RS: 2-1/4" dia.
						
LEVERS	Dayton Lever 83 Specify handing	Crescent Lever 86	American Lever 92	Titan Lever 96	ROSES	RX: 2-1/2"sq.
						RK: 2-1/2"sq.
						RL: 1-1/2"sq.
						

ArchiTech Series
Network Locks


Functions for Mortise Locks

CODE	FUNCTION	DESCRIPTION
FD	APARTMENT	Latch by lever either side except when outside locked by stop-button or projected deadbolt. Latch deadlocked by auxiliary latch or deadbolt & latch by key outside. Deadbolt by turn piece inside. Inside knob/lever retracts latch & deadbolt simultaneously, leaving outside locked.
E	STOREROOM	Latch by lever inside, key outside. Outside lever always rigid. Auxiliary latch deadlocks latch. Inside always open.
AD	AUTOMATIC DEADBOLT	Latch deadlocked by deadbolt automatically when door closes. Deadbolt & latch by key or redential outside. Inside lever retracts latch & deadbolt simultaneously, leaving outside locked.

ARCHITECH™ SERIES NETWORKX LOCKS

How to Order ArchiTech Mortise Models

Base distribution cylindrical model P/N scheme



	READER TYPE												
		1	2	7	A	B	C	D	E	F	H	V	W
LOCK TYPE	N90I	s/o	s/o	s/o	s/o	s/o	s/o	s/o	n/a	n/a	n/a	n/a	N/A
	N90J	s/o	s/o	s/o	s/o	s/o	s/o	s/o	n/a	n/a	n/a	n/a	N/A
	N90S	□	□	□	□	□	n/a	s/o	n/a	n/a	n/a	n/a	N/A
	N90T	□	□	□	□	□	n/a	s/o	n/a	n/a	n/a	n/a	N/A
	N90L	□	□	s/o	□	□	n/a	s/o	n/a	n/a	n/a	n/a	N/A
	N90M	s/o	s/o	s/o	s/o	s/o	n/a	s/o	n/a	n/a	n/a	n/a	N/A
	N90P	n/a	n/a	□	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	N/A
	N90Q	n/a	n/a	s/o	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	N/A
	N95I	□	□	□	□	□	□	s/o	n/a	n/a	n/a	n/a	N/A
	N95J	□	□	□	□	□	□	s/o	n/a	n/a	n/a	n/a	N/A
	N95S	□	□	□	□	□	n/a	s/o	n/a	n/a	n/a	n/a	N/A
	N95T	□	□	□	□	□	n/a	s/o	n/a	n/a	n/a	n/a	N/A
	N95L	□	□	s/o	□	□	n/a	s/o	n/a	n/a	n/a	n/a	N/A
	N95M	s/o	s/o	s/o	s/o	s/o	n/a	s/o	n/a	n/a	n/a	n/a	N/A
	N95P	n/a	n/a	s/o	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	N/A
	N95Q	n/a	n/a	s/o	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	N/A
	R90I	s/o	s/o	s/o	s/o	s/o	s/o	s/o	s/o	s/o	s/o	s/o	S/O
	R90J	□	□	s/o	s/o	s/o	s/o	s/o	s/o	s/o	s/o	s/o	S/O
	R90S	□	□	s/o	s/o	s/o	n/a	s/o	s/o	s/o	s/o	s/o	S/O
	R90T	□	□	s/o	s/o	s/o	n/a	s/o	s/o	s/o	s/o	s/o	S/O
	R90L	□	□	s/o	s/o	s/o	n/a	s/o	s/o	s/o	s/o	s/o	S/O
	R90M	s/o	s/o	s/o	s/o	s/o	n/a	s/o	s/o	s/o	s/o	s/o	S/O
	R90P	n/a	n/a	□	n/a	n/a	n/a	n/a	s/o	s/o	s/o	s/o	S/O
	R90Q	n/a	n/a	s/o	n/a	n/a	n/a	n/a	s/o	s/o	s/o	s/o	S/O
	R95I	□	□	□	□	□	□	s/o	s/o	s/o	s/o	ü	□
	R95J	□	□	□	□	□	□	s/o	s/o	s/o	s/o	ü	□
	R95S	□	□	□	□	□	n/a	s/o	s/o	s/o	s/o	ü	□
	R95T	□	□	□	□	□	n/a	s/o	s/o	s/o	s/o	ü	□
	R95L	□	□	s/o	□	□	n/a	s/o	s/o	s/o	s/o	s/o	S/O
	R95M	s/o	s/o	s/o	s/o	s/o	n/a	s/o	s/o	s/o	s/o	s/o	S/O
	R95P	n/a	n/a	s/o	n/a	n/a	n/a	n/a	s/o	s/o	s/o	s/o	S/O
	R95Q	n/a	n/a	s/o	n/a	n/a	n/a	n/a	s/o	s/o	s/o	s/o	S/O

ARCHITECH™ SERIES NETWORKX LOCKS

ArchiTech™ Series Networkx Locks Parts and Accessories

PRODUCT	DESCRIPTION	PRICE
AL-IME2EXP	Wireless Expander designed to expand the coverage area of version 2 gateways. AC power required. Up to 7 expanders per version 2 gateway	426.83
AL-IME2-PIE	Plug-in wireless expander, as above – Plugs into standard AC outlet	426.83
AL-IME-USB	USB Gateway (not for lockdown)	903.88
AL-PRE2	Prox card enroller – HID and iClass	1057.70
AL-NSM	Networkx Signal Meter	505.37
AL-NSG	Networkx Signal Generator	409.76
AL-PB	ArchiTech Power Booster	2212.71
ALHID1326	Proximity Access Cards 100 Per Box	591.41
ALHID1391	MicroProx Tag 10 per box	147.00
AL-IM3-80211	3rd Generation Hardware/Wireless Gateway	810.98
AL-IM3-POE	3rd Generation Hardware/Wireless POE Gateway	981.72
KH-36-10	Napco Branded Keyfob 10 pack	48.90
AL-4BKEYFOB	4 Button Remote Fob	190.85
AL-NETHIDNSPACK	Net Panel with HID reader	1609.84
AL-IDRW	Card Write-ReWriter	1057.70

Use the iLock® App to unlock your Networkx ArchiTech™ Bluetooth® Series Door Lock in seconds!



Introducing iLock, the easy smartphone mobile solution for unlocking your Trilogy® ArchiTech Bluetooth Series Designer Access Control Locks from any smart device without the need to carry cumbersome ID cards or keys. Password protected access is secure through the use of Bluetooth LE® and proprietary encryption. Additionally, an optional feature can be utilized, requiring a password for each unlock request.

The Key is Your Smartphone & More Secure Technology

Any Smart Device can be the Access Key: Much more than an ID card displayed on your smartphone, for your security, ArchiTech & its iLock App are wirelessly linked together, each supplying its portion of stored encrypted data to provide secure access without a key, fuss or worry, ensuring user identities. A unique combination of convenience



and cloneproof peace of mind, the ArchiTech platform uses universally-compatible Bluetooth LE technology, so they can use any smart device to unlock ArchiTech on your door(s); and do so from afar, at a comfortable, customizable range of up to 30 feet away. For even greater security users can add an optional passcode, entered on their phone App.

ArchiTech Series
Networkx Locks

iLock App is available from both iTunes and the Google Play Store

This page intentionally left blank.

This page intentionally left blank.



MARKSUSA

AMITYVILLE, N.Y. 11701

Effective July 1, 2026

DISTRIBUTED BY



800-645-9445 • www.marksusa.com • sales@marksusa.com

Marks USA is a Division of NAPCO Security Technologies, Inc. (NASDAQ: NSSC) • NAPCO • Alarm Lock • Continental Access • Marks USA
ArchiTech, LifeSaver, Survivor, Hi-Security, LocDown, Thinline, MVP EZ, MV Access, CA4K and Unilock are trademarks of Marks/NAPCO. Other trademarks listed are properties of their respective companies.
All prices published are suggested list prices in US Dollars. Some specifications are preliminary & subject to change without prior notice (Subsequent Tariffs/Surcharges May Apply).
Not responsible for typographical errors. Marks USA is a Division of Napco Security Technologies, Inc. (NASDAQ:NSSC) © NAPCO 10.1.25