

USE ON INSIDE
("PROTECTED SIDE") OF WOOD
OR METAL DOORS
MOUNTING TEMPLATE FOR THE
"SURFACE-MOUNTED
NETWORKX CONTROL MODULE"
(FOR CYLINDRICAL LOCKS)

Use this template to mount the "Surface-Mounted Networkx Control Module".
Note: The wire hole for the Surface-Mounted Networkx Control Module is located 5-5/32" from the "HORIZONTAL CENTER LINE OF LEVER" as shown.

IMPORTANT
WHEN PRINTING OR PHOTO-COPYING A TEMPLATE, ALWAYS SELECT PRINTING OPTIONS TO ENSURE THAT COPIES ARE PRODUCED WITHOUT SIZE ADJUSTMENTS.
VERIFY THE DIMENSIONS OF THIS BOX ARE 2.000 X 2.000 INCHES ± 0.010.

FOLD HERE AND
ALIGN TEMPLATE
ON HIGH EDGE OF
DOOR BEVEL (LONG
SIDE OF DOOR)

For installation on UL Listed Wood Fire Doors fill the through hole wire passage with UL Classified Fire Stop Sealant after connecting all wiring and testing the Lock

FOLD HERE AND
ALIGN TEMPLATE ON
LOW EDGE OF DOOR
BEVEL (SHORT SIDE
OF DOOR)

